

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0812	Air Core Coil	0,005mH +/-5% 0,06Ω wire 0,80mm=20AWG OD-9 / 8mm	0,005	0,060	0,80	20	9	9	8	0,004
000-1619	Air Core Coil	0,005mH +/-5% 0,013Ω wire 1,60mm=14AWG OD-18 / 25mm	0,005	0,013	1,60	14	8	18	25	0,033
000-1581	Air Core Coil	0,007mH +/-5% 0,03Ω wire 1,20mm=17AWG OD-28 / 10mm	0,007	0,030	1,20	17	20	28	10	0,015
000-1589	Air Core Coil	0,007mH +/-5% 0,15Ω wire 0,40mm=26AWG OD-11 / 8mm	0,007	0,150	0,40	26	9	11	8	0,002
000-0051	Air Core Coil	0,008mH +/-5% 0,016Ω wire 1,60mm=14AWG OD-18 / 25mm	0,008	0,016	1,60	14	8	18	25	0,033
000-0045	Air Core Coil	0,010mH +/-5% 0,020Ω wire 1,60mm=14AWG OD-21 / 25mm	0,010	0,020	1,60	14	8	21	25	0,037
000-0849	Air Core Coil	0,010mH +/-5% 0,06Ω wire 1,80mm=13AWG OD-23 / 20mm	0,010	0,060	1,80	13	8	23	20	0,047
000-1557	Air Core Coil	0,010mH +/-5% 0,070Ω wire 0,80mm=20AWG OD-14 / 25mm	0,010	0,070	0,80	20	8	14	25	0,010
000-1633	Air Core Coil	0,010mH +/-5% 0,025Ω wire 1,40mm=15AWG OD-17 / 25mm	0,010	0,025	1,40	15	8	17	25	0,032
000-1251	Air Core Coil	0,012mH +/-5% 0,025Ω wire 1,40mm=15AWG OD-17 / 25mm	0,012	0,025	1,40	15	8	17	25	0,032
000-1790	Air Core Coil	0,015mH +/-5% 0,080Ω wire 0,80mm=20AWG OD-14 / 25mm	0,015	0,080	0,80	20	8	14	25	0,012
000-0722	Air Core Coil	0,016mH +/-5% 0,05Ω wire 1,00mm=18AWG OD-29 / 15mm	0,016	0,050	1,00	18	25	29	15	0,019
000-0176	Air Core Coil	0,020mH +/-5% 0,028Ω wire 1,60mm=14AWG OD-24 / 25mm	0,020	0,028	1,60	14	8	24	25	0,057
000-0193	Air Core Coil	0,020mH +/-5% 0,04Ω wire 1,20mm=17AWG OD-34 / 15mm	0,020	0,040	1,20	17	25	34	15	0,029
000-0813	Air Core Coil	0,020mH +/-5% 0,10Ω wire 0,80mm=20AWG OD-19 / 8mm	0,020	0,100	0,80	20	9	19	8	0,009
000-1233	Air Core Coil	0,020mH +/-5% 0,105Ω wire 0,63mm=22AWG OD-15 / 8mm	0,020	0,105	0,63	22	9	15	8	0,006
000-1522	Air Core Coil	0,020mH +/-5% 0,090Ω wire 0,80mm=20AWG OD-14 / 25mm	0,020	0,090	0,80	20	8	14	25	0,013
000-0190	Air Core Coil	0,025mH +/-5% 0,040Ω wire 1,40mm=15AWG OD-38 / 15mm	0,025	0,035	1,40	15	25	36	15	0,050
000-0192	Air Core Coil	0,025mH +/-5% 0,04Ω wire 1,20mm=17AWG OD-34 / 15mm	0,025	0,040	1,20	17	25	34	15	0,032
000-1532	Air Core Coil	0,025mH +/-5% 0,132Ω wire 0,70mm=21AWG OD-13 / 25mm	0,025	0,132	0,70	21	8	13	25	0,011
000-1804	Air Core Coil	0,025mH +/-5% 0,060Ω wire 1,00mm=18AWG OD-31 / 15mm	0,025	0,060	1,00	18	25	31	15	0,021
000-0834	Air Core Coil	0,028mH +/-5% 0,29Ω wire 0,40mm=26AWG OD-12 / 8mm	0,028	0,290	0,40	26	9	12	8	0,003
000-0060	Air Core Coil	0,030mH +/-5% 0,040Ω wire 1,60mm=14AWG OD-30 / 25mm	0,030	0,040	1,60	14	8	30	25	0,087
000-0729	Air Core Coil	0,030mH +/-5% 0,07Ω wire 1,00mm=18AWG OD-31 / 15mm	0,030	0,060	1,00	18	25	31	15	0,022
000-0814	Air Core Coil	0,030mH +/-5% 0,12Ω wire 0,80mm=20AWG OD-20 / 8mm	0,030	0,120	0,80	20	9	20	8	0,012
000-0949	Air Core Coil	0,030mH +/-5% 0,049Ω wire 1,20mm=17AWG OD-34 / 15mm	0,030	0,049	1,20	17	25	34	15	0,034
000-1523	Air Core Coil	0,030mH +/-5% 0,120Ω wire 0,80mm=20AWG OD-15 / 25mm	0,030	0,120	0,80	20	8	15	25	0,016
000-1805	Air Core Coil	0,030mH +/-5% 0,290Ω wire 0,40mm=26AWG OD-12 / 8mm	0,030	0,290	0,40	26	9	12	8	0,003
000-0171	Air Core Coil	0,033mH +/-5% 0,07Ω wire 1,00mm=18AWG OD-29 / 8mm	0,033	0,070	1,00	18	15	29	8	0,023
000-1599	Air Core Coil	0,033mH +/-5% 0,22Ω wire 0,50mm=24AWG OD-15 / 8mm	0,033	0,240	0,50	24	9	15	8	0,005
000-1544	Air Core Coil	0,035mH +/-5% 0,150Ω wire 0,63mm=22AWG OD-17 / 8mm	0,035	0,150	0,63	22	9	17	8	0,008
000-0920	Air Core Coil	0,037mH +/-5% 0,058Ω wire 1,20mm=17AWG OD-34 / 15mm	0,037	0,058	1,20	17	25	34	15	0,036
000-1794	Air Core Coil	0,037mH +/-5% 0,14Ω wire 0,70mm=21AWG OD-20 / 15mm	0,037	0,140	0,70	21	15	20	15	0,013
000-0727	Air Core Coil	0,040mH +/-5% 0,09Ω wire 1,00mm=18AWG OD-25 / 15mm	0,040	0,090	1,00	18	15	25	15	0,028
000-1110	Air Core Coil	0,040mH +/-5% 0,13Ω wire 0,80mm=20AWG OD-21 / 8mm	0,040	0,130	0,80	20	9	21	8	0,014
000-1806	Air Core Coil	0,040mH +/-5% 0,240Ω wire 0,50mm=24AWG OD-15 / 8mm	0,040	0,240	0,50	24	9	15	8	0,005
000-1902	Air Core Coil	0,040mH +/-5% 0,040Ω wire 1,40mm=15AWG OD-38 / 15mm	0,040	0,040	1,40	15	25	38	15	0,055
000-0251	Air Core Coil	0,044mH +/-5% 0,09Ω wire 1,00mm=18AWG OD-25 / 15mm	0,044	0,090	1,00	18	15	25	15	0,028
000-0939	Air Core Coil	0,045mH +/-5% 0,090Ω wire 1,00mm=18AWG OD-25 / 15mm	0,045	0,090	1,00	18	15	25	15	0,028
000-1318	Air Core Coil	0,047mH +/-5% 0,170Ω wire 0,70mm=21AWG OD-20 / 15mm	0,047	0,170	0,70	21	15	20	15	0,013
000-0001	Air Core Coil	0,050mH +/-5% 0,046Ω wire 1,60mm=14AWG OD-30 / 25mm	0,050	0,046	1,60	14	8	30	25	0,096
000-0101	Air Core Coil	0,050mH +/-5% 0,038Ω wire 1,80mm=13AWG OD-32 / 25mm	0,050	0,038	1,80	13	8	32	25	0,121
000-0191	Air Core Coil	0,050mH +/-5% 0,05Ω wire 1,40mm=15AWG OD-40 / 15mm	0,050	0,050	1,40	15	25	40	15	0,060
000-0831	Air Core Coil	0,043mH +/-5% 0,060Ω wire 1,20mm=17AWG OD-34 / 15mm	0,050	0,060	1,20	17	25	34	15	0,046
000-0918	Air Core Coil	0,050mH +/-5% 0,124Ω wire 0,80mm=20AWG OD-23 / 8mm	0,050	0,124	0,80	20	9	23	8	0,016
000-1024	Air Core Coil	0,050mH +/-5% 0,060Ω wire 1,20mm=17AWG OD-34 / 15mm	0,050	0,060	1,20	17	25	34	15	0,046
000-1106	Air Core Coil	0,050mH +/-5% 0,260Ω wire 0,50mm=24AWG OD-15 / 8mm	0,050	0,260	0,50	24	9	15	8	0,006
000-1428	Air Core Coil	0,050mH +/-5% 0,178Ω wire 0,63mm=22AWG OD-18 / 8mm	0,050	0,178	0,63	22	9	18	8	0,010
000-1603	Air Core Coil	0,050mH +/-5% 0,170Ω wire 0,70mm=21AWG OD-21 / 15mm	0,050	0,170	0,70	21	15	21	15	0,014
000-1947	Air Core Coil	0,050mH +/-5% 0,090Ω wire 1,00mm=18AWG OD-33 / 15mm	0,050	0,090	1,00	18	25	33	15	0,031
000-1963	Air Core Coil	0,050mH +/-5% 0,090Ω wire 1,00mm=18AWG OD-25 / 15mm	0,050	0,090	1,00	18	15	25	15	0,029
000-0150	Air Core Coil	0,055mH +/-5% 0,170Ω wire 0,70mm=21AWG OD-25 / 8mm	0,055	0,170	0,70	21	15	25	8	0,013



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0870	Air Core Coil	0,055mH +/-5% 0,090Ω wire 1,00mm=18AWG OD-25 / 15mm	0,055	0,090	1,00	18	15	25	15	0,029
000-0980	Air Core Coil	0,057mH +/-5% 0,77Ω wire 0,30mm=29AWG OD-17 / 8mm	0,057	0,770	0,30	29	15	17	8	0,003
000-1053	Air Core Coil	0,060mH +/-5% 0,135Ω wire 0,80mm=20AWG OD-23 / 8mm	0,060	0,135	0,80	20	9	23	8	0,018
000-1903	Air Core Coil	0,060mH +/-5% 0,170Ω wire 0,70mm=21AWG OD-25 / 8mm	0,060	0,170	0,70	21	15	25	8	0,014
000-0741	Air Core Coil	0,065mH +/-5% 0,10Ω wire 1,00mm=18AWG OD-33 / 8mm	0,065	0,100	1,00	18	15	33	8	0,032
000-0828	Air Core Coil	0,068mH +/-5% 0,10Ω wire 1,00mm=18AWG OD-33 / 8mm	0,068	0,100	1,00	18	15	33	8	0,032
000-1693	Air Core Coil	0,070mH +/-5% 0,120Ω wire 1,00mm=18AWG OD-35 / 15mm	0,070	0,120	1,00	18	25	35	15	0,038
000-1694	Air Core Coil	0,070mH +/-5% 0,108Ω wire 1,00mm=18AWG OD-33 / 8mm	0,070	0,108	1,00	18	15	33	8	0,032
000-1807	Air Core Coil	0,070mH +/-5% 0,330Ω wire 0,50mm=24AWG OD-16 / 8mm	0,070	0,330	0,50	24	9	16	8	0,007
000-0997	Air Core Coil	0,074mH +/-5% 0,290Ω wire 0,63mm=22AWG OD-24 / 8mm	0,074	0,290	0,63	22	15	24	8	0,012
000-1069	Air Core Coil	0,075mH +/-5% 0,185Ω wire 0,70mm=21AWG OD-25 / 8mm	0,075	0,185	0,70	21	15	25	8	0,016
000-1426	Air Core Coil	0,075mH +/-5% 0,157Ω wire 0,80mm=20AWG OD-25 / 8mm	0,075	0,157	0,80	20	9	25	8	0,021
000-0730	Air Core Coil	0,080mH +/-3% 0,08Ω wire 1,20mm=17AWG OD-38 / 15mm	0,080	0,080	1,20	17	25	38	15	0,065
000-0839	Air Core Coil	0,080mH +/-5% 0,98Ω wire 0,30mm=29AWG OD-18 / 8mm	0,080	0,980	0,30	29	15	18	8	0,003
000-1028	Air Core Coil	0,080mH +/-5% 0,120Ω wire 1,00mm=18AWG OD-35 / 15mm	0,080	0,120	1,00	18	25	35	15	0,038
000-1154	Air Core Coil	0,080mH +/-5% 0,157Ω wire 0,80mm=20AWG OD-25 / 8mm	0,080	0,157	0,80	20	9	25	8	0,022
000-1517	Air Core Coil	0,080mH +/-5% 0,200Ω wire 0,70mm=21AWG OD-25 / 8mm	0,080	0,200	0,70	21	15	25	8	0,016
000-1534	Air Core Coil	0,080mH +/-5% 0,060Ω wire 1,40mm=15AWG OD-39 / 20mm	0,080	0,060	1,40	15	25	39	20	0,084
000-1808	Air Core Coil	0,082mH +/-5% 0,370Ω wire 0,50mm=24AWG OD-17 / 8mm	0,082	0,370	0,50	24	9	17	8	0,008
000-1032	Air Core Coil	0,085mH +/-5% 0,120Ω wire 1,00mm=18AWG OD-35 / 15mm	0,085	0,122	1,00	18	25	35	15	0,038
000-0881	Air Core Coil	0,090mH +/-5% 0,229Ω wire 0,70mm=21AWG OD-22 / 15mm	0,090	0,229	0,70	21	15	22	15	0,018
000-0922	Air Core Coil	0,090mH +/-5% 0,378Ω wire 0,50mm=24AWG OD-17 / 8mm	0,090	0,378	0,50	24	9	17	8	0,008
000-1141	Air Core Coil	0,090mH +/-5% 0,210Ω wire 0,70mm=21AWG OD-26 / 8mm	0,090	0,210	0,70	21	15	26	8	0,017
000-1646	Air Core Coil	0,090mH +/-5% 0,130Ω wire 1,00mm=18AWG OD-29 / 15mm	0,090	0,130	1,00	18	15	29	15	0,043
000-0002	Air Core Coil	0,100mH +/-3% 0,067Ω wire 1,60mm=14AWG OD-35 / 25mm	0,100	0,067	1,60	14	8	35	25	0,140
000-0102	Air Core Coil	0,100mH +/-3% 0,055Ω wire 1,80mm=13AWG OD-39 / 25mm	0,100	0,055	1,80	13	8	39	25	0,177
000-0206	Air Core Coil	0,100mH +/-3% 0,18Ω wire 1,00mm=18AWG OD-21 / 40mm	0,100	0,180	1,00	18	10	21	40	0,056
000-0241	Air Core Coil	0,100mH +/-3% 0,58Ω wire 0,40mm=26AWG OD-15 / 8mm	0,100	0,580	0,40	26	9	15	8	0,006
000-0951	Air Core Coil	0,100mH +/-3% 0,10Ω wire 1,20mm=17AWG OD-33 / 15mm	0,100	0,096	1,20	17	15	33	15	0,063
000-1002	Air Core Coil	0,100mH +/-3% 0,190Ω wire 0,80mm=20AWG OD-31 / 10mm	0,100	0,190	0,80	20	20	31	10	0,026
000-1148	Air Core Coil	0,100mH +/-3% 0,260Ω wire 0,70mm=21AWG OD-24 / 8mm	0,100	0,260	0,70	21	9	24	8	0,019
000-1149	Air Core Coil	0,100mH +/-3% 0,190Ω wire 0,80mm=20AWG OD-27 / 8mm	0,100	0,190	0,80	20	9	27	8	0,025
000-1234	Air Core Coil	0,100mH +/-3% 0,120Ω wire 1,00mm=18AWG OD-35 / 10mm	0,100	0,120	1,00	18	20	35	10	0,042
000-1237	Air Core Coil	0,100mH +/-3% 0,260Ω wire 0,70mm=21AWG OD-30 / 15mm	0,100	0,260	0,70	21	25	30	15	0,021
000-1361	Air Core Coil	0,100mH +/-3% 0,330Ω wire 0,70mm=21AWG OD-29 / 30mm	0,100	0,330	0,70	21	25	29	30	0,025
000-1449	Air Core Coil	0,100mH +/-3% 0,190Ω wire 0,80mm=20AWG OD-24 / 15mm	0,100	0,190	0,80	20	15	24	15	0,026
000-1463	Air Core Coil	0,100mH +/-3% 0,290Ω wire 0,63mm=22AWG OD-25 / 8mm	0,100	0,290	0,63	22	15	25	8	0,014
000-1533	Air Core Coil	0,100mH +/-3% 0,117Ω wire 1,20mm=17AWG OD-34 / 30mm	0,100	0,117	1,20	17	25	34	30	0,070
000-1535	Air Core Coil	0,100mH +/-3% 0,075Ω wire 1,40mm=15AWG OD-43 / 15mm	0,100	0,075	1,40	15	25	43	15	0,089
000-1536	Air Core Coil	0,100mH +/-3% 0,160Ω wire 1,00mm=18AWG OD-31 / 30mm	0,100	0,160	1,00	18	25	31	30	0,050
000-1580	Air Core Coil	0,100mH +/-3% 0,08Ω wire 1,40mm=15AWG OD-36 / 30mm	0,100	0,082	1,40	15	25	36	30	0,102
000-1751	Air Core Coil	0,100mH +/-3% 0,580Ω wire 0,50mm=24AWG OD-19 / 27mm	0,100	0,580	0,50	24	15	19	27	0,012
000-1752	Air Core Coil	0,100mH +/-3% 0,290Ω wire 0,70mm=21AWG OD-20 / 27mm	0,100	0,290	0,70	21	15	20	27	0,024
000-1801	Air Core Coil	0,100mH +/-3% 0,230Ω wire 0,70mm=21AWG OD-26 / 8mm	0,100	0,230	0,70	21	15	26	8	0,018
000-1809	Air Core Coil	0,100mH +/-3% 0,440Ω wire 0,50mm=24AWG OD-21 / 8mm	0,100	0,440	0,50	24	15	21	8	0,009
000-1810	Air Core Coil	0,100mH +/-3% 0,090Ω wire 1,20mm=17AWG OD-38 / 15mm	0,100	0,090	1,20	17	25	38	15	0,065
000-1900	Air Core Coil	0,100mH +/-3% 0,250Ω wire 0,70mm=21AWG OD-22 / 15mm	0,100	0,250	0,70	21	15	22	15	0,019
000-1948	Air Core Coil	0,100mH +/-3% 0,130Ω wire 1,00mm=18AWG OD-35 / 15mm	0,100	0,130	1,00	18	25	35	15	0,044
000-1964	Air Core Coil	0,100mH +/-3% 0,130Ω wire 1,00mm=18AWG OD-29 / 15mm	0,100	0,130	1,00	18	15	29	15	0,042
000-1617	Air Core Coil	0,107mH +/-5% 0,630Ω wire 0,40mm=26AWG OD-15 / 8mm	0,107	0,630	0,40	26	9	15	8	0,006
000-1620	Air Core Coil	0,107mH +/-5% 0,100Ω wire 1,20mm=17AWG OD-38 / 15mm	0,107	0,100	1,20	17	25	38	15	0,067
000-0177	Air Core Coil	0,110mH +/-3% 0,44Ω wire 0,50mm=24AWG OD-22 / 8mm	0,110	0,440	0,50	24	15	22	8	0,010

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0894	Air Core Coil	0,110mH +/-3% 0,430Q wire 0,50mm=24AWG OD-18 / 8mm	0,110	0,430	0,50	24	9	18	8	0,009
000-0895	Air Core Coil	0,110mH +/-5% 1,14Q wire 0,30mm=29AWG OD-18 / 8mm	0,110	1,140	0,30	29	15	18	8	0,003
000-0917	Air Core Coil	0,110mH +/-3% 0,133Q wire 1,00mm=18AWG OD-36 / 15mm	0,110	0,133	1,00	18	25	36	15	0,045
000-1621	Air Core Coil	0,110mH +/-3% 0,100Q wire 1,20mm=17AWG OD-38 / 15mm	0,110	0,100	1,20	17	25	38	15	0,067
000-1634	Air Core Coil	0,110mH +/-3% 0,200Q wire 0,80mm=20AWG OD-31 / 10mm	0,110	0,200	0,80	20	20	31	10	0,027
000-1692	Air Core Coil	0,110mH +/-3% 0,250Q wire 0,70mm=21AWG OD-24 / 15mm	0,110	0,250	0,70	21	15	24	15	0,021
000-0003	Air Core Coil	0,120mH +/-3% 0,074Q wire 1,60mm=14AWG OD-35 / 25mm	0,120	0,074	1,60	14	8	35	25	0,150
000-0066	Air Core Coil	0,120mH +/-3% 0,06Q wire 1,80mm=13AWG OD-46 / 30mm	0,120	0,060	1,80	13	25	46	30	0,188
000-0103	Air Core Coil	0,120mH +/-3% 0,060Q wire 1,80mm=13AWG OD-39 / 25mm	0,120	0,060	1,80	13	8	39	25	0,195
000-0928	Air Core Coil	0,120mH +/-3% 0,110Q wire 1,20mm=17AWG OD-38 / 15mm	0,120	0,110	1,20	17	25	38	15	0,072
000-1003	Air Core Coil	0,120mH +/-3% 0,320Q wire 0,63mm=22AWG OD-26 / 8mm	0,120	0,320	0,63	22	15	26	8	0,016
000-1080	Air Core Coil	0,120mH +/-3% 0,700Q wire 0,40mm=26AWG OD-20 / 8mm	0,120	0,700	0,40	26	15	20	8	0,006
000-1090	Air Core Coil	0,120mH +/-3% 0,250Q wire 0,70mm=21AWG OD-24 / 15mm	0,120	0,250	0,70	21	15	24	15	0,022
000-1261	Air Core Coil	0,120mH +/-3% 0,26Q wire 0,70mm=21AWG OD-27 / 8mm	0,120	0,260	0,70	21	15	27	8	0,020
000-1325	Air Core Coil	0,120mH +/-3% 0,440Q wire 0,50mm=24AWG OD-18 / 8mm	0,120	0,440	0,50	24	9	18	8	0,009
000-1543	Air Core Coil	0,120mH +/-3% 0,086Q wire 1,40mm=15AWG OD-43 / 15mm	0,120	0,086	1,40	15	25	43	15	0,095
000-1675	Air Core Coil	0,120mH +/-3% 0,147Q wire 1,00mm=18AWG OD-35 / 15mm	0,120	0,147	1,00	18	25	35	15	0,047
000-1680	Air Core Coil	0,120mH +/-3% 0,150Q wire 1,00mm=18AWG OD-29 / 15mm	0,120	0,150	1,00	18	15	29	15	0,046
000-1682	Air Core Coil	0,120mH +/-3% 0,140Q wire 1,00mm=18AWG OD-37 / 10mm	0,120	0,140	1,00	18	20	37	10	0,044
000-1811	Air Core Coil	0,120mH +/-3% 0,470Q wire 0,50mm=24AWG OD-22 / 8mm	0,120	0,470	0,50	24	15	22	8	0,010
000-1812	Air Core Coil	0,120mH +/-3% 0,210Q wire 0,80mm=20AWG OD-31 / 10mm	0,120	0,210	0,80	20	20	31	10	0,028
000-0999	Air Core Coil	0,125mH +/-5% 1,15Q wire 0,30mm=29AWG OD-18 / 8mm	0,125	1,150	0,30	29	15	18	8	0,003
000-0152	Air Core Coil	0,126mH +/-5% 0,15Q wire 1,00mm=18AWG OD-29 / 15mm	0,126	0,150	1,00	18	15	29	15	0,047
000-0208	Air Core Coil	0,130mH +/-3% 0,30Q wire 0,80mm=20AWG OD-18 / 40mm	0,130	0,300	0,80	20	10	18	40	0,040
000-0739	Air Core Coil	0,130mH +/-3% 0,71Q wire 0,40mm=26AWG OD-20 / 8mm	0,130	0,710	0,40	26	15	20	8	0,006
000-0901	Air Core Coil	0,130mH +/-3% 0,22Q wire 0,80mm=20AWG OD-32 / 10mm	0,130	0,220	0,80	20	20	32	10	0,030
000-0973	Air Core Coil	0,130mH +/-3% 0,31Q wire 0,63mm=22AWG OD-25 / 8mm	0,130	0,310	0,63	22	15	25	8	0,017
000-1531	Air Core Coil	0,130mH +/-3% 0,290Q wire 0,70mm=21AWG OD-25 / 15mm	0,130	0,290	0,70	21	15	25	15	0,022
000-1738	Air Core Coil	0,130mH +/-3% 0,476Q wire 0,50mm=24AWG OD-22 / 8mm	0,130	0,476	0,50	24	15	22	8	0,010
000-1949	Air Core Coil	0,130mH +/-3% 0,160Q wire 1,00mm=18AWG OD-37 / 15mm	0,130	0,160	1,00	18	25	37	15	0,050
000-1965	Air Core Coil	0,130mH +/-3% 0,160Q wire 1,00mm=18AWG OD-30 / 15mm	0,130	0,160	1,00	18	15	30	15	0,048
000-0168	Air Core Coil	0,135mH +/-5% 0,291Q wire 0,70mm=21AWG OD-25 / 15mm	0,135	0,291	0,70	21	15	25	15	0,023
000-0219	Air Core Coil	0,135mH +/-3% 0,085Q wire 1,40mm=15AWG OD-45 / 15mm	0,135	0,085	1,40	15	25	45	15	0,109
000-0702	Air Core Coil	0,135mH +/-3% 0,16Q wire 1,00mm=18AWG OD-30 / 15mm	0,135	0,160	1,00	18	15	30	15	0,050
000-0706	Air Core Coil	0,135mH +/-3% 0,12Q wire 1,20mm=17AWG OD-42 / 15mm	0,135	0,120	1,20	17	25	42	15	0,079
000-0721	Air Core Coil	0,135mH +/-3% 1,16Q wire 0,30mm=29AWG OD-18 / 8mm	0,135	1,160	0,30	29	15	18	8	0,003
000-0207	Air Core Coil	0,140mH +/-3% 0,22Q wire 1,00mm=18AWG OD-22 / 40mm	0,140	0,220	1,00	18	10	22	40	0,068
000-0247	Air Core Coil	0,140mH +/-3% 0,28Q wire 0,70mm=21AWG OD-29 / 8mm	0,140	0,283	0,70	21	15	29	8	0,023
000-0921	Air Core Coil	0,140mH +/-3% 0,163Q wire 1,00mm=18AWG OD-30 / 15mm	0,140	0,163	1,00	18	15	30	15	0,050
000-1112	Air Core Coil	0,140mH +/-3% 0,225Q wire 0,80mm=20AWG OD-32 / 10mm	0,140	0,225	0,80	20	20	32	10	0,030
000-1813	Air Core Coil	0,140mH +/-3% 0,500Q wire 0,50mm=24AWG OD-22 / 8mm	0,140	0,500	0,50	24	15	22	8	0,011
000-0004	Air Core Coil	0,150mH +/-3% 0,084Q wire 1,60mm=14AWG OD-38 / 25mm	0,150	0,084	1,60	14	8	38	25	0,166
000-0104	Air Core Coil	0,150mH +/-3% 0,070Q wire 1,80mm=13AWG OD-42 / 25mm	0,150	0,070	1,80	13	8	42	25	0,221
000-1007	Air Core Coil	0,150mH +/-3% 0,310Q wire 0,70mm=21AWG OD-25 / 15mm	0,150	0,310	0,70	21	15	25	15	0,024
000-1045	Air Core Coil	0,150mH +/-3% 0,240Q wire 0,80mm=20AWG OD-26 / 15mm	0,150	0,240	0,80	20	15	26	15	0,033
000-1051	Air Core Coil	0,150mH +/-3% 0,160Q wire 1,00mm=18AWG OD-37 / 15mm	0,150	0,160	1,00	18	25	37	15	0,054
000-1061	Air Core Coil	0,150mH +/-3% 0,300Q wire 0,70mm=21AWG OD-30 / 10mm	0,150	0,300	0,70	21	20	30	10	0,024
000-1092	Air Core Coil	0,150mH +/-3% 0,120Q wire 1,20mm=17AWG OD-41 / 15mm	0,150	0,120	1,20	17	25	41	15	0,079
000-1129	Air Core Coil	0,150mH +/-3% 0,330Q wire 0,63mm=22AWG OD-26 / 8mm	0,150	0,330	0,63	22	15	26	8	0,018
000-1130	Air Core Coil	0,150mH +/-3% 0,160Q wire 1,00mm=18AWG OD-31 / 15mm	0,150	0,160	1,00	18	15	31	15	0,055
000-1146	Air Core Coil	0,150mH +/-3% 0,290Q wire 0,70mm=21AWG OD-25 / 8mm	0,150	0,290	0,70	21	9	25	8	0,023
000-1206	Air Core Coil	0,150mH +/-3% 0,193Q wire 1,00mm=18AWG OD-33 / 30mm	0,150	0,193	1,00	18	25	33	30	0,062

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1236	Air Core Coil	0,150mH +/-3% 0,160Ω wire 1,00mm=18AWG OD-39 / 10mm	0,150	0,160	1,00	18	20	39	10	0,053
000-1262	Air Core Coil	0,150mH +/-3% 0,283Ω wire 0,70mm=21AWG OD-29 / 8mm	0,150	0,283	0,70	21	15	29	8	0,023
000-1324	Air Core Coil	0,150mH +/-3% 0,490Ω wire 0,50mm=24AWG OD-19 / 8mm	0,150	0,490	0,50	24	9	19	8	0,010
000-1358	Air Core Coil	0,150mH +/-3% 0,400Ω wire 0,70mm=21AWG OD-29 / 30mm	0,150	0,400	0,70	21	25	29	30	0,029
000-1472	Air Core Coil	0,150mH +/-3% 0,850Ω wire 0,40mm=26AWG OD-20 / 8mm	0,150	0,850	0,40	26	15	20	8	0,006
000-1485	Air Core Coil	0,150mH +/-3% 0,099Ω wire 1,40mm=15AWG OD-45 / 15mm	0,150	0,099	1,40	15	25	45	15	0,110
000-1496	Air Core Coil	0,150mH +/-3% 0,146Ω wire 1,20mm=17AWG OD-34 / 30mm	0,150	0,146	1,20	17	25	34	30	0,093
000-1688	Air Core Coil	0,150mH +/-3% 0,105Ω wire 1,40mm=15AWG OD-38 / 30mm	0,150	0,105	1,40	15	25	38	30	0,126
000-1814	Air Core Coil	0,150mH +/-3% 1,16Ω wire 0,30mm=29AWG OD-18 / 8mm	0,150	1,160	0,30	29	15	18	8	0,004
000-1815	Air Core Coil	0,150mH +/-3% 0,230Ω wire 0,80mm=20AWG OD-32 / 10mm	0,150	0,230	0,80	20	20	32	10	0,032
000-1816	Air Core Coil	0,150mH +/-3% 0,510Ω wire 0,50mm=24AWG OD-23 / 8mm	0,150	0,510	0,50	24	15	23	8	0,011
000-0064	Air Core Coil	0,160mH +/-3% 0,07Ω wire 1,80mm=13AWG OD-46 / 30mm	0,160	0,070	1,80	13	25	46	30	0,228
000-0225	Air Core Coil	0,160mH +/-3% 1,30Ω wire 0,30mm=29AWG OD-19 / 8mm	0,160	1,300	0,30	29	15	19	8	0,004
000-0232	Air Core Coil	0,160mH +/-3% 0,15Ω wire 1,20mm=17AWG OD-37 / 30mm	0,160	0,150	1,20	17	25	37	30	0,098
000-0746	Air Core Coil	0,160mH +/-3% 0,17Ω wire 1,00mm=18AWG OD-39 / 10mm	0,160	0,170	1,00	18	20	39	10	0,056
000-0952	Air Core Coil	0,160mH +/-3% 0,12Ω wire 1,20mm=17AWG OD-37 / 15mm	0,160	0,123	1,20	17	15	37	15	0,082
000-1008	Air Core Coil	0,160mH +/-3% 0,850Ω wire 0,40mm=26AWG OD-20 / 8mm	0,160	0,850	0,40	26	15	20	8	0,007
000-1397	Air Core Coil	0,160mH +/-3% 0,410Ω wire 0,70mm=21AWG OD-29 / 30mm	0,160	0,410	0,70	21	25	29	30	0,031
000-1627	Air Core Coil	0,160mH +/-3% 0,180Ω wire 1,00mm=18AWG OD-33 / 15mm	0,160	0,180	1,00	18	15	33	15	0,056
000-1684	Air Core Coil	0,160mH +/-3% 0,290Ω wire 0,70mm=21AWG OD-29 / 8mm	0,160	0,290	0,70	21	15	29	8	0,023
000-1817	Air Core Coil	0,160mH +/-3% 0,240Ω wire 0,80mm=20AWG OD-33 / 10mm	0,160	0,240	0,80	20	20	33	10	0,032
000-0978	Air Core Coil	0,169mH +/-5% 1,17Ω wire 0,30mm=29AWG OD-18 / 8mm	0,169	1,170	0,30	29	15	18	8	0,005
000-0822	Air Core Coil	0,170mH +/-3% 0,18Ω wire 1,00mm=18AWG OD-28 / 17mm	0,170	0,180	1,00	18	10	28	17	0,059
000-0965	Air Core Coil	0,170mH +/-3% 0,14Ω wire 1,20mm=17AWG OD-38 / 15mm	0,170	0,140	1,20	17	15	38	15	0,090
000-1049	Air Core Coil	0,170mH +/-3% 0,111Ω wire 1,40mm=15AWG OD-38 / 30mm	0,170	0,111	1,40	15	25	38	30	0,131
000-1270	Air Core Coil	0,170mH +/-3% 0,180Ω wire 1,00mm=18AWG OD-33 / 15mm	0,170	0,180	1,00	18	15	33	15	0,057
000-0164	Air Core Coil	0,174mH +/-3% 0,099Ω wire 1,40mm=15AWG OD-45 / 15mm	0,174	0,099	1,40	15	25	49	15	0,124
000-0005	Air Core Coil	0,180mH +/-3% 0,094Ω wire 1,60mm=14AWG OD-42 / 25mm	0,180	0,094	1,60	14	8	42	25	0,192
000-0105	Air Core Coil	0,180mH +/-3% 0,075Ω wire 1,80mm=13AWG OD-49 / 30mm	0,180	0,075	1,80	13	25	49	30	0,239
000-0798	Air Core Coil	0,180mH +/-3% 0,32Ω wire 0,70mm=21AWG OD-27 / 8mm	0,180	0,320	0,70	21	9	27	8	0,026
000-1010	Air Core Coil	0,180mH +/-3% 0,180Ω wire 1,00mm=18AWG OD-39 / 15mm	0,180	0,180	1,00	18	25	39	15	0,059
000-1066	Air Core Coil	0,180mH +/-3% 0,270Ω wire 0,80mm=20AWG OD-27 / 15mm	0,180	0,270	0,80	20	15	27	15	0,037
000-1072	Air Core Coil	0,180mH +/-3% 0,330Ω wire 0,70mm=21AWG OD-25 / 15mm	0,180	0,330	0,70	21	15	25	15	0,027
000-1091	Air Core Coil	0,180mH +/-3% 0,420Ω wire 0,63mm=22AWG OD-24 / 15mm	0,180	0,420	0,63	22	15	24	15	0,020
000-1207	Air Core Coil	0,180mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-33 / 30mm	0,180	0,210	1,00	18	25	33	30	0,067
000-1273	Air Core Coil	0,180mH +/-3% 0,105Ω wire 1,40mm=15AWG OD-56 / 10mm	0,180	0,105	1,40	15	25	56	10	0,123
000-1277	Air Core Coil	0,180mH +/-3% 0,180Ω wire 1,00mm=18AWG OD-39 / 10mm	0,180	0,180	1,00	18	20	39	10	0,056
000-1289	Air Core Coil	0,180mH +/-3% 0,180Ω wire 1,00mm=18AWG OD-33 / 15mm	0,180	0,180	1,00	18	15	33	15	0,060
000-1291	Air Core Coil	0,180mH +/-3% 0,321Ω wire 0,70mm=21AWG OD-30 / 8mm	0,180	0,321	0,70	21	15	30	8	0,024
000-1421	Air Core Coil	0,180mH +/-3% 0,430Ω wire 0,70mm=21AWG OD-29 / 30mm	0,180	0,430	0,70	21	25	29	30	0,032
000-1475	Air Core Coil	0,180mH +/-3% 1,20Ω wire 0,30mm=29AWG OD-18 / 8mm	0,180	1,200	0,30	29	15	18	8	0,005
000-1488	Air Core Coil	0,180mH +/-3% 0,382Ω wire 0,63mm=22AWG OD-27 / 8mm	0,180	0,382	0,63	22	15	27	8	0,020
000-1741	Air Core Coil	0,180mH +/-3% 0,850Ω wire 0,50mm=24AWG OD-28 / 30mm	0,180	0,850	0,50	24	25	28	30	0,017
000-1750	Air Core Coil	0,180mH +/-3% 0,810Ω wire 0,50mm=24AWG OD-19 / 27mm	0,180	0,810	0,50	24	15	19	27	0,016
000-1818	Air Core Coil	0,180mH +/-3% 0,250Ω wire 0,80mm=20AWG OD-34 / 10mm	0,180	0,250	0,80	20	20	34	10	0,035
000-1819	Air Core Coil	0,180mH +/-3% 0,900Ω wire 0,40mm=26AWG OD-20 / 8mm	0,180	0,900	0,40	26	15	20	8	0,008
000-1820	Air Core Coil	0,180mH +/-3% 0,550Ω wire 0,50mm=24AWG OD-23 / 8mm	0,180	0,550	0,50	24	15	23	8	0,012
000-1937	Air Core Coil	0,180mH +/-3% 0,140Ω wire 1,20mm=17AWG OD-38 / 15mm	0,180	0,140	1,20	17	15	38	15	0,091
000-0163	Air Core Coil	0,185mH +/-3% 0,11Ω wire 1,40mm=15AWG OD-50 / 15mm	0,185	0,115	1,40	15	25	50	15	0,128
000-0096	Air Core Coil	0,190mH +/-3% 0,08Ω wire 1,80mm=13AWG OD-46 / 25mm	0,190	0,080	1,80	13	8	46	25	0,252
000-0248	Air Core Coil	0,190mH +/-3% 0,11Ω wire 1,40mm=15AWG OD-49 / 15mm	0,190	0,115	1,40	15	25	50	15	0,133
000-0941	Air Core Coil	0,190mH +/-3% 0,290Ω wire 0,80mm=20AWG OD-29 / 13mm	0,190	0,290	0,80	20	15	29	13	0,037



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1042	Air Core Coil	0,190mH +/-3% 0,182Ω wire 1,00mm=18AWG OD-41 / 10mm	0,190	0,182	1,00	18	20	41	10	0,058
000-1530	Air Core Coil	0,190mH +/-3% 0,920Ω wire 0,40mm=26AWG OD-20 / 8mm	0,190	0,920	0,40	26	15	20	8	0,008
000-1576	Air Core Coil	0,190mH +/-3% 0,14Ω wire 1,20mm=17AWG OD-48 / 10mm	0,190	0,140	1,20	17	20	48	10	0,093
000-1597	Air Core Coil	0,190mH +/-3% 0,290Ω wire 0,80mm=20AWG OD-28 / 15mm	0,190	0,290	0,80	20	15	28	15	0,037
000-1667	Air Core Coil	0,190mH +/-3% 0,345Ω wire 0,70mm=21AWG OD-25 / 15mm	0,190	0,345	0,70	21	15	25	15	0,027
000-1763	Air Core Coil	0,190mH +/-3% 0,209Ω wire 1,00mm=18AWG OD-26 / 25mm	0,190	0,209	1,00	18	8	26	25	0,067
000-1906	Air Core Coil	0,190mH +/-3% 0,590Ω wire 0,50mm=24AWG OD-23 / 8mm	0,190	0,590	0,50	24	15	23	8	0,012
000-0919	Air Core Coil	0,193mH +/-5% 0,145Ω wire 1,20mm=17AWG OD-43 / 15mm	0,193	0,145	1,20	17	25	43	15	0,091
000-0057	Air Core Coil	0,200mH +/-3% 0,10Ω wire 1,60mm=14AWG OD-42 / 25mm	0,200	0,100	1,60	14	8	42	25	0,205
000-0139	Air Core Coil	0,200mH +/-3% 0,080Ω wire 1,80mm=13AWG OD-46 / 25mm	0,200	0,080	1,80	13	8	46	25	0,265
000-0803	Air Core Coil	0,200mH +/-3% 1,690Ω wire 0,30mm=29AWG OD-19 / 8mm	0,200	1,690	0,30	29	15	19	8	0,005
000-0854	Air Core Coil	0,200mH +/-3% 0,45Ω wire 0,63mm=22AWG OD-24 / 15mm	0,200	0,450	0,63	22	15	24	15	0,022
000-1011	Air Core Coil	0,200mH +/-3% 0,700Ω wire 0,50mm=24AWG OD-20 / 15mm	0,200	0,700	0,50	24	15	20	15	0,014
000-1073	Air Core Coil	0,200mH +/-3% 0,600Ω wire 0,50mm=24AWG OD-24 / 8mm	0,200	0,600	0,50	24	15	24	8	0,013
000-1100	Air Core Coil	0,200mH +/-3% 0,350Ω wire 0,70mm=21AWG OD-30 / 10mm	0,200	0,350	0,70	21	20	30	10	0,026
000-1101	Air Core Coil	0,200mH +/-3% 0,350Ω wire 0,70mm=21AWG OD-25 / 15mm	0,200	0,350	0,70	21	15	25	15	0,028
000-1109	Air Core Coil	0,200mH +/-3% 0,290Ω wire 0,80mm=20AWG OD-29 / 13mm	0,200	0,290	0,80	20	15	29	13	0,037
000-1147	Air Core Coil	0,200mH +/-3% 0,350Ω wire 0,70mm=21AWG OD-28 / 8mm	0,200	0,350	0,70	21	9	28	8	0,027
000-1276	Air Core Coil	0,200mH +/-3% 0,193Ω wire 1,00mm=18AWG OD-41 / 10mm	0,200	0,193	1,00	18	20	41	10	0,062
000-1357	Air Core Coil	0,200mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-35 / 25mm	0,200	0,210	1,00	18	25	35	25	0,068
000-1359	Air Core Coil	0,200mH +/-3% 0,450Ω wire 0,70mm=21AWG OD-30 / 30mm	0,200	0,450	0,70	21	25	30	30	0,034
000-1462	Air Core Coil	0,200mH +/-3% 0,420Ω wire 0,63mm=22AWG OD-28 / 8mm	0,200	0,420	0,63	22	15	28	8	0,021
000-1507	Air Core Coil	0,200mH +/-3% 0,130Ω wire 1,40mm=15AWG OD-41 / 30mm	0,200	0,130	1,40	15	25	41	30	0,148
000-1600	Air Core Coil	0,200mH +/-3% 0,150Ω wire 1,20mm=17AWG OD-43 / 15mm	0,200	0,150	1,20	17	25	43	15	0,093
000-1606	Air Core Coil	0,200mH +/-3% 0,115Ω wire 1,40mm=15AWG OD-48 / 15mm	0,200	0,115	1,40	15	25	48	15	0,135
000-1612	Air Core Coil	0,200mH +/-3% 0,110Ω wire 1,40mm=15AWG OD-56 / 10mm	0,200	0,110	1,40	15	25	56	10	0,132
000-1622	Air Core Coil	0,200mH +/-3% 0,295Ω wire 0,80mm=20AWG OD-28 / 15mm	0,200	0,295	0,80	20	15	28	15	0,037
000-1822	Air Core Coil	0,200mH +/-3% 0,200Ω wire 1,00mm=18AWG OD-39 / 15mm	0,200	0,200	1,00	18	25	39	15	0,063
000-1823	Air Core Coil	0,200mH +/-3% 0,940Ω wire 0,40mm=26AWG OD-21 / 8mm	0,200	0,940	0,40	26	15	21	8	0,008
000-1824	Air Core Coil	0,200mH +/-3% 0,290Ω wire 0,80mm=20AWG OD-34 / 10mm	0,200	0,290	0,80	20	20	34	10	0,037
000-1875	Air Core Coil	0,200mH +/-3% 1,000Ω wire 0,40mm=26AWG OD-24 / 10mm	0,200	1,000	0,40	26	20	24	10	0,009
000-1928	Air Core Coil	0,200mH +/-3% 0,150Ω wire 1,20mm=17AWG OD-40 / 15mm	0,200	0,150	1,20	17	15	40	15	0,092
000-1985	Air Core Coil	0,200mH +/-3% 0,220Ω wire 1,00mm=18AWG OD-26 / 25mm	0,200	0,220	1,00	18	8	26	25	0,069
000-0100	Air Core Coil	0,210mH +/-3% 0,080Ω wire 1,80mm=13AWG OD-49 / 30mm	0,210	0,080	1,80	13	25	49	30	0,263
000-1074	Air Core Coil	0,210mH +/-3% 0,605Ω wire 0,50mm=24AWG OD-24 / 8mm	0,210	0,605	0,50	24	15	24	8	0,014
000-1086	Air Core Coil	0,210mH +/-3% 0,295Ω wire 0,80mm=20AWG OD-34 / 10mm	0,210	0,295	0,80	20	20	34	10	0,038
000-1420	Air Core Coil	0,210mH +/-3% 0,460Ω wire 0,70mm=21AWG OD-30 / 30mm	0,210	0,460	0,70	21	25	30	30	0,036
000-1559	Air Core Coil	0,210mH +/-3% 0,150Ω wire 1,20mm=17AWG OD-44 / 15mm	0,210	0,150	1,20	17	25	44	15	0,095
000-1686	Air Core Coil	0,210mH +/-3% 0,370Ω wire 0,70mm=21AWG OD-31 / 8mm	0,210	0,370	0,70	21	15	31	8	0,027
000-0006	Air Core Coil	0,220mH +/-3% 0,104Ω wire 1,60mm=14AWG OD-42 / 25mm	0,220	0,104	1,60	14	8	42	25	0,219
000-0106	Air Core Coil	0,220mH +/-3% 0,083Ω wire 1,80mm=13AWG OD-49 / 30mm	0,220	0,083	1,80	13	25	49	30	0,265
000-1013	Air Core Coil	0,220mH +/-3% 0,440Ω wire 0,63mm=22AWG OD-29 / 8mm	0,220	0,440	0,63	22	15	29	8	0,023
000-1015	Air Core Coil	0,220mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-34 / 15mm	0,220	0,210	1,00	18	15	34	15	0,067
000-1125	Air Core Coil	0,220mH +/-3% 0,370Ω wire 0,70mm=21AWG OD-26 / 15mm	0,220	0,370	0,70	21	15	26	15	0,031
000-1263	Air Core Coil	0,220mH +/-3% 0,349Ω wire 0,70mm=21AWG OD-31 / 8mm	0,220	0,349	0,70	21	15	31	8	0,028
000-1268	Air Core Coil	0,220mH +/-3% 0,120Ω wire 1,40mm=15AWG OD-50 / 15mm	0,220	0,120	1,40	15	25	50	15	0,139
000-1278	Air Core Coil	0,220mH +/-3% 0,205Ω wire 1,00mm=18AWG OD-41 / 10mm	0,220	0,205	1,00	18	20	41	10	0,065
000-1308	Air Core Coil	0,220mH +/-3% 0,300Ω wire 0,80mm=20AWG OD-33 / 8mm	0,220	0,300	0,80	20	9	33	8	0,039
000-1323	Air Core Coil	0,220mH +/-3% 0,640Ω wire 0,50mm=24AWG OD-21 / 8mm	0,220	0,640	0,50	24	9	21	8	0,014
000-1345	Air Core Coil	0,220mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-39 / 15mm	0,220	0,210	1,00	18	25	39	15	0,068
000-1631	Air Core Coil	0,220mH +/-3% 0,140Ω wire 1,40mm=15AWG OD-41 / 30mm	0,220	0,140	1,40	15	25	41	30	0,155
000-1650	Air Core Coil	0,220mH +/-3% 0,465Ω wire 0,63mm=22AWG OD-24 / 15mm	0,220	0,465	0,63	22	15	24	15	0,023



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1674	Air Core Coil	0,220mH +/-3% 0,360Ω wire 0,70mm=21AWG OD-29 / 8mm	0,220	0,360	0,70	21	9	29	8	0,028
000-1708	Air Core Coil	0,220mH +/-3% 0,310Ω wire 0,80mm=20AWG OD-28 / 15mm	0,220	0,310	0,80	20	15	28	15	0,039
000-1742	Air Core Coil	0,220mH +/-3% 0,465Ω wire 0,70mm=21AWG OD-31 / 30mm	0,220	0,465	0,70	21	25	31	30	0,036
000-1745	Air Core Coil	0,220mH +/-3% 0,240Ω wire 1,00mm=18AWG OD-35 / 30mm	0,220	0,240	1,00	18	25	35	30	0,075
000-1753	Air Core Coil	0,220mH +/-3% 0,455Ω wire 0,70mm=21AWG OD-23 / 27mm	0,220	0,455	0,70	21	15	23	27	0,034
000-1756	Air Core Coil	0,220mH +/-3% 0,230Ω wire 1,00mm=18AWG OD-27 / 27mm	0,220	0,230	1,00	18	15	27	27	0,073
000-1825	Air Core Coil	0,220mH +/-3% 0,300Ω wire 0,80mm=20AWG OD-34 / 10mm	0,220	0,300	0,80	20	20	34	10	0,039
000-1826	Air Core Coil	0,220mH +/-3% 0,610Ω wire 0,50mm=24AWG OD-24 / 8mm	0,220	0,610	0,50	24	15	24	8	0,014
000-1827	Air Core Coil	0,220mH +/-3% 1,070Ω wire 0,40mm=26AWG OD-19 / 15mm	0,220	1,070	0,40	26	15	19	15	0,009
000-1909	Air Core Coil	0,220mH +/-3% 0,440Ω wire 0,70mm=21AWG OD-20 / 25mm	0,220	0,440	0,70	21	8	20	25	0,034
000-1910	Air Core Coil	0,220mH +/-3% 0,353Ω wire 0,70mm=21AWG OD-31 / 10mm	0,220	0,353	0,70	21	20	31	10	0,029
000-1912	Air Core Coil	0,220mH +/-3% 0,880Ω wire 0,40mm=26AWG OD-17 / 8mm	0,220	0,880	0,40	26	9	17	8	0,008
000-1914	Air Core Coil	0,220mH +/-3% 0,800Ω wire 0,50mm=24AWG OD-15 / 25mm	0,220	0,800	0,50	24	8	15	25	0,017
000-1915	Air Core Coil	0,220mH +/-3% 0,500Ω wire 0,63mm=22AWG OD-17 / 25mm	0,220	0,500	0,63	22	8	17	25	0,027
000-1921	Air Core Coil	0,220mH +/-3% 0,170Ω wire 1,20mm=17AWG OD-37 / 30mm	0,220	0,170	1,20	17	25	37	30	0,113
000-1922	Air Core Coil	0,220mH +/-3% 0,160Ω wire 1,20mm=17AWG OD-45 / 15mm	0,220	0,160	1,20	17	25	45	15	0,100
000-1923	Air Core Coil	0,220mH +/-3% 0,160Ω wire 1,20mm=17AWG OD-40 / 15mm	0,220	0,160	1,20	17	15	40	15	0,097
000-1998	Air Core Coil	0,220mH +/-3% 0,230Ω wire 1,00mm=18AWG OD-26 / 25mm	0,220	0,230	1,00	18	8	26	25	0,073
000-0227	Air Core Coil	0,230mH +/-3% 0,15Ω wire 1,20mm=17AWG OD-40 / 15mm	0,230	0,150	1,20	17	15	40	15	0,106
000-1016	Air Core Coil	0,230mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-34 / 15mm	0,230	0,210	1,00	18	15	34	15	0,068
000-1165	Air Core Coil	0,230mH +/-3% 0,370Ω wire 0,70mm=21AWG OD-31 / 8mm	0,230	0,370	0,70	21	15	31	8	0,029
000-1616	Air Core Coil	0,230mH +/-3% 0,305Ω wire 0,80mm=20AWG OD-35 / 10mm	0,230	0,305	0,80	20	20	35	10	0,040
000-1648	Air Core Coil	0,230mH +/-3% 0,44Ω wire 0,63mm=22AWG OD-29 / 8mm	0,230	0,440	0,63	22	15	29	8	0,024
000-0245	Air Core Coil	0,240mH +/-3% 0,11Ω wire 1,60mm=14AWG OD-43 / 25mm	0,240	0,110	1,60	14	8	43	25	0,226
000-0736	Air Core Coil	0,240mH +/-3% 0,45Ω wire 0,63mm=22AWG OD-29 / 8mm	0,240	0,450	0,63	22	15	29	8	0,024
000-0905	Air Core Coil	0,240mH +/-3% 0,125Ω wire 1,40mm=15AWG OD-52 / 15mm	0,240	0,125	1,40	15	25	52	15	0,146
000-1017	Air Core Coil	0,240mH +/-3% 1,690Ω wire 0,30mm=29AWG OD-19 / 8mm	0,240	1,690	0,30	29	15	19	8	0,005
000-1084	Air Core Coil	0,240mH +/-3% 0,310Ω wire 0,80mm=20AWG OD-35 / 10mm	0,240	0,310	0,80	20	20	35	10	0,041
000-1102	Air Core Coil	0,240mH +/-3% 0,640Ω wire 0,50mm=24AWG OD-24 / 8mm	0,240	0,640	0,50	24	15	24	8	0,015
000-1481	Air Core Coil	0,240mH +/-3% 1,020Ω wire 0,40mm=26AWG OD-22 / 8mm	0,240	1,020	0,40	26	15	22	8	0,009
000-1642	Air Core Coil	0,240mH +/-3% 0,165Ω wire 1,20mm=17AWG OD-40 / 15mm	0,240	0,165	1,20	17	15	40	15	0,110
000-1683	Air Core Coil	0,240mH +/-3% 0,375Ω wire 0,70mm=21AWG OD-31 / 8mm	0,240	0,375	0,70	21	15	31	8	0,030
000-1926	Air Core Coil	0,240mH +/-3% 0,210Ω wire 1,00mm=18AWG OD-39 / 15mm	0,240	0,210	1,00	18	25	39	15	0,071
000-0991	Air Core Coil	0,245mH +/-5% 1,45Ω wire 0,30mm=29AWG OD-15 / 8mm	0,245	1,450	0,30	29	9	15	8	0,005
000-1076	Air Core Coil	0,250mH +/-3% 0,220Ω wire 1,00mm=18AWG OD-40 / 15mm	0,250	0,220	1,00	18	25	40	15	0,071
000-1093	Air Core Coil	0,250mH +/-3% 0,170Ω wire 1,20mm=17AWG OD-42 / 15mm	0,250	0,170	1,20	17	15	42	15	0,113
000-1152	Air Core Coil	0,250mH +/-3% 0,720Ω wire 0,50mm=24AWG OD-21 / 15mm	0,250	0,720	0,50	24	15	21	15	0,016
000-1155	Air Core Coil	0,250mH +/-3% 0,140Ω wire 1,40mm=15AWG OD-41 / 30mm	0,250	0,140	1,40	15	25	41	30	0,165
000-1269	Air Core Coil	0,250mH +/-3% 0,128Ω wire 1,40mm=15AWG OD-52 / 15mm	0,250	0,128	1,40	15	25	52	15	0,150
000-1279	Air Core Coil	0,250mH +/-3% 0,223Ω wire 1,00mm=18AWG OD-34 / 15mm	0,250	0,223	1,00	18	15	34	15	0,072
000-1360	Air Core Coil	0,250mH +/-3% 0,490Ω wire 0,70mm=21AWG OD-31 / 30mm	0,250	0,490	0,70	21	25	31	30	0,039
000-1464	Air Core Coil	0,250mH +/-3% 0,400Ω wire 0,70mm=21AWG OD-26 / 15mm	0,250	0,400	0,70	21	15	26	15	0,031
000-1490	Air Core Coil	0,250mH +/-3% 0,460Ω wire 0,63mm=22AWG OD-29 / 8mm	0,250	0,460	0,63	22	15	29	8	0,024
000-1525	Air Core Coil	0,250mH +/-3% 0,660Ω wire 0,50mm=24AWG OD-24 / 8mm	0,250	0,660	0,50	24	15	24	8	0,015
000-1528	Air Core Coil	0,250mH +/-3% 0,330Ω wire 0,80mm=20AWG OD-29 / 15mm	0,250	0,330	0,80	20	15	29	15	0,043
000-1645	Air Core Coil	0,250mH +/-3% 0,380Ω wire 0,70mm=21AWG OD-32 / 8mm	0,250	0,380	0,70	21	15	32	8	0,031
000-1904	Air Core Coil	0,250mH +/-3% 0,250Ω wire 1,00mm=18AWG OD-35 / 30mm	0,250	0,250	1,00	18	25	35	30	0,081
000-1905	Air Core Coil	0,250mH +/-3% 0,250Ω wire 1,00mm=18AWG OD-26 / 25mm	0,250	0,250	1,00	18	8	26	25	0,078
000-1925	Air Core Coil	0,250mH +/-3% 1,020Ω wire 0,40mm=26AWG OD-22 / 8mm	0,250	1,020	0,40	26	15	22	8	0,010
000-0867	Air Core Coil	0,256mH +/-3% 0,23Ω wire 1,00mm=18AWG OD-35 / 15mm	0,256	0,230	1,00	18	15	35	15	0,074
000-0879	Air Core Coil	0,260mH +/-3% 0,470Ω wire 0,63mm=22AWG OD-29 / 8mm	0,260	0,470	0,63	22	15	29	8	0,024
000-0904	Air Core Coil	0,260mH +/-3% 0,132Ω wire 1,40mm=15AWG OD-52 / 15mm	0,260	0,132	1,40	15	25	52	15	0,157



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0907	Air Core Coil	0,260mH +/-3% 0,091Ω wire 1,80mm=13AWG OD-50 / 25mm	0,260	0,091	1,80	13	8	50	25	0,302
000-1113	Air Core Coil	0,260mH +/-3% 0,317Ω wire 0,80mm=20AWG OD-36 / 10mm	0,260	0,317	0,80	20	20	36	10	0,042
000-1162	Air Core Coil	0,260mH +/-3% 0,410Ω wire 0,70mm=21AWG OD-26 / 15mm	0,260	0,410	0,70	21	15	26	15	0,033
000-1266	Air Core Coil	0,260mH +/-3% 1,830Ω wire 0,30mm=29AWG OD-19 / 8mm	0,260	1,830	0,30	29	15	19	8	0,005
000-1372	Air Core Coil	0,260mH +/-3% 0,260Ω wire 1,00mm=18AWG OD-35 / 30mm	0,260	0,260	1,00	18	25	35	30	0,083
000-1412	Air Core Coil	0,260mH +/-3% 0,186Ω wire 1,20mm=17AWG OD-39 / 30mm	0,260	0,186	1,20	17	25	39	30	0,116
000-1414	Air Core Coil	0,260mH +/-3% 0,140Ω wire 1,40mm=15AWG OD-41 / 30mm	0,260	0,140	1,40	15	25	41	30	0,169
000-1419	Air Core Coil	0,260mH +/-3% 0,500Ω wire 0,70mm=21AWG OD-31 / 30mm	0,260	0,500	0,70	21	25	31	30	0,039
000-1728	Air Core Coil	0,260mH +/-3% 0,225Ω wire 1,00mm=18AWG OD-40 / 15mm	0,260	0,225	1,00	18	25	40	15	0,073
000-1777	Air Core Coil	0,260mH +/-3% 0,710Ω wire 0,50mm=24AWG OD-22 / 8mm	0,260	0,710	0,50	24	9	22	8	0,015
000-1000	Air Core Coil	0,267mH +/-5% 1,90Ω wire 0,30mm=29AWG OD-18 / 8mm	0,267	1,900	0,30	29	15	18	8	0,005
000-0007	Air Core Coil	0,270mH +/-3% 0,120Ω wire 1,60mm=14AWG OD-44 / 25mm	0,270	0,120	1,60	14	8	44	25	0,242
000-0107	Air Core Coil	0,270mH +/-3% 0,095Ω wire 1,80mm=13AWG OD-52 / 30mm	0,270	0,095	1,80	13	25	52	30	0,303
000-0797	Air Core Coil	0,270mH +/-3% 1,94Ω wire 0,30mm=29AWG OD-19 / 8mm	0,270	1,940	0,30	29	15	19	8	0,005
000-0882	Air Core Coil	0,270mH +/-3% 0,750Ω wire 0,50mm=24AWG OD-21 / 15mm	0,270	0,750	0,50	24	15	21	15	0,015
000-0889	Air Core Coil	0,270mH +/-3% 0,150Ω wire 1,40mm=15AWG OD-40 / 25mm	0,270	0,150	1,40	15	8	40	25	0,181
000-1019	Air Core Coil	0,270mH +/-3% 0,410Ω wire 0,70mm=21AWG OD-26 / 15mm	0,270	0,410	0,70	21	15	26	15	0,034
000-1168	Air Core Coil	0,270mH +/-3% 0,414Ω wire 0,70mm=21AWG OD-32 / 10mm	0,270	0,414	0,70	21	20	32	10	0,031
000-1208	Air Core Coil	0,270mH +/-3% 0,266Ω wire 1,00mm=18AWG OD-35 / 30mm	0,270	0,266	1,00	18	25	35	30	0,085
000-1275	Air Core Coil	0,270mH +/-3% 0,134Ω wire 1,40mm=15AWG OD-52 / 15mm	0,270	0,134	1,40	15	25	52	15	0,159
000-1322	Air Core Coil	0,270mH +/-3% 0,710Ω wire 0,50mm=24AWG OD-22 / 8mm	0,270	0,710	0,50	24	9	22	8	0,016
000-1350	Air Core Coil	0,270mH +/-3% 0,405Ω wire 0,70mm=21AWG OD-33 / 8mm	0,270	0,405	0,70	21	15	33	8	0,031
000-1446	Air Core Coil	0,270mH +/-3% 0,230Ω wire 1,00mm=18AWG OD-40 / 15mm	0,270	0,230	1,00	18	25	40	15	0,074
000-1579	Air Core Coil	0,270mH +/-3% 0,17Ω wire 1,20mm=17AWG OD-52 / 10mm	0,270	0,170	1,20	17	20	52	10	0,115
000-1632	Air Core Coil	0,270mH +/-3% 0,160Ω wire 1,20mm=17AWG OD-46 / 15mm	0,270	0,160	1,20	17	25	46	15	0,113
000-1635	Air Core Coil	0,270mH +/-3% 0,23Ω wire 1,00mm=18AWG OD-35 / 15mm	0,270	0,230	1,00	18	15	35	15	0,074
000-1640	Air Core Coil	0,270mH +/-3% 0,490Ω wire 0,63mm=22AWG OD-29 / 8mm	0,270	0,490	0,63	22	15	29	8	0,025
000-1769	Air Core Coil	0,270mH +/-3% 0,152Ω wire 1,40mm=15AWG OD-41 / 30mm	0,270	0,152	1,40	15	25	41	30	0,170
000-1828	Air Core Coil	0,270mH +/-3% 0,330Ω wire 0,80mm=20AWG OD-36 / 10mm	0,270	0,330	0,80	20	20	36	10	0,044
000-1829	Air Core Coil	0,270mH +/-3% 0,680Ω wire 0,50mm=24AWG OD-25 / 8mm	0,270	0,680	0,50	24	15	25	8	0,016
000-1986	Air Core Coil	0,270mH +/-3% 0,260Ω wire 1,00mm=18AWG OD-28 / 25mm	0,270	0,260	1,00	18	8	28	25	0,082
000-0738	Air Core Coil	0,275mH +/-3% 1,05Ω wire 0,40mm=26AWG OD-22 / 8mm	0,275	1,050	0,40	26	15	22	8	0,010
000-1916	Air Core Coil	0,275mH +/-5% 0,170Ω wire 1,20mm=17AWG OD-46 / 15mm	0,275	0,170	1,20	17	25	46	15	0,115
000-1917	Air Core Coil	0,275mH +/-5% 0,235Ω wire 1,00mm=18AWG OD-40 / 15mm	0,275	0,235	1,00	18	25	40	15	0,075
000-1919	Air Core Coil	0,275mH +/-5% 0,230Ω wire 1,00mm=18AWG OD-35 / 15mm	0,275	0,230	1,00	18	15	35	15	0,075
000-0801	Air Core Coil	0,280mH +/-3% 1,950Ω wire 0,30mm=29AWG OD-19 / 8mm	0,280	1,950	0,30	29	15	19	8	0,005
000-0903	Air Core Coil	0,280mH +/-3% 0,140Ω wire 1,40mm=15AWG OD-53 / 15mm	0,280	0,140	1,40	15	25	53	15	0,162
000-1020	Air Core Coil	0,280mH +/-3% 0,500Ω wire 0,63mm=22AWG OD-30 / 8mm	0,280	0,500	0,63	22	15	30	8	0,025
000-1114	Air Core Coil	0,280mH +/-3% 0,335Ω wire 0,80mm=20AWG OD-36 / 10mm	0,280	0,335	0,80	20	20	36	10	0,045
000-1164	Air Core Coil	0,280mH +/-3% 0,790Ω wire 0,50mm=24AWG OD-21 / 15mm	0,280	0,790	0,50	24	15	21	15	0,017
000-1340	Air Core Coil	0,280mH +/-3% 0,240Ω wire 1,00mm=18AWG OD-40 / 15mm	0,280	0,240	1,00	18	25	40	15	0,076
000-1456	Air Core Coil	0,280mH +/-3% 0,420Ω wire 0,70mm=21AWG OD-26 / 15mm	0,280	0,420	0,70	21	15	26	15	0,034
000-1590	Air Core Coil	0,280mH +/-3% 0,710Ω wire 0,50mm=24AWG OD-25 / 8mm	0,280	0,710	0,50	24	15	25	8	0,016
000-1759	Air Core Coil	0,280mH +/-3% 0,192Ω wire 1,20mm=17AWG OD-34 / 27mm	0,280	0,192	1,20	17	15	34	27	0,126
000-1764	Air Core Coil	0,280mH +/-3% 0,191Ω wire 1,20mm=17AWG OD-39 / 30mm	0,280	0,191	1,20	17	25	39	30	0,124
000-1830	Air Core Coil	0,280mH +/-3% 0,420Ω wire 0,70mm=21AWG OD-33 / 10mm	0,280	0,420	0,70	21	20	33	10	0,032
000-1831	Air Core Coil	0,280mH +/-3% 0,760Ω wire 0,50mm=24AWG OD-27 / 10mm	0,280	0,760	0,50	24	20	27	10	0,016
000-0065	Air Core Coil	0,290mH +/-3% 0,12Ω wire 1,60mm=14AWG OD-46 / 25mm	0,290	0,120	1,60	14	8	46	25	0,246
000-0843	Air Core Coil	0,290mH +/-3% 0,750Ω wire 0,50mm=24AWG OD-25 / 8mm	0,290	0,750	0,50	24	15	25	8	0,016
000-0868	Air Core Coil	0,290mH +/-3% 0,180Ω wire 1,20mm=17AWG OD-48 / 15mm	0,290	0,180	1,20	17	25	48	15	0,117
000-1643	Air Core Coil	0,290mH +/-3% 0,420Ω wire 0,70mm=21AWG OD-33 / 8mm	0,290	0,420	0,70	21	15	33	8	0,032
000-1644	Air Core Coil	0,290mH +/-3% 0,23Ω wire 1,00mm=18AWG OD-36 / 15mm	0,290	0,230	1,00	18	15	36	15	0,076

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1651	Air Core Coil	0,290mH +/-3% 0,520Q wire 0,63mm=22AWG OD-25 / 15mm	0,290	0,520	0,63	22	15	25	15	0,028
000-0954	Air Core Coil	0,300mH +/-3% 0,100Q wire 1,80mm=13AWG OD-52 / 30mm	0,300	0,100	1,80	13	25	52	30	0,325
000-0969	Air Core Coil	0,300mH +/-3% 1,35Q wire 0,40mm=26AWG OD-16 / 20mm	0,300	1,350	0,40	26	10	16	20	0,011
000-1027	Air Core Coil	0,300mH +/-3% 0,210Q wire 1,20mm=17AWG OD-39 / 30mm	0,300	0,210	1,20	17	25	39	30	0,134
000-1143	Air Core Coil	0,300mH +/-3% 0,550Q wire 0,63mm=22AWG OD-33 / 15mm	0,300	0,550	0,63	22	25	33	15	0,028
000-1163	Air Core Coil	0,300mH +/-3% 0,157Q wire 1,40mm=15AWG OD-43 / 30mm	0,300	0,157	1,40	15	25	43	30	0,183
000-1170	Air Core Coil	0,300mH +/-3% 0,440Q wire 0,70mm=21AWG OD-27 / 15mm	0,300	0,440	0,70	21	15	27	15	0,035
000-1223	Air Core Coil	0,300mH +/-3% 0,430Q wire 0,70mm=21AWG OD-34 / 10mm	0,300	0,430	0,70	21	20	34	10	0,035
000-1272	Air Core Coil	0,300mH +/-3% 0,144Q wire 1,40mm=15AWG OD-53 / 15mm	0,300	0,144	1,40	15	25	53	15	0,171
000-1313	Air Core Coil	0,300mH +/-3% 0,24Q wire 1,00mm=18AWG OD-36 / 15mm	0,300	0,240	1,00	18	15	36	15	0,080
000-1315	Air Core Coil	0,300mH +/-3% 0,260Q wire 1,00mm=18AWG OD-45 / 8mm	0,300	0,260	1,00	18	9	45	8	0,078
000-1335	Air Core Coil	0,300mH +/-3% 0,180Q wire 1,20mm=17AWG OD-48 / 15mm	0,300	0,180	1,20	17	25	48	15	0,118
000-1362	Air Core Coil	0,300mH +/-3% 0,540Q wire 0,70mm=21AWG OD-31 / 30mm	0,300	0,540	0,70	21	25	31	30	0,042
000-1452	Air Core Coil	0,300mH +/-3% 0,550Q wire 0,63mm=22AWG OD-25 / 15mm	0,300	0,550	0,63	22	15	25	15	0,028
000-1454	Air Core Coil	0,300mH +/-3% 0,500Q wire 0,63mm=22AWG OD-30 / 8mm	0,300	0,500	0,63	22	15	30	8	0,026
000-1483	Air Core Coil	0,300mH +/-3% 0,160Q wire 1,40mm=15AWG OD-40 / 25mm	0,300	0,160	1,40	15	8	40	25	0,193
000-1575	Air Core Coil	0,300mH +/-3% 0,18Q wire 1,20mm=17AWG OD-54 / 10mm	0,300	0,180	1,20	17	20	54	10	0,124
000-1803	Air Core Coil	0,300mH +/-3% 1,140Q wire 0,40mm=26AWG OD-22 / 8mm	0,300	1,140	0,40	26	15	22	8	0,010
000-1832	Air Core Coil	0,300mH +/-3% 0,370Q wire 0,80mm=20AWG OD-29 / 15mm	0,300	0,362	0,80	20	15	29	15	0,047
000-1833	Air Core Coil	0,300mH +/-3% 0,750Q wire 0,50mm=24AWG OD-25 / 8mm	0,300	0,750	0,50	24	15	25	8	0,016
000-1880	Air Core Coil	0,300mH +/-3% 0,430Q wire 0,70mm=21AWG OD-33 / 8mm	0,300	0,430	0,70	21	15	33	8	0,034
000-1883	Air Core Coil	0,300mH +/-3% 0,750Q wire 0,50mm=24AWG OD-22 / 8mm	0,300	0,750	0,50	24	9	22	8	0,016
000-1884	Air Core Coil	0,300mH +/-3% 1,100Q wire 0,40mm=26AWG OD-18 / 8mm	0,300	1,100	0,40	26	9	18	8	0,009
000-1885	Air Core Coil	0,300mH +/-3% 1,950Q wire 0,30mm=29AWG OD-19 / 8mm	0,300	1,950	0,30	29	15	19	8	0,005
000-0145	Air Core Coil	0,310mH +/-3% 0,24Q wire 1,00mm=18AWG OD-36 / 15mm	0,310	0,240	1,00	18	15	36	15	0,081
000-1433	Air Core Coil	0,310mH +/-3% 0,550Q wire 0,70mm=21AWG OD-31 / 30mm	0,310	0,550	0,70	21	25	31	30	0,043
000-1629	Air Core Coil	0,310mH +/-3% 0,160Q wire 1,40mm=15AWG OD-43 / 30mm	0,310	0,160	1,40	15	25	43	30	0,185
000-1685	Air Core Coil	0,310mH +/-3% 0,460Q wire 0,70mm=21AWG OD-27 / 15mm	0,310	0,460	0,70	21	15	27	15	0,035
000-0166	Air Core Coil	0,320mH +/-3% 0,10Q wire 1,80mm=13AWG OD-52 / 30mm	0,320	0,100	1,80	13	25	52	30	0,340
000-0173	Air Core Coil	0,320mH +/-3% 0,210Q wire 1,20mm=17AWG OD-39 / 30mm	0,320	0,210	1,20	17	25	39	30	0,137
000-0966	Air Core Coil	0,320mH +/-3% 0,88Q wire 0,50mm=24AWG OD-22 / 15mm	0,320	0,880	0,50	24	15	22	15	0,019
000-1059	Air Core Coil	0,320mH +/-3% 1,970Q wire 0,30mm=29AWG OD-15 / 8mm	0,320	1,970	0,30	29	9	15	8	0,005
000-1115	Air Core Coil	0,320mH +/-3% 0,366Q wire 0,80mm=20AWG OD-30 / 15mm	0,320	0,366	0,80	20	15	30	15	0,049
000-1172	Air Core Coil	0,320mH +/-3% 0,164Q wire 1,40mm=15AWG OD-43 / 30mm	0,320	0,164	1,40	15	25	43	30	0,187
000-1529	Air Core Coil	0,320mH +/-3% 0,560Q wire 0,63mm=22AWG OD-25 / 15mm	0,320	0,560	0,63	22	15	25	15	0,029
000-1661	Air Core Coil	0,320mH +/-3% 0,470Q wire 0,70mm=21AWG OD-27 / 15mm	0,320	0,470	0,70	21	15	27	15	0,036
000-0008	Air Core Coil	0,330mH +/-3% 0,129Q wire 1,60mm=14AWG OD-46 / 25mm	0,330	0,129	1,60	14	8	46	25	0,268
000-0108	Air Core Coil	0,330mH +/-3% 0,105Q wire 1,80mm=13AWG OD-52 / 30mm	0,330	0,105	1,80	13	25	52	30	0,342
000-0890	Air Core Coil	0,330mH +/-3% 0,170Q wire 1,40mm=15AWG OD-40 / 25mm	0,330	0,170	1,40	15	8	40	25	0,189
000-1021	Air Core Coil	0,330mH +/-3% 0,480Q wire 0,70mm=21AWG OD-28 / 15mm	0,330	0,480	0,70	21	15	28	15	0,037
000-1022	Air Core Coil	0,330mH +/-3% 0,260Q wire 1,00mm=18AWG OD-42 / 15mm	0,330	0,260	1,00	18	25	42	15	0,084
000-1071	Air Core Coil	0,330mH +/-3% 0,153Q wire 1,40mm=15AWG OD-53 / 15mm	0,330	0,153	1,40	15	25	53	15	0,179
000-1173	Air Core Coil	0,330mH +/-3% 0,220Q wire 1,20mm=17AWG OD-39 / 30mm	0,330	0,220	1,20	17	25	39	30	0,140
000-1214	Air Core Coil	0,330mH +/-3% 1,240Q wire 0,40mm=26AWG OD-25 / 10mm	0,330	1,240	0,40	26	20	25	10	0,011
000-1264	Air Core Coil	0,330mH +/-3% 0,445Q wire 0,70mm=21AWG OD-34 / 8mm	0,330	0,445	0,70	21	15	34	8	0,036
000-1310	Air Core Coil	0,330mH +/-3% 0,160Q wire 1,40mm=15AWG OD-44 / 30mm	0,330	0,160	1,40	15	25	44	30	0,193
000-1321	Air Core Coil	0,330mH +/-3% 0,790Q wire 0,50mm=24AWG OD-23 / 8mm	0,330	0,790	0,50	24	9	23	8	0,017
000-1513	Air Core Coil	0,330mH +/-3% 1,200Q wire 0,40mm=26AWG OD-22 / 8mm	0,330	1,200	0,40	26	15	22	8	0,010
000-1550	Air Core Coil	0,330mH +/-3% 2,000Q wire 0,30mm=29AWG OD-20 / 8mm	0,330	2,000	0,30	29	15	20	8	0,006
000-1551	Air Core Coil	0,330mH +/-3% 1,970Q wire 0,30mm=29AWG OD-15 / 8mm	0,330	1,970	0,30	29	9	15	8	0,005
000-1679	Air Core Coil	0,330mH +/-3% 0,26Q wire 1,00mm=18AWG OD-36 / 15mm	0,330	0,260	1,00	18	15	36	15	0,085
000-1712	Air Core Coil	0,330mH +/-3% 0,194Q wire 1,20mm=17AWG OD-48 / 15mm	0,330	0,194	1,20	17	25	48	15	0,127

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1743	Air Core Coil	0,330mH +/-3% 0,561Ω wire 0,70mm=21AWG OD-31 / 30mm	0,330	0,561	0,70	21	25	31	30	0,044
000-1746	Air Core Coil	0,330mH +/-3% 0,310Ω wire 1,00mm=18AWG OD-35 / 30mm	0,330	0,310	1,00	18	25	35	30	0,093
000-1754	Air Core Coil	0,330mH +/-3% 0,561Ω wire 0,70mm=21AWG OD-24 / 27mm	0,330	0,561	0,70	21	15	24	27	0,042
000-1757	Air Core Coil	0,330mH +/-3% 0,293Ω wire 1,00mm=18AWG OD-29 / 27mm	0,330	0,293	1,00	18	15	29	27	0,091
000-1834	Air Core Coil	0,330mH +/-3% 0,780Ω wire 0,50mm=24AWG OD-26 / 8mm	0,330	0,780	0,50	24	15	26	8	0,018
000-1835	Air Core Coil	0,330mH +/-3% 0,390Ω wire 0,80mm=20AWG OD-30 / 15mm	0,330	0,390	0,80	20	15	30	15	0,051
000-1890	Air Core Coil	0,330mH +/-3% 0,580Ω wire 0,63mm=22AWG OD-25 / 15mm	0,330	0,580	0,63	22	15	25	15	0,030
000-1987	Air Core Coil	0,330mH +/-3% 0,290Ω wire 1,00mm=18AWG OD-28 / 25mm	0,330	0,290	1,00	18	8	28	25	0,090
000-0832	Air Core Coil	0,340mH +/-3% 0,27Ω wire 1,00mm=18AWG OD-37 / 15mm	0,340	0,270	1,00	18	15	37	15	0,085
000-0859	Air Core Coil	0,340mH +/-3% 0,10Ω wire 1,80mm=13AWG OD-52 / 30mm	0,340	0,100	1,80	13	25	52	30	0,343
000-0869	Air Core Coil	0,340mH +/-3% 0,218Ω wire 1,20mm=17AWG OD-34 / 25mm	0,340	0,218	1,20	17	8	34	25	0,136
000-0908	Air Core Coil	0,340mH +/-3% 0,580Ω wire 0,63mm=22AWG OD-31 / 8mm	0,340	0,580	0,63	22	15	31	8	0,029
000-1911	Air Core Coil	0,340mH +/-3% 0,790Ω wire 0,50mm=24AWG OD-26 / 8mm	0,340	0,790	0,50	24	15	26	8	0,018
000-0860	Air Core Coil	0,350mH +/-3% 0,11Ω wire 1,80mm=13AWG OD-55 / 30mm	0,350	0,110	1,80	13	25	55	30	0,351
000-1009	Air Core Coil	0,350mH +/-3% 0,275Ω wire 1,00mm=18AWG OD-37 / 15mm	0,350	0,275	1,00	18	15	37	15	0,086
000-1204	Air Core Coil	0,350mH +/-3% 0,400Ω wire 0,80mm=20AWG OD-30 / 15mm	0,350	0,400	0,80	20	15	30	15	0,053
000-1332	Air Core Coil	0,350mH +/-3% 0,490Ω wire 0,70mm=21AWG OD-28 / 15mm	0,350	0,490	0,70	21	15	28	15	0,038
000-1354	Air Core Coil	0,350mH +/-3% 0,475Ω wire 0,70mm=21AWG OD-34 / 8mm	0,350	0,475	0,70	21	15	34	8	0,037
000-1363	Air Core Coil	0,350mH +/-3% 0,580Ω wire 0,70mm=21AWG OD-31 / 30mm	0,350	0,580	0,70	21	25	31	30	0,045
000-1417	Air Core Coil	0,350mH +/-3% 0,167Ω wire 1,40mm=15AWG OD-44 / 30mm	0,350	0,167	1,40	15	25	44	30	0,201
000-1450	Air Core Coil	0,350mH +/-3% 0,800Ω wire 0,50mm=24AWG OD-26 / 8mm	0,350	0,800	0,50	24	15	26	8	0,018
000-1453	Air Core Coil	0,350mH +/-3% 0,580Ω wire 0,63mm=22AWG OD-31 / 8mm	0,350	0,580	0,63	22	15	31	8	0,029
000-1836	Air Core Coil	0,350mH +/-3% 1,240Ω wire 0,40mm=26AWG OD-23 / 8mm	0,350	1,240	0,40	26	15	23	8	0,010
000-1876	Air Core Coil	0,350mH +/-3% 1,300Ω wire 0,40mm=26AWG OD-25 / 10mm	0,350	1,300	0,40	26	20	25	10	0,011
000-1979	Air Core Coil	0,350mH +/-3% 0,230Ω wire 1,20mm=17AWG OD-40 / 30mm	0,350	0,230	1,20	17	25	40	30	0,143
000-0054	Air Core Coil	0,360mH +/-3% 0,137Ω wire 1,60mm=14AWG OD-49 / 25mm	0,360	0,137	1,60	14	8	49	25	0,282
000-0737	Air Core Coil	0,360mH +/-3% 0,40Ω wire 0,80mm=20AWG OD-31 / 15mm	0,360	0,400	0,80	20	15	31	15	0,053
000-0968	Air Core Coil	0,360mH +/-3% 1,25Ω wire 0,40mm=26AWG OD-23 / 8mm	0,360	1,250	0,40	26	15	23	8	0,011
000-1082	Air Core Coil	0,360mH +/-3% 0,525Ω wire 0,70mm=21AWG OD-29 / 15mm	0,360	0,525	0,70	21	15	29	15	0,038
000-1153	Air Core Coil	0,360mH +/-3% 0,280Ω wire 1,00mm=18AWG OD-37 / 15mm	0,360	0,280	1,00	18	15	37	15	0,088
000-1415	Air Core Coil	0,360mH +/-3% 0,170Ω wire 1,40mm=15AWG OD-44 / 30mm	0,360	0,170	1,40	15	25	44	30	0,203
000-1432	Air Core Coil	0,360mH +/-3% 0,590Ω wire 0,70mm=21AWG OD-31 / 30mm	0,360	0,590	0,70	21	25	31	30	0,047
000-1628	Air Core Coil	0,360mH +/-3% 0,315Ω wire 1,00mm=18AWG OD-36 / 30mm	0,360	0,315	1,00	18	25	36	30	0,098
000-1729	Air Core Coil	0,360mH +/-3% 0,235Ω wire 1,20mm=17AWG OD-40 / 30mm	0,360	0,235	1,20	17	25	40	30	0,145
000-0140	Air Core Coil	0,370mH +/-3% 0,110Ω wire 1,80mm=13AWG OD-56 / 30mm	0,370	0,110	1,80	13	25	56	30	0,360
000-0858	Air Core Coil	0,370mH +/-3% 0,50Ω wire 0,70mm=21AWG OD-35 / 8mm	0,370	0,500	0,70	21	15	35	8	0,038
000-1116	Air Core Coil	0,370mH +/-3% 0,170Ω wire 1,40mm=15AWG OD-44 / 30mm	0,370	0,170	1,40	15	25	44	30	0,206
000-1117	Air Core Coil	0,370mH +/-3% 0,280Ω wire 1,00mm=18AWG OD-42 / 15mm	0,370	0,280	1,00	18	25	42	15	0,090
000-1177	Air Core Coil	0,370mH +/-3% 0,24Ω wire 1,20mm=17AWG OD-41 / 30mm	0,370	0,240	1,20	17	25	41	30	0,147
000-1178	Air Core Coil	0,370mH +/-3% 0,320Ω wire 1,00mm=18AWG OD-36 / 30mm	0,370	0,320	1,00	18	25	36	30	0,098
000-1179	Air Core Coil	0,370mH +/-3% 0,920Ω wire 0,50mm=24AWG OD-22 / 15mm	0,370	0,920	0,50	24	15	22	15	0,019
000-1317	Air Core Coil	0,370mH +/-3% 0,620Ω wire 0,63mm=22AWG OD-25 / 15mm	0,370	0,620	0,63	22	15	25	15	0,031
000-1343	Air Core Coil	0,370mH +/-3% 0,580Ω wire 0,63mm=22AWG OD-31 / 8mm	0,370	0,580	0,63	22	15	31	8	0,030
000-1344	Air Core Coil	0,370mH +/-3% 0,630Ω wire 0,63mm=22AWG OD-33 / 15mm	0,370	0,630	0,63	22	25	33	15	0,032
000-1492	Air Core Coil	0,370mH +/-3% 0,410Ω wire 0,80mm=20AWG OD-31 / 15mm	0,370	0,410	0,80	20	15	31	15	0,053
000-0231	Air Core Coil	0,380mH +/-3% 0,24Ω wire 1,20mm=17AWG OD-41 / 30mm	0,380	0,240	1,20	17	25	41	30	0,155
000-0862	Air Core Coil	0,380mH +/-3% 0,11Ω wire 1,80mm=13AWG OD-56 / 30mm	0,380	0,110	1,80	13	25	56	30	0,367
000-1004	Air Core Coil	0,380mH +/-3% 0,860Ω wire 0,50mm=24AWG OD-26 / 8mm	0,380	0,860	0,50	24	15	26	8	0,018
000-1773	Air Core Coil	0,380mH +/-3% 1,300Ω wire 0,40mm=26AWG OD-23 / 8mm	0,380	1,300	0,40	26	15	23	8	0,011
000-1837	Air Core Coil	0,380mH +/-3% 0,285Ω wire 1,00mm=18AWG OD-38 / 15mm	0,380	0,285	1,00	18	15	38	15	0,089
000-1593	Air Core Coil	0,383mH +/-5% 0,18Ω wire 1,40mm=15AWG OD-43 / 25mm	0,383	0,180	1,40	15	8	43	25	0,215
000-0986	Air Core Coil	0,385mH +/-5% 0,11Ω wire 1,80mm=13AWG OD-55 / 30mm	0,385	0,110	1,80	13	25	55	30	0,374



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0009	Air Core Coil	0,390mH +/-3% 0,140Ω wire 1,60mm=14AWG OD-50 / 25mm	0,390	0,140	1,60	14	8	50	25	0,295
000-0109	Air Core Coil	0,390mH +/-3% 0,111Ω wire 1,80mm=13AWG OD-55 / 30mm	0,390	0,110	1,80	13	25	55	30	0,374
000-1018	Air Core Coil	0,390mH +/-3% 0,527Ω wire 0,70mm=21AWG OD-29 / 15mm	0,390	0,527	0,70	21	15	29	15	0,041
000-1104	Air Core Coil	0,390mH +/-3% 0,290Ω wire 1,00mm=18AWG OD-42 / 15mm	0,390	0,290	1,00	18	25	42	15	0,092
000-1181	Air Core Coil	0,390mH +/-3% 0,240Ω wire 1,20mm=17AWG OD-41 / 30mm	0,390	0,240	1,20	17	25	41	30	0,155
000-1211	Air Core Coil	0,390mH +/-3% 0,322Ω wire 1,00mm=18AWG OD-37 / 30mm	0,390	0,322	1,00	18	25	37	30	0,100
000-1274	Air Core Coil	0,390mH +/-3% 0,167Ω wire 1,40mm=15AWG OD-56 / 15mm	0,390	0,167	1,40	15	25	56	15	0,199
000-1292	Air Core Coil	0,390mH +/-3% 0,498Ω wire 0,70mm=21AWG OD-35 / 8mm	0,390	0,498	0,70	21	15	35	8	0,039
000-1514	Air Core Coil	0,390mH +/-3% 1,300Ω wire 0,40mm=26AWG OD-23 / 8mm	0,390	1,300	0,40	26	15	23	8	0,011
000-1578	Air Core Coil	0,390mH +/-3% 0,211Ω wire 1,20mm=17AWG OD-58 / 10mm	0,390	0,210	1,20	17	20	58	10	0,145
000-1624	Air Core Coil	0,390mH +/-3% 0,285Ω wire 1,00mm=18AWG OD-42 / 12mm	0,390	0,285	1,00	18	17	42	12	0,090
000-1641	Air Core Coil	0,390mH +/-3% 0,205Ω wire 1,20mm=17AWG OD-50 / 15mm	0,390	0,205	1,20	17	25	50	15	0,139
000-1677	Air Core Coil	0,390mH +/-3% 0,293Ω wire 1,00mm=18AWG OD-38 / 15mm	0,390	0,293	1,00	18	15	38	15	0,090
000-1838	Air Core Coil	0,390mH +/-3% 0,860Ω wire 0,50mm=24AWG OD-26 / 8mm	0,390	0,860	0,50	24	15	26	8	0,018
000-1839	Air Core Coil	0,390mH +/-3% 0,420Ω wire 0,80mm=20AWG OD-31 / 15mm	0,390	0,420	0,80	20	15	31	15	0,054
000-1879	Air Core Coil	0,390mH +/-3% 2,40Ω wire 0,30mm=29AWG OD-18 / 15mm	0,390	2,400	0,30	29	15	18	15	0,007
000-1895	Air Core Coil	0,390mH +/-3% 0,170Ω wire 1,40mm=15AWG OD-46 / 30mm	0,390	0,170	1,40	15	25	46	30	0,211
000-1908	Air Core Coil	0,390mH +/-3% 0,600Ω wire 0,70mm=21AWG OD-22 / 25mm	0,390	0,600	0,70	21	8	22	25	0,046
000-1988	Air Core Coil	0,390mH +/-3% 0,320Ω wire 1,00mm=18AWG OD-29 / 25mm	0,390	0,320	1,00	18	8	29	25	0,103
000-0050	Air Core Coil	0,400mH +/-3% 0,140Ω wire 1,60mm=14AWG OD-50 / 25mm	0,400	0,140	1,60	14	8	50	25	0,300
000-0829	Air Core Coil	0,400mH +/-3% 0,111Ω wire 1,80mm=13AWG OD-56 / 30mm	0,400	0,110	1,80	13	25	56	30	0,382
000-1171	Air Core Coil	0,400mH +/-3% 0,598Ω wire 0,63mm=22AWG OD-32 / 8mm	0,400	0,598	0,63	22	15	32	8	0,031
000-1184	Air Core Coil	0,400mH +/-3% 0,960Ω wire 0,50mm=24AWG OD-23 / 15mm	0,400	0,960	0,50	24	15	23	15	0,020
000-1186	Air Core Coil	0,400mH +/-3% 0,180Ω wire 1,40mm=15AWG OD-46 / 30mm	0,400	0,180	1,40	15	25	46	30	0,218
000-1243	Air Core Coil	0,400mH +/-3% 0,167Ω wire 1,40mm=15AWG OD-56 / 15mm	0,400	0,167	1,40	15	25	56	15	0,201
000-1320	Air Core Coil	0,400mH +/-3% 0,890Ω wire 0,50mm=24AWG OD-24 / 8mm	0,400	0,890	0,50	24	9	24	8	0,019
000-1328	Air Core Coil	0,400mH +/-3% 0,890Ω wire 0,50mm=24AWG OD-27 / 8mm	0,400	0,890	0,50	24	15	27	8	0,019
000-1364	Air Core Coil	0,400mH +/-3% 0,640Ω wire 0,70mm=21AWG OD-32 / 30mm	0,400	0,640	0,70	21	25	32	30	0,049
000-1474	Air Core Coil	0,400mH +/-3% 0,530Ω wire 0,70mm=21AWG OD-29 / 15mm	0,400	0,530	0,70	21	15	29	15	0,041
000-1489	Air Core Coil	0,400mH +/-3% 0,640Ω wire 0,63mm=22AWG OD-26 / 15mm	0,400	0,640	0,63	22	15	26	15	0,033
000-1512	Air Core Coil	0,400mH +/-3% 0,245Ω wire 1,20mm=17AWG OD-41 / 30mm	0,400	0,245	1,20	17	25	41	30	0,156
000-1515	Air Core Coil	0,400mH +/-3% 0,212Ω wire 1,20mm=17AWG OD-45 / 15mm	0,400	0,212	1,20	17	15	45	15	0,141
000-1548	Air Core Coil	0,400mH +/-3% 0,183Ω wire 1,40mm=15AWG OD-43 / 25mm	0,400	0,183	1,40	15	8	43	25	0,225
000-1552	Air Core Coil	0,400mH +/-3% 2,230Ω wire 0,30mm=29AWG OD-16 / 8mm	0,400	2,230	0,30	29	9	16	8	0,006
000-1553	Air Core Coil	0,400mH +/-3% 2,50Ω wire 0,30mm=29AWG OD-18 / 15mm	0,400	2,500	0,30	29	15	18	15	0,007
000-1556	Air Core Coil	0,400mH +/-3% 1,700Ω wire 0,40mm=26AWG OD-14 / 25mm	0,400	1,700	0,40	26	8	14	25	0,015
000-1654	Air Core Coil	0,400mH +/-3% 0,300Ω wire 1,00mm=18AWG OD-35 / 22mm	0,400	0,300	1,00	18	19	35	22	0,098
000-1840	Air Core Coil	0,400mH +/-3% 0,430Ω wire 0,80mm=20AWG OD-32 / 15mm	0,400	0,430	0,80	20	15	32	15	0,055
000-1841	Air Core Coil	0,400mH +/-3% 0,330Ω wire 1,00mm=18AWG OD-37 / 30mm	0,400	0,330	1,00	18	25	37	30	0,104
000-1950	Air Core Coil	0,400mH +/-3% 0,290Ω wire 1,00mm=18AWG OD-43 / 15mm	0,400	0,290	1,00	18	25	43	15	0,094
000-1966	Air Core Coil	0,400mH +/-3% 0,294Ω wire 1,00mm=18AWG OD-38 / 15mm	0,400	0,294	1,00	18	15	38	15	0,093
000-0187	Air Core Coil	0,410mH +/-3% 0,18Ω wire 1,40mm=15AWG OD-46 / 30mm	0,410	0,180	1,40	15	25	46	30	0,220
000-0847	Air Core Coil	0,410mH +/-3% 0,12Ω wire 1,80mm=13AWG OD-56 / 30mm	0,410	0,120	1,80	13	25	56	30	0,383
000-1120	Air Core Coil	0,410mH +/-3% 0,435Ω wire 0,80mm=20AWG OD-32 / 15mm	0,410	0,435	0,80	20	15	32	15	0,057
000-1303	Air Core Coil	0,410mH +/-3% 0,300Ω wire 1,00mm=18AWG OD-38 / 15mm	0,410	0,300	1,00	18	15	38	15	0,094
000-1304	Air Core Coil	0,410mH +/-3% 0,300Ω wire 1,00mm=18AWG OD-37 / 20mm	0,410	0,300	1,00	18	20	37	20	0,090
000-1447	Air Core Coil	0,410mH +/-3% 0,580Ω wire 0,70mm=21AWG OD-29 / 20mm	0,410	0,580	0,70	21	20	29	20	0,044
000-0067	Air Core Coil	0,420mH +/-3% 0,140Ω wire 1,60mm=14AWG OD-51 / 25mm	0,420	0,140	1,60	14	8	51	25	0,311
000-0188	Air Core Coil	0,420mH +/-3% 0,12Ω wire 1,80mm=13AWG OD-56 / 30mm	0,420	0,120	1,80	13	25	56	30	0,386
000-1157	Air Core Coil	0,420mH +/-3% 0,980Ω wire 0,50mm=24AWG OD-23 / 15mm	0,420	0,980	0,50	24	15	23	15	0,021
000-1188	Air Core Coil	0,420mH +/-3% 0,440Ω wire 0,80mm=20AWG OD-32 / 15mm	0,420	0,440	0,80	20	15	32	15	0,057
000-1189	Air Core Coil	0,420mH +/-3% 0,190Ω wire 1,40mm=15AWG OD-46 / 30mm	0,420	0,190	1,40	15	25	46	30	0,220



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1190	Air Core Coil	0,420mH +/-3% 1,520Ω wire 0,40mm=26AWG OD-21 / 15mm	0,420	1,520	0,40	26	15	21	15	0,013
000-1404	Air Core Coil	0,420mH +/-3% 0,540Ω wire 0,70mm=21AWG OD-29 / 15mm	0,420	0,540	0,70	21	15	29	15	0,042
000-1451	Air Core Coil	0,420mH +/-3% 0,650Ω wire 0,63mm=22AWG OD-26 / 15mm	0,420	0,650	0,63	22	15	26	15	0,034
000-1574	Air Core Coil	0,420mH +/-3% 0,22Ω wire 1,20mm=17AWG OD-58 / 10mm	0,420	0,220	1,20	17	20	58	10	0,150
000-1577	Air Core Coil	0,420mH +/-3% 0,30Ω wire 1,00mm=18AWG OD-37 / 20mm	0,420	0,300	1,00	18	20	37	20	0,095
000-1976	Air Core Coil	0,420mH +/-3% 0,250Ω wire 1,20mm=17AWG OD-41 / 30mm	0,420	0,250	1,20	17	25	41	30	0,157
000-0911	Air Core Coil	0,424mH +/-5% 0,303Ω wire 1,00mm=18AWG OD-44 / 15mm	0,424	0,303	1,00	18	25	44	15	0,095
000-0199	Air Core Coil	0,430mH +/-3% 0,190Ω wire 1,40mm=15AWG OD-46 / 30mm	0,430	0,190	1,40	15	25	46	30	0,223
000-0204	Air Core Coil	0,430mH +/-3% 0,385Ω wire 1,00mm=18AWG OD-26 / 40mm	0,430	0,385	1,00	18	10	26	40	0,120
000-0820	Air Core Coil	0,430mH +/-3% 0,310Ω wire 1,00mm=18AWG OD-45 / 15mm	0,430	0,300	1,00	18	25	45	15	0,097
000-0899	Air Core Coil	0,430mH +/-3% 0,670Ω wire 0,63mm=22AWG OD-34 / 15mm	0,430	0,670	0,63	22	25	34	15	0,034
000-1121	Air Core Coil	0,430mH +/-3% 0,445Ω wire 0,80mm=20AWG OD-32 / 15mm	0,430	0,445	0,80	20	15	32	15	0,058
000-1842	Air Core Coil	0,430mH +/-3% 0,910Ω wire 0,50mm=24AWG OD-27 / 8mm	0,430	0,910	0,50	24	15	27	8	0,020
000-1968	Air Core Coil	0,430mH +/-3% 0,545Ω wire 0,70mm=21AWG OD-29 / 15mm	0,430	0,545	0,70	21	15	29	15	0,042
000-0198	Air Core Coil	0,440mH +/-3% 0,190Ω wire 1,40mm=15AWG OD-46 / 30mm	0,440	0,190	1,40	15	25	46	30	0,225
000-1191	Air Core Coil	0,440mH +/-3% 0,310Ω wire 1,00mm=18AWG OD-45 / 15mm	0,440	0,310	1,00	18	25	45	15	0,098
000-1192	Air Core Coil	0,440mH +/-3% 0,680Ω wire 0,63mm=22AWG OD-34 / 15mm	0,440	0,680	0,63	22	25	34	15	0,035
000-1390	Air Core Coil	0,440mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-41 / 30mm	0,440	0,260	1,20	17	25	41	30	0,159
000-1391	Air Core Coil	0,440mH +/-3% 1,320Ω wire 0,40mm=26AWG OD-26 / 10mm	0,440	1,320	0,40	26	20	26	10	0,012
000-1460	Air Core Coil	0,440mH +/-3% 0,455Ω wire 0,80mm=20AWG OD-32 / 15mm	0,440	0,455	0,80	20	15	32	15	0,059
000-1974	Air Core Coil	0,440mH +/-3% 0,560Ω wire 0,70mm=21AWG OD-29 / 15mm	0,440	0,560	0,70	21	15	29	15	0,043
000-0053	Air Core Coil	0,450mH +/-3% 0,160Ω wire 1,60mm=14AWG OD-51 / 30mm	0,450	0,160	1,60	14	25	51	30	0,315
000-0068	Air Core Coil	0,450mH +/-3% 0,15Ω wire 1,60mm=14AWG OD-51 / 25mm	0,450	0,150	1,60	14	8	51	25	0,321
000-1193	Air Core Coil	0,450mH +/-3% 0,980Ω wire 0,50mm=24AWG OD-29 / 10mm	0,450	0,980	0,50	24	20	29	10	0,021
000-1194	Air Core Coil	0,450mH +/-3% 1,560Ω wire 0,40mm=26AWG OD-21 / 15mm	0,450	1,560	0,40	26	15	21	15	0,013
000-1195	Air Core Coil	0,450mH +/-3% 0,460Ω wire 0,80mm=20AWG OD-32 / 15mm	0,450	0,460	0,80	20	15	32	15	0,061
000-1196	Air Core Coil	0,450mH +/-3% 0,310Ω wire 1,00mm=18AWG OD-39 / 15mm	0,450	0,310	1,00	18	15	39	15	0,098
000-1365	Air Core Coil	0,450mH +/-3% 0,660Ω wire 0,70mm=21AWG OD-32 / 30mm	0,450	0,660	0,70	21	25	32	30	0,053
000-1400	Air Core Coil	0,450mH +/-3% 0,940Ω wire 0,50mm=24AWG OD-27 / 8mm	0,450	0,940	0,50	24	15	27	8	0,020
000-1655	Air Core Coil	0,450mH +/-3% 0,190Ω wire 1,40mm=15AWG OD-46 / 30mm	0,450	0,190	1,40	15	25	46	30	0,239
000-1927	Air Core Coil	0,450mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-41 / 30mm	0,450	0,260	1,20	17	25	41	30	0,160
000-0249	Air Core Coil	0,460mH +/-3% 0,18Ω wire 1,40mm=15AWG OD-60 / 15mm	0,460	0,180	1,40	15	25	60	15	0,226
000-1197	Air Core Coil	0,460mH +/-3% 1,000Ω wire 0,50mm=24AWG OD-29 / 10mm	0,460	1,000	0,50	24	20	29	10	0,021
000-1213	Air Core Coil	0,460mH +/-3% 1,390Ω wire 0,40mm=26AWG OD-23 / 8mm	0,460	1,390	0,40	26	15	23	8	0,012
000-1331	Air Core Coil	0,460mH +/-3% 0,560Ω wire 0,70mm=21AWG OD-29 / 15mm	0,460	0,560	0,70	21	15	29	15	0,043
000-1877	Air Core Coil	0,460mH +/-3% 1,470Ω wire 0,40mm=26AWG OD-26 / 10mm	0,460	1,470	0,40	26	20	26	10	0,013
000-1977	Air Core Coil	0,460mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-41 / 30mm	0,460	0,260	1,20	17	25	41	30	0,162
000-0010	Air Core Coil	0,470mH +/-3% 0,164Ω wire 1,60mm=14AWG OD-52 / 30mm	0,470	0,164	1,60	14	25	52	30	0,322
000-0110	Air Core Coil	0,470mH +/-3% 0,130Ω wire 1,80mm=13AWG OD-59 / 30mm	0,470	0,130	1,80	13	25	59	30	0,409
000-0887	Air Core Coil	0,470mH +/-3% 0,250Ω wire 1,20mm=17AWG OD-50 / 15mm	0,470	0,250	1,20	17	25	50	15	0,159
000-0967	Air Core Coil	0,470mH +/-3% 1,70Ω wire 0,40mm=26AWG OD-20 / 20mm	0,470	1,700	0,40	26	10	17	20	0,014
000-1030	Air Core Coil	0,470mH +/-3% 0,570Ω wire 0,70mm=21AWG OD-29 / 15mm	0,470	0,570	0,70	21	15	29	15	0,045
000-1031	Air Core Coil	0,470mH +/-3% 0,320Ω wire 1,00mm=18AWG OD-45 / 15mm	0,470	0,320	1,00	18	25	45	15	0,103
000-1198	Air Core Coil	0,470mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-41 / 30mm	0,470	0,260	1,20	17	25	41	30	0,164
000-1242	Air Core Coil	0,470mH +/-3% 0,190Ω wire 1,40mm=15AWG OD-59 / 15mm	0,470	0,190	1,40	15	25	59	15	0,218
000-1281	Air Core Coil	0,470mH +/-3% 0,320Ω wire 1,00mm=18AWG OD-40 / 15mm	0,470	0,320	1,00	18	15	40	15	0,102
000-1294	Air Core Coil	0,470mH +/-3% 0,690Ω wire 0,63mm=22AWG OD-27 / 15mm	0,470	0,690	0,63	22	15	27	15	0,036
000-1297	Air Core Coil	0,470mH +/-3% 0,730Ω wire 0,63mm=22AWG OD-34 / 15mm	0,470	0,730	0,63	22	25	34	15	0,036
000-1518	Air Core Coil	0,470mH +/-3% 0,200Ω wire 1,40mm=15AWG OD-46 / 30mm	0,470	0,200	1,40	15	25	46	30	0,232
000-1539	Air Core Coil	0,470mH +/-3% 0,330Ω wire 1,00mm=18AWG OD-37 / 20mm	0,470	0,330	1,00	18	20	37	20	0,093
000-1636	Air Core Coil	0,470mH +/-3% 1,350Ω wire 0,40mm=26AWG OD-20 / 8mm	0,470	1,350	0,40	26	9	20	8	0,012
000-1747	Air Core Coil	0,470mH +/-3% 0,355Ω wire 1,00mm=18AWG OD-37 / 30mm	0,470	0,355	1,00	18	25	37	30	0,112



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1758	Air Core Coil	0,470mH +/-3% 0,351Ω wire 1,00mm=18AWG OD-33 / 27mm	0,470	0,351	1,00	18	15	33	27	0,111
000-1760	Air Core Coil	0,470mH +/-3% 0,259Ω wire 1,20mm=17AWG OD-38 / 27mm	0,470	0,259	1,20	17	15	38	27	0,167
000-1843	Air Core Coil	0,470mH +/-3% 0,470Ω wire 0,80mm=20AWG OD-32 / 15mm	0,470	0,470	0,80	20	15	32	15	0,062
000-1845	Air Core Coil	0,470mH +/-3% 0,950Ω wire 0,50mm=24AWG OD-27 / 8mm	0,470	0,950	0,50	24	15	27	8	0,021
000-1989	Air Core Coil	0,470mH +/-3% 0,360Ω wire 1,00mm=18AWG OD-31 / 25mm	0,470	0,360	1,00	18	8	31	25	0,111
000-0209	Air Core Coil	0,480mH +/-3% 0,200Ω wire 1,40mm=15AWG OD-46 / 30mm	0,480	0,200	1,40	15	25	46	30	0,232
000-0703	Air Core Coil	0,480mH +/-3% 0,47Ω wire 0,80mm=20AWG OD-33 / 15mm	0,480	0,470	0,80	20	15	33	15	0,063
000-1054	Air Core Coil	0,480mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-41 / 30mm	0,480	0,260	1,20	17	25	41	30	0,168
000-1201	Air Core Coil	0,480mH +/-3% 0,325Ω wire 1,00mm=18AWG OD-45 / 15mm	0,480	0,325	1,00	18	25	45	15	0,104
000-1573	Air Core Coil	0,480mH +/-3% 0,24Ω wire 1,20mm=17AWG OD-61 / 10mm	0,480	0,240	1,20	17	20	61	10	0,162
000-1755	Air Core Coil	0,480mH +/-3% 0,700Ω wire 0,70mm=21AWG OD-25 / 27mm	0,480	0,700	0,70	21	15	25	27	0,053
000-1762	Air Core Coil	0,480mH +/-3% 0,690Ω wire 0,70mm=21AWG OD-32 / 30mm	0,480	0,690	0,70	21	25	32	30	0,054
000-0175	Air Core Coil	0,490mH +/-3% 0,13Ω wire 1,80mm=13AWG OD-59 / 30mm	0,490	0,130	1,80	13	25	59	30	0,433
000-0194	Air Core Coil	0,490mH +/-3% 0,201Ω wire 1,40mm=15AWG OD-46 / 30mm	0,490	0,201	1,40	15	25	46	30	0,236
000-0228	Air Core Coil	0,490mH +/-3% 0,26Ω wire 1,20mm=17AWG OD-41 / 30mm	0,490	0,260	1,20	17	25	41	30	0,175
000-1055	Air Core Coil	0,490mH +/-3% 2,29Ω wire 0,30mm=29AWG OD-16 / 8mm	0,490	2,290	0,30	29	9	16	8	0,007
000-1122	Air Core Coil	0,490mH +/-3% 0,477Ω wire 0,80mm=20AWG OD-33 / 15mm	0,490	0,477	0,80	20	15	33	15	0,063
000-1202	Air Core Coil	0,490mH +/-3% 1,630Ω wire 0,40mm=26AWG OD-21 / 15mm	0,490	1,630	0,40	26	15	21	15	0,014
000-1203	Air Core Coil	0,490mH +/-3% 0,325Ω wire 1,00mm=18AWG OD-40 / 15mm	0,490	0,325	1,00	18	15	40	15	0,104
000-1689	Air Core Coil	0,490mH +/-3% 0,580Ω wire 0,70mm=21AWG OD-30 / 15mm	0,490	0,580	0,70	21	15	30	15	0,046
000-0734	Air Core Coil	0,500mH +/-3% 2,31Ω wire 0,30mm=29AWG OD-16 / 8mm	0,500	2,310	0,30	29	9	16	8	0,007
000-0835	Air Core Coil	0,500mH +/-3% 0,70Ω wire 0,70mm=21AWG OD-23 / 25mm	0,500	0,700	0,70	21	8	23	25	0,053
000-0855	Air Core Coil	0,500mH +/-3% 0,71Ω wire 0,63mm=22AWG OD-27 / 15mm	0,500	0,710	0,63	22	15	27	15	0,038
000-0883	Air Core Coil	0,500mH +/-3% 1,080Ω wire 0,50mm=24AWG OD-23 / 15mm	0,500	1,080	0,50	24	15	23	15	0,022
000-0950	Air Core Coil	0,500mH +/-3% 0,260Ω wire 1,20mm=17AWG OD-40 / 25mm	0,500	0,260	1,20	17	15	40	25	0,170
000-0981	Air Core Coil	0,500mH +/-3% 0,160Ω wire 1,60mm=14AWG OD-53 / 30mm	0,500	0,160	1,60	14	25	53	30	0,331
000-1034	Air Core Coil	0,500mH +/-3% 0,490Ω wire 0,80mm=20AWG OD-33 / 15mm	0,500	0,490	0,80	20	15	33	15	0,063
000-1205	Air Core Coil	0,500mH +/-3% 0,280Ω wire 1,20mm=17AWG OD-41 / 30mm	0,500	0,280	1,20	17	25	41	30	0,176
000-1267	Air Core Coil	0,500mH +/-3% 0,203Ω wire 1,40mm=15AWG OD-48 / 30mm	0,500	0,203	1,40	15	25	48	30	0,238
000-1327	Air Core Coil	0,500mH +/-3% 1,000Ω wire 0,50mm=24AWG OD-28 / 8mm	0,500	1,000	0,50	24	15	28	8	0,022
000-1366	Air Core Coil	0,500mH +/-3% 0,700Ω wire 0,70mm=21AWG OD-32 / 30mm	0,500	0,700	0,70	21	25	32	30	0,055
000-1389	Air Core Coil	0,500mH +/-3% 1,530Ω wire 0,40mm=26AWG OD-26 / 10mm	0,500	1,530	0,40	26	20	26	10	0,014
000-1401	Air Core Coil	0,500mH +/-3% 0,330Ω wire 1,00mm=18AWG OD-40 / 15mm	0,500	0,330	1,00	18	15	40	15	0,107
000-1402	Air Core Coil	0,500mH +/-3% 0,340Ω wire 1,00mm=18AWG OD-39 / 20mm	0,500	0,340	1,00	18	20	39	20	0,107
000-1403	Air Core Coil	0,500mH +/-3% 0,380Ω wire 1,00mm=18AWG OD-39 / 30mm	0,500	0,380	1,00	18	25	39	30	0,118
000-1405	Air Core Coil	0,500mH +/-3% 0,580Ω wire 0,70mm=21AWG OD-30 / 15mm	0,500	0,580	0,70	21	15	30	15	0,047
000-1505	Air Core Coil	0,500mH +/-3% 0,248Ω wire 1,20mm=17AWG OD-48 / 15mm	0,500	0,248	1,20	17	15	48	15	0,158
000-1555	Air Core Coil	0,500mH +/-3% 1,500Ω wire 0,40mm=26AWG OD-24 / 8mm	0,500	1,500	0,40	26	15	24	8	0,013
000-1596	Air Core Coil	0,500mH +/-3% 0,670Ω wire 0,63mm=22AWG OD-33 / 8mm	0,500	0,670	0,63	22	15	33	8	0,035
000-1881	Air Core Coil	0,500mH +/-3% 0,640Ω wire 0,70mm=21AWG OD-30 / 20mm	0,500	0,640	0,70	21	20	30	20	0,050
000-0174	Air Core Coil	0,510mH +/-3% 0,132Ω wire 1,80mm=13AWG OD-59 / 30mm	0,510	0,132	1,80	13	25	59	30	0,441
000-0195	Air Core Coil	0,510mH +/-3% 0,204Ω wire 1,40mm=15AWG OD-48 / 30mm	0,510	0,204	1,40	15	25	48	30	0,250
000-1123	Air Core Coil	0,510mH +/-3% 0,495Ω wire 0,80mm=20AWG OD-33 / 15mm	0,510	0,495	0,80	20	15	33	15	0,064
000-1319	Air Core Coil	0,510mH +/-3% 1,010Ω wire 0,50mm=24AWG OD-25 / 8mm	0,510	1,010	0,50	24	9	25	8	0,021
000-1431	Air Core Coil	0,510mH +/-3% 0,710Ω wire 0,70mm=21AWG OD-32 / 30mm	0,510	0,710	0,70	21	25	32	30	0,056
000-0977	Air Core Coil	0,518mH +/-5% 2,52Ω wire 0,30mm=29AWG OD-19 / 15mm	0,518	2,520	0,30	29	15	19	15	0,009
000-0714	Air Core Coil	0,520mH +/-3% 0,34Ω wire 1,00mm=18AWG OD-40 / 15mm	0,520	0,340	1,00	18	15	40	15	0,108
000-0924	Air Core Coil	0,520mH +/-3% 0,261Ω wire 1,20mm=17AWG OD-52 / 15mm	0,520	0,261	1,20	17	25	52	15	0,162
000-0925	Air Core Coil	0,520mH +/-3% 0,26Ω wire 1,20mm=17AWG OD-41 / 25mm	0,520	0,261	1,20	17	15	41	25	0,175
000-1479	Air Core Coil	0,520mH +/-3% 0,210Ω wire 1,40mm=15AWG OD-48 / 30mm	0,520	0,210	1,40	15	25	48	30	0,253
000-1545	Air Core Coil	0,520mH +/-3% 0,340Ω wire 1,00mm=18AWG OD-46 / 15mm	0,520	0,340	1,00	18	25	46	15	0,107
000-1665	Air Core Coil	0,520mH +/-3% 0,590Ω wire 0,70mm=21AWG OD-30 / 15mm	0,520	0,590	0,70	21	15	30	15	0,047



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0099	Air Core Coil	0,530mH +/-3% 0,135Ω wire 1,80mm=13AWG OD-59 / 30mm	0,530	0,135	1,80	13	25	59	30	0,459
000-0210	Air Core Coil	0,530mH +/-3% 0,210Ω wire 1,40mm=15AWG OD-48 / 30mm	0,530	0,210	1,40	15	25	48	30	0,255
000-0995	Air Core Coil	0,530mH +/-3% 0,295Ω wire 1,20mm=17AWG OD-43 / 30mm	0,530	0,295	1,20	17	25	43	30	0,177
000-1124	Air Core Coil	0,530mH +/-3% 0,500Ω wire 0,80mm=20AWG OD-34 / 15mm	0,530	0,500	0,80	20	15	34	15	0,066
000-0178	Air Core Coil	0,540mH +/-3% 0,21Ω wire 1,40mm=15AWG OD-49 / 30mm	0,540	0,210	1,40	15	25	49	30	0,257
000-0180	Air Core Coil	0,540mH +/-3% 0,14Ω wire 1,80mm=13AWG OD-59 / 30mm	0,540	0,140	1,80	13	25	59	30	0,465
000-0929	Air Core Coil	0,540mH +/-3% 0,385Ω wire 1,00mm=18AWG OD-33 / 25mm	0,540	0,385	1,00	18	8	33	25	0,120
000-0961	Air Core Coil	0,550mH +/-3% 0,360Ω wire 1,00mm=18AWG OD-39 / 20mm	0,550	0,360	1,00	18	20	39	20	0,111
000-1036	Air Core Coil	0,550mH +/-3% 0,220Ω wire 1,40mm=15AWG OD-49 / 30mm	0,550	0,220	1,40	15	25	49	30	0,253
000-1145	Air Core Coil	0,550mH +/-3% 0,750Ω wire 0,63mm=22AWG OD-27 / 15mm	0,550	0,750	0,63	22	15	27	15	0,039
000-1209	Air Core Coil	0,550mH +/-3% 0,600Ω wire 0,70mm=21AWG OD-30 / 15mm	0,550	0,600	0,70	21	15	30	15	0,049
000-1435	Air Core Coil	0,550mH +/-3% 1,520Ω wire 0,40mm=26AWG OD-24 / 8mm	0,550	1,520	0,40	26	15	24	8	0,013
000-1509	Air Core Coil	0,550mH +/-3% 0,300Ω wire 1,20mm=17AWG OD-43 / 30mm	0,550	0,300	1,20	17	25	43	30	0,182
000-1846	Air Core Coil	0,550mH +/-3% 0,500Ω wire 0,80mm=20AWG OD-34 / 15mm	0,550	0,500	0,80	20	15	34	15	0,068
000-0011	Air Core Coil	0,560mH +/-3% 0,180Ω wire 1,60mm=14AWG OD-54 / 30mm	0,560	0,180	1,60	14	25	54	30	0,356
000-0111	Air Core Coil	0,560mH +/-3% 0,140Ω wire 1,80mm=13AWG OD-59 / 30mm	0,560	0,140	1,80	13	25	59	30	0,470
000-0888	Air Core Coil	0,560mH +/-3% 0,272Ω wire 1,20mm=17AWG OD-55 / 15mm	0,560	0,272	1,20	17	25	55	15	0,172
000-1026	Air Core Coil	0,560mH +/-3% 0,760Ω wire 0,63mm=22AWG OD-27 / 15mm	0,560	0,760	0,63	22	15	27	15	0,039
000-1035	Air Core Coil	0,560mH +/-3% 0,360Ω wire 1,00mm=18AWG OD-46 / 15mm	0,560	0,360	1,00	18	25	46	15	0,111
000-1040	Air Core Coil	0,560mH +/-3% 0,610Ω wire 0,70mm=21AWG OD-30 / 15mm	0,560	0,610	0,70	21	15	30	15	0,050
000-1161	Air Core Coil	0,560mH +/-3% 1,530Ω wire 0,40mm=26AWG OD-24 / 8mm	0,560	1,530	0,40	26	15	24	8	0,013
000-1210	Air Core Coil	0,560mH +/-3% 0,300Ω wire 1,20mm=17AWG OD-43 / 30mm	0,560	0,300	1,20	17	25	43	30	0,182
000-1373	Air Core Coil	0,560mH +/-3% 0,400Ω wire 1,00mm=18AWG OD-39 / 30mm	0,560	0,400	1,00	18	25	39	30	0,124
000-1407	Air Core Coil	0,560mH +/-3% 0,45Ω wire 1,00mm=18AWG OD-30 / 40mm	0,560	0,450	1,00	18	10	30	40	0,139
000-1572	Air Core Coil	0,560mH +/-3% 0,27Ω wire 1,20mm=17AWG OD-46 / 20mm	0,560	0,270	1,20	17	20	46	20	0,177
000-1678	Air Core Coil	0,560mH +/-3% 0,345Ω wire 1,00mm=18AWG OD-40 / 15mm	0,560	0,345	1,00	18	15	40	15	0,116
000-1847	Air Core Coil	0,560mH +/-3% 1,100Ω wire 0,50mm=24AWG OD-28 / 8mm	0,560	1,100	0,50	24	15	28	8	0,023
000-1848	Air Core Coil	0,560mH +/-3% 0,510Ω wire 0,80mm=20AWG OD-34 / 15mm	0,560	0,510	0,80	20	15	34	15	0,068
000-1896	Air Core Coil	0,560mH +/-3% 0,220Ω wire 1,40mm=15AWG OD-49 / 30mm	0,560	0,220	1,40	15	25	49	30	0,258
000-1990	Air Core Coil	0,560mH +/-3% 0,390Ω wire 1,00mm=18AWG OD-33 / 25mm	0,560	0,390	1,00	18	8	33	25	0,125
000-0155	Air Core Coil	0,580mH +/-3% 0,51Ω wire 0,80mm=20AWG OD-33 / 15mm	0,580	0,510	0,80	20	15	33	15	0,069
000-1039	Air Core Coil	0,580mH +/-3% 2,820Ω wire 0,30mm=29AWG OD-17 / 8mm	0,580	2,820	0,30	29	9	17	8	0,007
000-1302	Air Core Coil	0,580mH +/-3% 0,310Ω wire 1,20mm=17AWG OD-43 / 30mm	0,580	0,310	1,20	17	25	43	30	0,187
000-1700	Air Core Coil	0,580mH +/-3% 3,120Ω wire 0,30mm=29AWG OD-19 / 15mm	0,580	3,120	0,30	29	15	19	15	0,009
000-1439	Air Core Coil	0,590mH +/-3% 0,815Ω wire 0,63mm=22AWG OD-28 / 15mm	0,590	0,815	0,63	22	15	28	15	0,040
000-0052	Air Core Coil	0,600mH +/-3% 0,184Ω wire 1,60mm=14AWG OD-54 / 30mm	0,600	0,184	1,60	14	25	54	30	0,370
000-0151	Air Core Coil	0,600mH +/-3% 0,150Ω wire 1,80mm=13AWG OD-62 / 30mm	0,600	0,150	1,80	13	25	62	30	0,480
000-0213	Air Core Coil	0,600mH +/-3% 3,18Ω wire 0,30mm=29AWG OD-19 / 15mm	0,600	3,180	0,30	29	15	19	15	0,009
000-0912	Air Core Coil	0,600mH +/-3% 0,279Ω wire 1,20mm=17AWG OD-56 / 15mm	0,600	0,279	1,20	17	25	56	15	0,173
000-1367	Air Core Coil	0,600mH +/-3% 0,770Ω wire 0,70mm=21AWG OD-32 / 30mm	0,600	0,770	0,70	21	25	32	30	0,061
000-1406	Air Core Coil	0,600mH +/-3% 0,630Ω wire 0,70mm=21AWG OD-30 / 15mm	0,600	0,630	0,70	21	15	30	15	0,054
000-1444	Air Core Coil	0,600mH +/-3% 0,230Ω wire 1,40mm=15AWG OD-49 / 30mm	0,600	0,230	1,40	15	25	49	30	0,268
000-1511	Air Core Coil	0,600mH +/-3% 0,310Ω wire 1,20mm=17AWG OD-43 / 30mm	0,600	0,310	1,20	17	25	43	30	0,191
000-1571	Air Core Coil	0,600mH +/-3% 0,28Ω wire 1,20mm=17AWG OD-48 / 20mm	0,600	0,280	1,20	17	20	48	20	0,184
000-1735	Air Core Coil	0,600mH +/-3% 1,600Ω wire 0,40mm=26AWG OD-24 / 8mm	0,600	1,600	0,40	26	15	24	8	0,014
000-1761	Air Core Coil	0,600mH +/-3% 0,294Ω wire 1,20mm=17AWG OD-41 / 27mm	0,600	0,294	1,20	17	15	41	27	0,193
000-1849	Air Core Coil	0,600mH +/-3% 1,120Ω wire 0,50mm=24AWG OD-29 / 8mm	0,600	1,120	0,50	24	15	29	8	0,024
000-1850	Air Core Coil	0,600mH +/-3% 0,530Ω wire 0,80mm=20AWG OD-35 / 15mm	0,600	0,530	0,80	20	15	35	15	0,071
000-1851	Air Core Coil	0,600mH +/-3% 0,410Ω wire 1,00mm=18AWG OD-39 / 30mm	0,600	0,410	1,00	18	25	39	30	0,129
000-1951	Air Core Coil	0,600mH +/-3% 0,370Ω wire 1,00mm=18AWG OD-47 / 15mm	0,600	0,370	1,00	18	25	47	15	0,117
000-1967	Air Core Coil	0,600mH +/-3% 0,370Ω wire 1,00mm=18AWG OD-44 / 15mm	0,600	0,370	1,00	18	15	44	15	0,116
000-1991	Air Core Coil	0,600mH +/-3% 0,410Ω wire 1,00mm=18AWG OD-33 / 25mm	0,600	0,410	1,00	18	8	33	25	0,129



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

		diametro interno diametro esterno									
codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	ø [mm]	ø [mm]	Altezza [mm]	Peso [kg]		
000-0987	Air Core Coil 0,610mH +/-3% 0,22Ω wire 1,40mm=15AWG OD-49 / 30mm	0,610	0,220	1,40	15	25		49	30	0,278	
000-1353	Air Core Coil 0,610mH +/-3% 0,820Ω wire 0,63mm=22AWG OD-28 / 15mm	0,610	0,820	0,63	22	15		28	15	0,041	
000-0012	Air Core Coil 0,620mH +/-3% 0,189Ω wire 1,60mm=14AWG OD-54 / 30mm	0,620	0,189	1,60	14	25		54	30	0,375	
000-0112	Air Core Coil 0,620mH +/-3% 0,150Ω wire 1,80mm=13AWG OD-62 / 30mm	0,620	0,150	1,80	13	25		62	30	0,483	
000-0716	Air Core Coil 0,620mH +/-3% 0,320Ω wire 1,20mm=17AWG OD-43 / 30mm	0,620	0,320	1,20	17	25		43	30	0,197	
000-0927	Air Core Coil 0,620mH +/-3% 0,380Ω wire 1,00mm=18AWG OD-47 / 15mm	0,620	0,380	1,00	18	25		47	15	0,120	
000-0988	Air Core Coil 0,620mH +/-3% 0,22Ω wire 1,40mm=15AWG OD-49 / 30mm	0,620	0,220	1,40	15	25		49	30	0,279	
000-1265	Air Core Coil 0,620mH +/-3% 1,140Ω wire 0,50mm=24AWG OD-29 / 8mm	0,620	1,140	0,50	24	15		29	8	0,024	
000-1558	Air Core Coil 0,620mH +/-3% 0,550Ω wire 0,80mm=20AWG OD-35 / 15mm	0,620	0,550	0,80	20	15		35	15	0,072	
000-1668	Air Core Coil 0,620mH +/-3% 0,650Ω wire 0,70mm=21AWG OD-30 / 15mm	0,620	0,650	0,70	21	15		30	15	0,055	
000-0165	Air Core Coil 0,630mH +/-3% 0,23Ω wire 1,40mm=15AWG OD-49 / 30mm	0,630	0,230	1,40	15	25		49	30	0,280	
000-0214	Air Core Coil 0,630mH +/-3% 3,19Ω wire 0,30mm=29AWG OD-19 / 15mm	0,630	3,190	0,30	29	15		19	15	0,010	
000-0244	Air Core Coil 0,630mH +/-3% 0,18Ω wire 1,60mm=14AWG OD-55 / 30mm	0,630	0,180	1,60	14	25		55	30	0,380	
000-1398	Air Core Coil 0,637mH +/-5% 0,890Ω wire 0,63mm=22AWG OD-29 / 15mm	0,637	0,890	0,63	22	15		29	15	0,042	
000-0215	Air Core Coil 0,640mH +/-3% 0,380Ω wire 1,00mm=18AWG OD-47 / 15mm	0,640	0,380	1,00	18	25		47	15	0,124	
000-0913	Air Core Coil 0,640mH +/-3% 0,286Ω wire 1,20mm=17AWG OD-56 / 15mm	0,640	0,286	1,20	17	25		56	15	0,178	
000-1731	Air Core Coil 0,640mH +/-3% 0,240Ω wire 1,40mm=15AWG OD-49 / 30mm	0,640	0,240	1,40	15	25		49	30	0,281	
000-1796	Air Core Coil 0,640mH +/-3% 1,680Ω wire 0,40mm=26AWG OD-25 / 8mm	0,640	1,680	0,40	26	15		25	8	0,015	
000-0142	Air Core Coil 0,650mH +/-3% 0,153Ω wire 1,80mm=13AWG OD-62 / 30mm	0,650	0,153	1,80	13	25		62	30	0,503	
000-0863	Air Core Coil 0,650mH +/-3% 0,430Ω wire 1,00mm=18AWG OD-34 / 25mm	0,650	0,430	1,00	18	8		34	25	0,133	
000-0914	Air Core Coil 0,650mH +/-3% 0,800Ω wire 0,70mm=21AWG OD-25 / 25mm	0,650	0,800	0,70	21	8		25	25	0,063	
000-1085	Air Core Coil 0,650mH +/-3% 0,430Ω wire 1,00mm=18AWG OD-39 / 30mm	0,650	0,430	1,00	18	25		39	30	0,135	
000-1416	Air Core Coil 0,650mH +/-3% 0,240Ω wire 1,40mm=15AWG OD-49 / 30mm	0,650	0,240	1,40	15	25		49	30	0,282	
000-1737	Air Core Coil 0,650mH +/-3% 1,160Ω wire 0,50mm=24AWG OD-29 / 8mm	0,650	1,160	0,50	24	15		29	8	0,025	
000-1772	Air Core Coil 0,650mH +/-3% 1,680Ω wire 0,40mm=26AWG OD-25 / 8mm	0,650	1,680	0,40	26	15		25	8	0,015	
000-1791	Air Core Coil 0,650mH +/-3% 0,320Ω wire 1,20mm=17AWG OD-43 / 30mm	0,650	0,320	1,20	17	25		43	30	0,198	
000-1929	Air Core Coil 0,650mH +/-3% 0,560Ω wire 0,80mm=20AWG OD-35 / 15mm	0,650	0,560	0,80	20	15		35	15	0,074	
000-1952	Air Core Coil 0,650mH +/-3% 0,380Ω wire 1,00mm=18AWG OD-47 / 15mm	0,650	0,380	1,00	18	25		47	15	0,124	
000-0916	Air Core Coil 0,665mH +/-5% 0,245Ω wire 1,40mm=15AWG OD-49 / 30mm	0,665	0,245	1,40	15	25		49	30	0,283	
000-0179	Air Core Coil 0,670mH +/-3% 0,55Ω wire 0,80mm=20AWG OD-35 / 15mm	0,670	0,550	0,80	20	15		35	15	0,074	
000-0982	Air Core Coil 0,670mH +/-3% 0,24Ω wire 1,40mm=15AWG OD-49 / 30mm	0,670	0,240	1,40	15	25		49	30	0,285	
000-0013	Air Core Coil 0,680mH +/-3% 0,200Ω wire 1,60mm=14AWG OD-54 / 30mm	0,680	0,200	1,60	14	25		54	30	0,393	
000-0113	Air Core Coil 0,680mH +/-3% 0,155Ω wire 1,80mm=13AWG OD-62 / 30mm	0,680	0,155	1,80	13	25		62	30	0,520	
000-1044	Air Core Coil 0,680mH +/-3% 0,700Ω wire 0,70mm=21AWG OD-32 / 15mm	0,680	0,700	0,70	21	15		32	15	0,056	
000-1282	Air Core Coil 0,680mH +/-3% 0,400Ω wire 1,00mm=18AWG OD-45 / 15mm	0,680	0,400	1,00	18	15		45	15	0,130	
000-1287	Air Core Coil 0,680mH +/-3% 0,410Ω wire 1,00mm=18AWG OD-48 / 15mm	0,680	0,410	1,00	18	25		48	15	0,125	
000-1305	Air Core Coil 0,680mH +/-3% 0,330Ω wire 1,20mm=17AWG OD-43 / 30mm	0,680	0,330	1,20	17	25		43	30	0,203	
000-1537	Air Core Coil 0,680mH +/-3% 0,440Ω wire 1,00mm=18AWG OD-39 / 30mm	0,680	0,440	1,00	18	25		39	30	0,139	
000-1542	Air Core Coil 0,680mH +/-3% 3,530Ω wire 0,30mm=29AWG OD-19 / 15mm	0,680	3,530	0,30	29	15		19	15	0,010	
000-1570	Air Core Coil 0,680mH +/-3% 0,30Ω wire 1,20mm=17AWG OD-48 / 20mm	0,680	0,300	1,20	17	20		48	20	0,197	
000-1766	Air Core Coil 0,680mH +/-3% 0,870Ω wire 0,63mm=22AWG OD-28 / 15mm	0,680	0,870	0,63	22	15		28	15	0,042	
000-1852	Air Core Coil 0,680mH +/-3% 0,560Ω wire 0,80mm=20AWG OD-35 / 15mm	0,680	0,560	0,80	20	15		35	15	0,075	
000-1853	Air Core Coil 0,680mH +/-3% 1,220Ω wire 0,50mm=24AWG OD-31 / 10mm	0,680	1,220	0,50	24	20		31	10	0,026	
000-1854	Air Core Coil 0,680mH +/-3% 0,240Ω wire 1,40mm=15AWG OD-49 / 30mm	0,680	0,240	1,40	15	25		49	30	0,288	
000-1907	Air Core Coil 0,680mH +/-3% 0,820Ω wire 0,70mm=21AWG OD-25 / 25mm	0,680	0,820	0,70	21	8		25	25	0,064	
000-1997	Air Core Coil 0,680mH +/-3% 0,440Ω wire 1,00mm=18AWG OD-34 / 25mm	0,680	0,440	1,00	18	8		34	25	0,138	
000-0221	Air Core Coil 0,690mH +/-3% 0,88Ω wire 0,63mm=22AWG OD-29 / 15mm	0,690	0,880	0,63	22	15		29	15	0,043	
000-0821	Air Core Coil 0,690mH +/-3% 0,390Ω wire 1,00mm=18AWG OD-48 / 15mm	0,690	0,390	1,00	18	25		48	15	0,128	
000-0748	Air Core Coil 0,700mH +/-3% 0,40Ω wire 1,00mm=18AWG OD-41 / 20mm	0,700	0,400	1,00	18	20		41	20	0,132	
000-0807	Air Core Coil 0,700mH +/-3% 1,31Ω wire 0,50mm=24AWG OD-21 / 15mm	0,700	1,310	0,50	24	8		21	20	0,028	
000-0808	Air Core Coil 0,700mH +/-3% 1,74Ω wire 0,50mm=24AWG OD-18 / 40mm	0,700	1,740	0,50	24	10		18	40	0,036	
000-0989	Air Core Coil 0,700mH +/-3% 1,75Ω wire 0,40mm=26AWG OD-25 / 8mm	0,700	1,750	0,40	26	15		25	8	0,015	



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno		diametro esterno		Altezza [mm]	Peso [kg]
						ø [mm]	ø [mm]	ø [mm]	ø [mm]		
000-1046	Air Core Coil 0,700mH +/-3% 1,250Ω wire 0,50mm=24AWG OD-30 / 8mm	0,700	1,250	0,50	24	15		30		8	0,025
000-1144	Air Core Coil 0,700mH +/-3% 0,400Ω wire 1,00mm=18AWG OD-48 / 15mm	0,700	0,400	1,00	18	25		48		15	0,127
000-1334	Air Core Coil 0,700mH +/-3% 0,710Ω wire 0,70mm=21AWG OD-32 / 15mm	0,700	0,710	0,70	21	15		32		15	0,057
000-1352	Air Core Coil 0,700mH +/-3% 0,900Ω wire 0,63mm=22AWG OD-29 / 15mm	0,700	0,900	0,63	22	15		29		15	0,044
000-1410	Air Core Coil 0,700mH +/-3% 0,850Ω wire 0,70mm=21AWG OD-33 / 30mm	0,700	0,850	0,70	21	25		33		30	0,066
000-1510	Air Core Coil 0,700mH +/-3% 0,340Ω wire 1,20mm=17AWG OD-45 / 30mm	0,700	0,340	1,20	17	25		45		30	0,210
000-1554	Air Core Coil 0,700mH +/-3% 3,870Ω wire 0,30mm=29AWG OD-20 / 15mm	0,700	3,870	0,30	29	15		20		15	0,010
000-1569	Air Core Coil 0,700mH +/-3% 0,30Ω wire 1,20mm=17AWG OD-48 / 20mm	0,700	0,300	1,20	17	20		48		20	0,200
000-1615	Air Core Coil 0,700mH +/-3% 0,245Ω wire 1,40mm=15AWG OD-50 / 30mm	0,700	0,245	1,40	15	25		50		30	0,292
000-1855	Air Core Coil 0,700mH +/-3% 0,570Ω wire 0,80mm=20AWG OD-35 / 15mm	0,700	0,570	0,80	20	15		35		15	0,077
000-0877	Air Core Coil 0,710mH +/-3% 0,40Ω wire 1,00mm=18AWG OD-48 / 15mm	0,710	0,400	1,00	18	25		48		15	0,128
000-0878	Air Core Coil 0,710mH +/-3% 1,750Ω wire 0,40mm=26AWG OD-25 / 8mm	0,710	1,750	0,40	26	15		25		8	0,015
000-0866	Air Core Coil 0,720mH +/-3% 0,40Ω wire 1,00mm=18AWG OD-49 / 15mm	0,720	0,400	1,00	18	25		49		15	0,130
000-0940	Air Core Coil 0,720mH +/-3% 0,25Ω wire 1,40mm=15AWG OD-50 / 30mm	0,720	0,250	1,40	15	25		50		30	0,303
000-1038	Air Core Coil 0,720mH +/-3% 3,000Ω wire 0,30mm=29AWG OD-17 / 8mm	0,720	3,000	0,30	29	9		17		8	0,008
000-1286	Air Core Coil 0,740mH +/-3% 0,420Ω wire 1,00mm=18AWG OD-48 / 15mm	0,740	0,420	1,00	18	25		48		15	0,131
000-1296	Air Core Coil 0,740mH +/-3% 0,940Ω wire 0,63mm=22AWG OD-35 / 15mm	0,740	0,940	0,63	22	25		35		15	0,048
000-0061	Air Core Coil 0,750mH +/-3% 0,205Ω wire 1,60mm=14AWG OD-58 / 30mm	0,750	0,205	1,60	14	25		58		30	0,415
000-1075	Air Core Coil 0,750mH +/-3% 0,420Ω wire 1,00mm=18AWG OD-48 / 15mm	0,750	0,420	1,00	18	25		48		15	0,131
000-1079	Air Core Coil 0,750mH +/-3% 0,470Ω wire 1,00mm=18AWG OD-40 / 30mm	0,750	0,470	1,00	18	25		40		30	0,145
000-1105	Air Core Coil 0,750mH +/-3% 1,280Ω wire 0,50mm=24AWG OD-30 / 8mm	0,750	1,250	0,50	24	15		30		8	0,026
000-1160	Air Core Coil 0,750mH +/-3% 1,810Ω wire 0,40mm=26AWG OD-25 / 8mm	0,750	1,810	0,40	26	15		25		8	0,015
000-1224	Air Core Coil 0,750mH +/-3% 0,350Ω wire 1,20mm=17AWG OD-45 / 30mm	0,750	0,350	1,20	17	25		45		30	0,215
000-1356	Air Core Coil 0,750mH +/-3% 0,740Ω wire 0,70mm=21AWG OD-32 / 15mm	0,750	0,740	0,70	21	15		32		15	0,058
000-1856	Air Core Coil 0,750mH +/-3% 0,590Ω wire 0,80mm=20AWG OD-36 / 15mm	0,750	0,590	0,80	20	15		36		15	0,081
000-1857	Air Core Coil 0,750mH +/-3% 0,260Ω wire 1,40mm=15AWG OD-51 / 30mm	0,750	0,260	1,40	15	25		51		30	0,305
000-0848	Air Core Coil 0,760mH +/-3% 0,17Ω wire 1,80mm=13AWG OD-65 / 30mm	0,760	0,170	1,80	13	25		65		30	0,547
000-1396	Air Core Coil 0,760mH +/-3% 3,88Ω wire 0,30mm=29AWG OD-20 / 15mm	0,760	3,880	0,30	29	15		20		15	0,010
000-1568	Air Core Coil 0,760mH +/-3% 0,31Ω wire 1,20mm=17AWG OD-50 / 20mm	0,760	0,310	1,20	17	20		50		20	0,211
000-1736	Air Core Coil 0,760mH +/-3% 1,830Ω wire 0,40mm=26AWG OD-25 / 8mm	0,760	1,830	0,40	26	15		25		8	0,016
000-0056	Air Core Coil 0,770mH +/-3% 0,21Ω wire 1,60mm=14AWG OD-58 / 30mm	0,770	0,210	1,60	14	25		58		30	0,420
000-0246	Air Core Coil 0,770mH +/-3% 0,425Ω wire 1,00mm=18AWG OD-50 / 15mm	0,770	0,425	1,00	18	25		50		15	0,134
000-0747	Air Core Coil 0,770mH +/-3% 0,32Ω wire 1,20mm=17AWG OD-50 / 20mm	0,770	0,320	1,20	17	20		50		20	0,212
000-0955	Air Core Coil 0,770mH +/-3% 0,264Ω wire 1,40mm=15AWG OD-51 / 30mm	0,770	0,264	1,40	15	25		51		30	0,310
000-0958	Air Core Coil 0,770mH +/-3% 0,620Ω wire 0,80mm=20AWG OD-36 / 15mm	0,770	0,620	0,80	20	15		36		15	0,082
000-0205	Air Core Coil 0,780mH +/-3% 0,533Ω wire 1,00mm=18AWG OD-30 / 40mm	0,780	0,533	1,00	18	10		30		40	0,165
000-0902	Air Core Coil 0,780mH +/-3% 0,425Ω wire 1,00mm=18AWG OD-50 / 15mm	0,780	0,425	1,00	18	25		50		15	0,134
000-0910	Air Core Coil 0,780mH +/-3% 0,750Ω wire 0,70mm=21AWG OD-33 / 15mm	0,780	0,750	0,70	21	15		33		15	0,060
000-0953	Air Core Coil 0,780mH +/-3% 0,27Ω wire 1,40mm=15AWG OD-51 / 30mm	0,780	0,267	1,40	15	25		51		30	0,315
000-1734	Air Core Coil 0,780mH +/-3% 1,86Ω wire 0,40mm=26AWG OD-25 / 8mm	0,780	1,860	0,40	26	15		25		8	0,016
000-0092	Air Core Coil 0,790mH +/-3% 0,18Ω wire 1,80mm=13AWG OD-65 / 30mm	0,790	0,180	1,80	13	25		65		30	0,559
000-1696	Air Core Coil 0,790mH +/-3% 0,750Ω wire 0,70mm=21AWG OD-33 / 15mm	0,790	0,750	0,70	21	15		33		15	0,061
000-0948	Air Core Coil 0,794mH +/-5% 1,860Ω wire 0,40mm=26AWG OD-25 / 8mm	0,794	1,860	0,40	26	15		25		8	0,016
000-0044	Air Core Coil 0,800mH +/-3% 0,209Ω wire 1,60mm=14AWG OD-58 / 30mm	0,800	0,209	1,60	14	25		58		30	0,426
000-0098	Air Core Coil 0,800mH +/-3% 0,170Ω wire 1,80mm=13AWG OD-65 / 30mm	0,800	0,170	1,80	13	25		65		30	0,564
000-0844	Air Core Coil 0,800mH +/-3% 0,87Ω wire 0,70mm=21AWG OD-25 / 25mm	0,800	0,870	0,70	21	8		25		25	0,071
000-1012	Air Core Coil 0,800mH +/-3% 0,360Ω wire 1,20mm=17AWG OD-45 / 30mm	0,800	0,360	1,20	17	25		45		30	0,225
000-1169	Air Core Coil 0,800mH +/-3% 0,750Ω wire 0,70mm=21AWG OD-33 / 15mm	0,800	0,750	0,70	21	15		33		15	0,061
000-1244	Air Core Coil 0,800mH +/-3% 0,270Ω wire 1,40mm=15AWG OD-52 / 30mm	0,800	0,270	1,40	15	25		52		30	0,319
000-1285	Air Core Coil 0,800mH +/-3% 0,430Ω wire 1,00mm=18AWG OD-50 / 15mm	0,800	0,430	1,00	18	25		50		15	0,137
000-1368	Air Core Coil 0,800mH +/-3% 0,900Ω wire 0,70mm=21AWG OD-33 / 30mm	0,800	0,900	0,70	21	25		33		30	0,068
000-1394	Air Core Coil 0,800mH +/-3% 0,620Ω wire 0,80mm=20AWG OD-36 / 15mm	0,800	0,620	0,80	20	15		36		15	0,083



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice	Descrizione		induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno		diametro esterno		Altezza [mm]	Peso [kg]
							ø [mm]	ø [mm]	ø [mm]	ø [mm]		
000-1567	Air Core Coil	0,800mH +/-3% 0,32Ω wire 1,20mm=17AWG OD-50 / 20mm	0,800	0,320	1,20	17	20		50		20	0,217
000-1691	Air Core Coil	0,800mH +/-3% 1,400Ω wire 0,50mm=24AWG OD-25 / 15mm	0,800	1,400	0,50	24	15		25		15	0,030
000-1744	Air Core Coil	0,800mH +/-3% 1,890Ω wire 0,40mm=26AWG OD-25 / 8mm	0,800	1,890	0,40	26	15		25		8	0,017
000-1992	Air Core Coil	0,800mH +/-3% 0,470Ω wire 1,00mm=18AWG OD-35 / 25mm	0,800	0,470	1,00	18	8		35		25	0,152
000-0014	Air Core Coil	0,820mH +/-3% 0,215Ω wire 1,60mm=14AWG OD-58 / 30mm	0,820	0,215	1,60	14	25		58		30	0,441
000-0114	Air Core Coil	0,820mH +/-3% 0,180Ω wire 1,80mm=13AWG OD-65 / 30mm	0,820	0,180	1,80	13	25		65		30	0,571
000-0156	Air Core Coil	0,820mH +/-3% 0,97Ω wire 0,63mm=22AWG OD-36 / 15mm	0,820	0,970	0,63	22	25		36		15	0,049
000-0203	Air Core Coil	0,820mH +/-3% 0,56Ω wire 1,00mm=18AWG OD-32 / 40mm	0,820	0,560	1,00	18	10		32		40	0,173
000-0994	Air Core Coil	0,820mH +/-3% 0,330Ω wire 1,20mm=17AWG OD-58 / 15mm	0,820	0,330	1,20	17	25		58		15	0,211
000-1288	Air Core Coil	0,820mH +/-3% 0,480Ω wire 1,00mm=18AWG OD-40 / 30mm	0,820	0,480	1,00	18	25		40		30	0,151
000-1676	Air Core Coil	0,820mH +/-3% 0,439Ω wire 1,00mm=18AWG OD-50 / 15mm	0,820	0,439	1,00	18	25		50		15	0,138
000-1787	Air Core Coil	0,820mH +/-3% 3,900Ω wire 0,30mm=29AWG OD-20 / 15mm	0,820	3,900	0,30	29	15		20		15	0,010
000-1858	Air Core Coil	0,820mH +/-3% 1,350Ω wire 0,50mm=24AWG OD-31 / 8mm	0,820	1,350	0,50	24	15		31		8	0,027
000-1859	Air Core Coil	0,820mH +/-3% 0,630Ω wire 0,80mm=20AWG OD-36 / 15mm	0,820	0,630	0,80	20	15		36		15	0,083
000-1860	Air Core Coil	0,820mH +/-3% 0,760Ω wire 0,70mm=21AWG OD-33 / 15mm	0,820	0,760	0,70	21	15		33		15	0,064
000-1882	Air Core Coil	0,820mH +/-3% 0,365Ω wire 1,20mm=17AWG OD-45 / 30mm	0,820	0,365	1,20	17	25		45		30	0,230
000-1897	Air Core Coil	0,820mH +/-3% 0,270Ω wire 1,40mm=15AWG OD-52 / 30mm	0,820	0,270	1,40	15	25		52		30	0,319
000-1973	Air Core Coil	0,820mH +/-3% 0,440Ω wire 1,00mm=18AWG OD-46 / 15mm	0,820	0,440	1,00	18	15		46		15	0,141
000-1993	Air Core Coil	0,820mH +/-3% 0,480Ω wire 1,00mm=18AWG OD-36 / 25mm	0,820	0,480	1,00	18	8		36		25	0,155
000-1565	Air Core Coil	0,830mH +/-3% 0,270Ω wire 1,40mm=15AWG OD-52 / 30mm	0,830	0,270	1,40	15	25		52		30	0,320
000-0972	Air Core Coil	0,840mH +/-3% 0,45Ω wire 1,00mm=18AWG OD-46 / 15mm	0,840	0,450	1,00	18	15		46		15	0,144
000-0015	Air Core Coil	0,850mH +/-3% 0,220Ω wire 1,60mm=14AWG OD-58 / 30mm	0,850	0,220	1,60	14	25		58		30	0,446
000-0115	Air Core Coil	0,850mH +/-3% 0,180Ω wire 1,80mm=13AWG OD-65 / 30mm	0,850	0,180	1,80	13	25		65		30	0,590
000-0930	Air Core Coil	0,850mH +/-3% 0,448Ω wire 1,00mm=18AWG OD-43 / 20mm	0,850	0,448	1,00	18	20		43		20	0,144
000-1064	Air Core Coil	0,850mH +/-3% 1,930Ω wire 0,40mm=26AWG OD-25 / 8mm	0,850	1,930	0,40	26	15		25		8	0,017
000-1128	Air Core Coil	0,850mH +/-3% 0,640Ω wire 0,80mm=20AWG OD-37 / 15mm	0,850	0,640	0,80	20	15		37		15	0,085
000-1284	Air Core Coil	0,850mH +/-3% 0,440Ω wire 1,00mm=18AWG OD-50 / 15mm	0,850	0,440	1,00	18	25		50		15	0,144
000-1430	Air Core Coil	0,850mH +/-3% 0,450Ω wire 1,00mm=18AWG OD-48 / 15mm	0,850	0,450	1,00	18	15		48		15	0,144
000-1445	Air Core Coil	0,850mH +/-3% 0,280Ω wire 1,40mm=15AWG OD-52 / 30mm	0,850	0,280	1,40	15	25		52		30	0,323
000-1784	Air Core Coil	0,850mH +/-3% 0,370Ω wire 1,20mm=17AWG OD-45 / 30mm	0,850	0,370	1,20	17	25		45		30	0,233
000-1861	Air Core Coil	0,850mH +/-3% 0,500Ω wire 1,00mm=18AWG OD-40 / 30mm	0,850	0,500	1,00	18	25		40		30	0,153
000-1669	Air Core Coil	0,860mH +/-3% 0,800Ω wire 0,70mm=21AWG OD-33 / 15mm	0,860	0,800	0,70	21	15		33		15	0,063
000-0170	Air Core Coil	0,870mH +/-3% 0,22Ω wire 1,60mm=14AWG OD-59 / 30mm	0,870	0,220	1,60	14	25		59		30	0,450
000-1158	Air Core Coil	0,870mH +/-3% 1,950Ω wire 0,40mm=26AWG OD-26 / 8mm	0,870	1,950	0,40	26	15		26		8	0,017
000-1295	Air Core Coil	0,870mH +/-3% 1,010Ω wire 0,63mm=22AWG OD-36 / 15mm	0,870	1,010	0,63	22	25		36		15	0,051
000-1438	Air Core Coil	0,870mH +/-3% 3,460Ω wire 0,30mm=29AWG OD-18 / 8mm	0,870	3,460	0,30	29	9		18		8	0,009
000-1443	Air Core Coil	0,870mH +/-3% 0,800Ω wire 0,70mm=21AWG OD-33 / 15mm	0,870	0,800	0,70	21	15		33		15	0,064
000-1918	Air Core Coil	0,870mH +/-3% 0,380Ω wire 1,20mm=17AWG OD-45 / 30mm	0,870	0,380	1,20	17	25		45		30	0,236
000-0818	Air Core Coil	0,875mH +/-5% 0,460Ω wire 1,00mm=18AWG OD-48 / 15mm	0,875	0,460	1,00	18	15		48		15	0,146
000-0252	Air Core Coil	0,880mH +/-3% 0,290Ω wire 1,40mm=15AWG OD-54 / 30mm	0,880	0,290	1,40	15	25		54		30	0,337
000-0712	Air Core Coil	0,880mH +/-3% 1,45Ω wire 0,50mm=24AWG OD-26 / 15mm	0,880	1,450	0,50	24	15		26		15	0,030
000-0845	Air Core Coil	0,880mH +/-3% 0,38Ω wire 1,20mm=17AWG OD-45 / 30mm	0,880	0,380	1,20	17	25		45		30	0,238
000-1429	Air Core Coil	0,880mH +/-3% 0,470Ω wire 1,00mm=18AWG OD-48 / 15mm	0,880	0,470	1,00	18	15		48		15	0,146
000-1437	Air Core Coil	0,880mH +/-3% 0,940Ω wire 0,70mm=21AWG OD-34 / 30mm	0,880	0,940	0,70	21	25		34		30	0,075
000-1052	Air Core Coil	0,890mH +/-3% 0,670Ω wire 0,80mm=20AWG OD-38 / 15mm	0,890	0,670	0,80	20	15		38		15	0,088
000-1408	Air Core Coil	0,890mH +/-3% 0,800Ω wire 0,70mm=21AWG OD-33 / 15mm	0,890	0,800	0,70	21	15		33		15	0,064
000-0016	Air Core Coil	0,900mH +/-3% 0,228Ω wire 1,60mm=14AWG OD-58 / 30mm	0,900	0,228	1,60	14	25		58		30	0,462
000-0116	Air Core Coil	0,900mH +/-3% 0,185Ω wire 1,80mm=13AWG OD-65 / 30mm	0,900	0,185	1,80	13	25		65		30	0,620
000-0239	Air Core Coil	0,900mH +/-3% 2,23Ω wire 0,40mm=26AWG OD-25 / 10mm	0,900	2,230	0,40	26	18		25		10	0,017
000-0824	Air Core Coil	0,900mH +/-3% 1,49Ω wire 0,50mm=24AWG OD-26 / 15mm	0,900	1,490	0,50	24	15		26		15	0,031
000-0825	Air Core Coil	0,900mH +/-3% 3,94Ω wire 0,30mm=29AWG OD-19 / 15mm	0,900	3,940	0,30	29	15		19		15	0,011
000-1001	Air Core Coil	0,900mH +/-3% 0,950Ω wire 0,70mm=21AWG OD-35 / 30mm	0,900	0,950	0,70	21	25		35		30	0,076



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1413	Air Core Coil	0,900mH +/-3% 0,390Ω wire 1,20mm=17AWG OD-45 / 30mm	0,900	0,390	1,20	17	25	45	30	0,240
000-1448	Air Core Coil	0,900mH +/-3% 0,810Ω wire 0,70mm=21AWG OD-34 / 15mm	0,900	0,810	0,70	21	15	34	15	0,065
000-1526	Air Core Coil	0,900mH +/-3% 0,670Ω wire 0,80mm=20AWG OD-38 / 15mm	0,900	0,670	0,80	20	15	38	15	0,090
000-1566	Air Core Coil	0,900mH +/-3% 0,35Ω wire 1,20mm=17AWG OD-52 / 20mm	0,900	0,350	1,20	17	20	52	20	0,234
000-1647	Air Core Coil	0,900mH +/-3% 0,530Ω wire 1,00mm=18AWG OD-42 / 30mm	0,900	0,530	1,00	18	25	42	30	0,159
000-1657	Air Core Coil	0,900mH +/-3% 0,290Ω wire 1,40mm=15AWG OD-54 / 30mm	0,900	0,290	1,40	15	25	54	30	0,337
000-1878	Air Core Coil	0,900mH +/-3% 2,090Ω wire 0,40mm=26AWG OD-26 / 8mm	0,900	2,090	0,40	26	15	26	8	0,018
000-1953	Air Core Coil	0,900mH +/-3% 0,460Ω wire 1,00mm=18AWG OD-52 / 15mm	0,900	0,460	1,00	18	25	52	15	0,147
000-1969	Air Core Coil	0,900mH +/-3% 0,470Ω wire 1,00mm=18AWG OD-48 / 15mm	0,900	0,470	1,00	18	15	48	15	0,148
000-1862	Air Core Coil	0,910mH +/-3% 0,290Ω wire 1,40mm=15AWG OD-54 / 30mm	0,910	0,290	1,40	15	25	54	30	0,339
000-0837	Air Core Coil	0,920mH +/-3% 0,68Ω wire 0,80mm=20AWG OD-38 / 15mm	0,920	0,680	0,80	20	15	38	15	0,090
000-0846	Air Core Coil	0,920mH +/-3% 0,39Ω wire 1,20mm=17AWG OD-48 / 30mm	0,920	0,390	1,20	17	25	48	30	0,242
000-1081	Air Core Coil	0,930mH +/-3% 0,300Ω wire 1,40mm=15AWG OD-54 / 30mm	0,930	0,300	1,40	15	25	54	30	0,344
000-1369	Air Core Coil	0,930mH +/-3% 0,970Ω wire 0,70mm=21AWG OD-35 / 30mm	0,930	0,970	0,70	21	25	35	30	0,077
000-1235	Air Core Coil	0,940mH +/-3% 0,500Ω wire 1,00mm=18AWG OD-57 / 21mm	0,940	0,500	1,00	18	42	57	21	0,157
000-0017	Air Core Coil	0,950mH +/-3% 0,236Ω wire 1,60mm=14AWG OD-61 / 30mm	0,950	0,236	1,60	14	25	61	30	0,478
000-0117	Air Core Coil	0,950mH +/-3% 0,190Ω wire 1,80mm=13AWG OD-69 / 30mm	0,950	0,190	1,80	13	25	69	30	0,640
000-0944	Air Core Coil	0,950mH +/-3% 0,390Ω wire 1,20mm=17AWG OD-48 / 30mm	0,950	0,390	1,20	17	25	48	30	0,246
000-0962	Air Core Coil	0,950mH +/-3% 1,030Ω wire 0,63mm=22AWG OD-30 / 15mm	0,950	1,030	0,63	22	15	30	15	0,052
000-1077	Air Core Coil	0,950mH +/-3% 0,300Ω wire 1,40mm=15AWG OD-54 / 30mm	0,950	0,300	1,40	15	25	54	30	0,347
000-1134	Air Core Coil	0,950mH +/-3% 0,680Ω wire 0,80mm=20AWG OD-38 / 15mm	0,950	0,680	0,80	20	15	38	15	0,092
000-1399	Air Core Coil	0,950mH +/-3% 0,830Ω wire 0,70mm=21AWG OD-34 / 15mm	0,950	0,830	0,70	21	15	34	15	0,067
000-1954	Air Core Coil	0,950mH +/-3% 0,480Ω wire 1,00mm=18AWG OD-52 / 15mm	0,950	0,480	1,00	18	25	52	15	0,155
000-1970	Air Core Coil	0,950mH +/-3% 0,480Ω wire 1,00mm=18AWG OD-48 / 15mm	0,950	0,480	1,00	18	15	48	15	0,153
000-1337	Air Core Coil	0,960mH +/-3% 0,370Ω wire 1,20mm=17AWG OD-60 / 15mm	0,960	0,370	1,20	17	25	60	15	0,235
000-1374	Air Core Coil	0,960mH +/-3% 0,540Ω wire 1,00mm=18AWG OD-42 / 30mm	0,960	0,540	1,00	18	25	42	30	0,166
000-1436	Air Core Coil	0,960mH +/-3% 0,990Ω wire 0,70mm=21AWG OD-35 / 30mm	0,960	0,990	0,70	21	25	35	30	0,078
000-0018	Air Core Coil	1,000mH +/-3% 0,245Ω wire 1,60mm=14AWG OD-61 / 30mm	1,000	0,245	1,60	14	25	61	30	0,504
000-0118	Air Core Coil	1,000mH +/-3% 0,198Ω wire 1,80mm=13AWG OD-69 / 30mm	1,000	0,198	1,80	13	25	69	30	0,658
000-0749	Air Core Coil	1,000mH +/-3% 0,50Ω wire 1,00mm=18AWG OD-45 / 20mm	1,000	0,550	1,00	18	20	45	20	0,163
000-0826	Air Core Coil	1,000mH +/-3% 3,98Ω wire 0,30mm=29AWG OD-19 / 15mm	1,000	3,980	0,30	29	15	19	15	0,011
000-1056	Air Core Coil	1,000mH +/-3% 0,710Ω wire 0,80mm=20AWG OD-38 / 15mm	1,000	0,710	0,80	20	15	38	15	0,096
000-1057	Air Core Coil	1,000mH +/-3% 0,550Ω wire 1,00mm=18AWG OD-42 / 30mm	1,000	0,550	1,00	18	25	42	30	0,172
000-1089	Air Core Coil	1,000mH +/-3% 1,570Ω wire 0,50mm=24AWG OD-26 / 15mm	1,000	1,570	0,50	24	15	26	15	0,034
000-1094	Air Core Coil	1,000mH +/-3% 0,395Ω wire 1,20mm=17AWG OD-48 / 30mm	1,000	0,395	1,20	17	25	48	30	0,256
000-1096	Air Core Coil	1,000mH +/-3% 0,285Ω wire 1,40mm=15AWG OD-71 / 21mm	1,000	0,285	1,40	15	42	71	21	0,348
000-1231	Air Core Coil	1,000mH +/-3% 0,720Ω wire 0,80mm=20AWG OD-43 / 15mm	1,000	0,720	0,80	20	25	43	15	0,092
000-1239	Air Core Coil	1,000mH +/-3% 0,480Ω wire 1,00mm=18AWG OD-52 / 15mm	1,000	0,480	1,00	18	25	52	15	0,158
000-1370	Air Core Coil	1,000mH +/-3% 1,000Ω wire 0,70mm=21AWG OD-35 / 30mm	1,000	1,000	0,70	21	25	35	30	0,080
000-1395	Air Core Coil	1,000mH +/-3% 2,240Ω wire 0,40mm=26AWG OD-29 / 10mm	1,000	2,240	0,40	26	20	29	10	0,019
000-1409	Air Core Coil	1,000mH +/-3% 0,850Ω wire 0,70mm=21AWG OD-34 / 15mm	1,000	0,850	0,70	21	15	34	15	0,069
000-1440	Air Core Coil	1,000mH +/-3% 1,100Ω wire 0,63mm=22AWG OD-30 / 15mm	1,000	1,100	0,63	22	15	30	15	0,055
000-1563	Air Core Coil	1,000mH +/-3% 0,36Ω wire 1,20mm=17AWG OD-52 / 20mm	1,000	0,360	1,20	17	20	52	20	0,248
000-1786	Air Core Coil	1,000mH +/-3% 4,40Ω wire 0,30mm=29AWG OD-14 / 20mm	1,000	4,400	0,30	29	10	14	20	0,012
000-1898	Air Core Coil	1,000mH +/-3% 0,300Ω wire 1,40mm=15AWG OD-54 / 30mm	1,000	0,300	1,40	15	25	54	30	0,365
000-1972	Air Core Coil	1,000mH +/-3% 0,490Ω wire 1,00mm=18AWG OD-49 / 15mm	1,000	0,490	1,00	18	15	49	15	0,157
000-1994	Air Core Coil	1,000mH +/-3% 0,540Ω wire 1,00mm=18AWG OD-36 / 25mm	1,000	0,540	1,00	18	8	36	25	0,172
000-1047	Air Core Coil	1,040mH +/-3% 0,290Ω wire 1,40mm=15AWG OD-71 / 21mm	1,040	0,290	1,40	15	42	71	21	0,355
000-1135	Air Core Coil	1,050mH +/-3% 0,730Ω wire 0,80mm=20AWG OD-39 / 15mm	1,050	0,730	0,80	20	15	39	15	0,097
000-1782	Air Core Coil	1,050mH +/-3% 0,397Ω wire 1,20mm=17AWG OD-49 / 30mm	1,050	0,397	1,20	17	25	49	30	0,263
000-0058	Air Core Coil	1,060mH +/-3% 0,25Ω wire 1,60mm=14AWG OD-63 / 30mm	1,060	0,250	1,60	14	25	63	30	0,520
000-1701	Air Core Coil	1,060mH +/-3% 4,380Ω wire 0,30mm=29AWG OD-20 / 15mm	1,060	4,380	0,30	29	15	20	15	0,011

COSTRUIRE
AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1776	Air Core Coil	1,060mH +/-3% 1,690Ω wire 0,50mm=24AWG OD-26 / 15mm	1,060	1,690	0,50	24	15	26	15	0,035
000-0055	Air Core Coil	1,070mH +/-3% 0,251Ω wire 1,60mm=14AWG OD-63 / 30mm	1,070	0,251	1,60	14	25	63	30	0,520
000-0019	Air Core Coil	1,100mH +/-3% 0,258Ω wire 1,60mm=14AWG OD-63 / 30mm	1,100	0,258	1,60	14	25	63	30	0,523
000-0119	Air Core Coil	1,100mH +/-3% 0,208Ω wire 1,80mm=13AWG OD-69 / 30mm	1,100	0,208	1,80	13	25	69	30	0,680
000-0243	Air Core Coil	1,100mH +/-3% 0,31Ω wire 1,40mm=15AWG OD-57 / 30mm	1,100	0,310	1,40	15	25	57	30	0,394
000-0827	Air Core Coil	1,100mH +/-3% 4,39Ω wire 0,30mm=29AWG OD-20 / 15mm	1,100	4,390	0,30	29	15	20	15	0,011
000-1078	Air Core Coil	1,100mH +/-3% 0,570Ω wire 1,00mm=18AWG OD-43 / 30mm	1,100	0,570	1,00	18	25	43	30	0,176
000-1477	Air Core Coil	1,100mH +/-3% 0,920Ω wire 0,70mm=21AWG OD-35 / 15mm	1,100	0,920	0,70	21	15	35	15	0,072
000-1478	Air Core Coil	1,100mH +/-3% 0,760Ω wire 0,80mm=20AWG OD-39 / 15mm	1,100	0,760	0,80	20	15	39	15	0,097
000-1562	Air Core Coil	1,100mH +/-3% 0,39Ω wire 1,20mm=17AWG OD-55 / 20mm	1,100	0,390	1,20	17	20	55	20	0,264
000-1795	Air Core Coil	1,100mH +/-3% 1,55Ω wire 0,50mm=24AWG OD-30 / 8mm	1,100	1,550	0,50	24	9	30	8	0,033
000-1886	Air Core Coil	1,100mH +/-3% 1,700Ω wire 0,50mm=24AWG OD-26 / 15mm	1,100	1,700	0,50	24	15	26	15	0,035
000-1887	Air Core Coil	1,100mH +/-3% 1,150Ω wire 0,63mm=22AWG OD-30 / 15mm	1,100	1,150	0,63	22	15	30	15	0,056
000-1924	Air Core Coil	1,100mH +/-3% 0,420Ω wire 1,20mm=17AWG OD-49 / 30mm	1,100	0,420	1,20	17	25	49	30	0,268
000-1931	Air Core Coil	1,100mH +/-3% 0,310Ω wire 1,40mm=15AWG OD-72 / 21mm	1,100	0,310	1,40	15	42	72	21	0,360
000-1014	Air Core Coil	1,130mH +/-3% 4,400Ω wire 0,30mm=29AWG OD-20 / 15mm	1,130	4,400	0,30	29	15	20	15	0,011
000-1983	Air Core Coil	1,130mH +/-3% 0,430Ω wire 1,20mm=17AWG OD-50 / 30mm	1,130	0,430	1,20	17	25	50	30	0,272
000-1984	Air Core Coil	1,130mH +/-3% 0,320Ω wire 1,40mm=15AWG OD-56 / 30mm	1,130	0,320	1,40	15	25	56	30	0,380
000-1067	Air Core Coil	1,150mH +/-3% 2,390Ω wire 0,40mm=26AWG OD-29 / 10mm	1,150	2,390	0,40	26	20	29	10	0,021
000-1136	Air Core Coil	1,150mH +/-3% 0,760Ω wire 0,80mm=20AWG OD-40 / 15mm	1,150	0,760	0,80	20	15	40	15	0,102
000-1174	Air Core Coil	1,150mH +/-3% 0,445Ω wire 1,20mm=17AWG OD-50 / 30mm	1,150	0,445	1,20	17	25	50	30	0,276
000-1256	Air Core Coil	1,150mH +/-3% 0,322Ω wire 1,40mm=15AWG OD-56 / 30mm	1,150	0,322	1,40	15	25	56	30	0,385
000-1625	Air Core Coil	1,150mH +/-3% 0,590Ω wire 1,00mm=18AWG OD-43 / 30mm	1,150	0,590	1,00	18	25	43	30	0,183
000-1797	Air Core Coil	1,150mH +/-3% 0,32Ω wire 1,40mm=15AWG OD-60 / 25mm	1,150	0,320	1,40	15	25	60	25	0,389
000-0237	Air Core Coil	1,170mH +/-3% 1,70Ω wire 0,50mm=24AWG OD-30 / 8mm	1,170	1,700	0,50	24	9	30	8	0,035
000-0020	Air Core Coil	1,200mH +/-3% 0,270Ω wire 1,60mm=14AWG OD-63 / 30mm	1,200	0,270	1,60	14	25	63	30	0,552
000-0120	Air Core Coil	1,200mH +/-3% 0,220Ω wire 1,80mm=13AWG OD-71 / 30mm	1,200	0,220	1,80	13	25	71	30	0,720
000-0242	Air Core Coil	1,200mH +/-3% 2,67Ω wire 0,40mm=26AWG OD-23 / 15mm	1,200	2,670	0,40	26	15	23	15	0,023
000-0853	Air Core Coil	1,200mH +/-3% 1,18Ω wire 0,63mm=22AWG OD-32 / 15mm	1,200	1,180	0,63	22	15	32	15	0,058
000-0896	Air Core Coil	1,200mH +/-3% 0,340Ω wire 1,40mm=15AWG OD-51 / 33mm	1,200	0,340	1,40	15	17	51	33	0,424
000-0984	Air Core Coil	1,200mH +/-3% 0,28Ω wire 1,60mm=14AWG OD-66 / 25mm	1,200	0,280	1,60	14	8	66	25	0,568
000-1133	Air Core Coil	1,200mH +/-3% 1,760Ω wire 0,50mm=24AWG OD-27 / 15mm	1,200	1,760	0,50	24	15	27	15	0,037
000-1280	Air Core Coil	1,200mH +/-3% 0,555Ω wire 1,00mm=18AWG OD-53 / 15mm	1,200	0,555	1,00	18	25	53	15	0,176
000-1301	Air Core Coil	1,200mH +/-3% 0,460Ω wire 1,20mm=17AWG OD-50 / 30mm	1,200	0,460	1,20	17	25	50	30	0,283
000-1336	Air Core Coil	1,200mH +/-3% 0,330Ω wire 1,40mm=15AWG OD-73 / 21mm	1,200	0,330	1,40	15	42	73	21	0,386
000-1467	Air Core Coil	1,200mH +/-3% 0,550Ω wire 1,00mm=18AWG OD-48 / 20mm	1,200	0,550	1,00	18	20	48	20	0,173
000-1527	Air Core Coil	1,200mH +/-3% 0,41Ω wire 1,20mm=17AWG OD-57 / 20mm	1,200	0,410	1,20	17	20	57	20	0,278
000-1767	Air Core Coil	1,200mH +/-3% 4,660Ω wire 0,30mm=29AWG OD-20 / 15mm	1,200	4,660	0,30	29	15	20	15	0,013
000-1863	Air Core Coil	1,200mH +/-3% 0,950Ω wire 0,70mm=21AWG OD-36 / 15mm	1,200	0,950	0,70	21	15	36	15	0,077
000-1864	Air Core Coil	1,200mH +/-3% 0,800Ω wire 0,80mm=20AWG OD-41 / 15mm	1,200	0,800	0,80	20	15	41	15	0,106
000-1899	Air Core Coil	1,200mH +/-3% 0,330Ω wire 1,40mm=15AWG OD-57 / 30mm	1,200	0,330	1,40	15	25	57	30	0,396
000-1901	Air Core Coil	1,200mH +/-3% 0,600Ω wire 1,00mm=18AWG OD-44 / 30mm	1,200	0,600	1,00	18	25	44	30	0,184
000-1995	Air Core Coil	1,200mH +/-3% 0,590Ω wire 1,00mm=18AWG OD-36 / 25mm	1,200	0,590	1,00	18	8	36	25	0,196
000-0149	Air Core Coil	1,250mH +/-3% 0,42Ω wire 1,20mm=17AWG OD-51 / 30mm	1,250	0,420	1,20	17	25	51	30	0,290
000-0795	Air Core Coil	1,250mH +/-3% 0,34Ω wire 1,40mm=15AWG OD-54 / 33mm	1,250	0,340	1,40	15	17	54	33	0,428
000-0974	Air Core Coil	1,250mH +/-3% 1,21Ω wire 0,63mm=22AWG OD-32 / 15mm	1,250	1,210	0,63	22	15	32	15	0,062
000-1137	Air Core Coil	1,250mH +/-3% 0,800Ω wire 0,80mm=20AWG OD-41 / 15mm	1,250	0,800	0,80	20	15	41	15	0,106
000-1626	Air Core Coil	1,250mH +/-3% 0,610Ω wire 1,00mm=18AWG OD-44 / 30mm	1,250	0,610	1,00	18	25	44	30	0,190
000-1656	Air Core Coil	1,250mH +/-3% 0,340Ω wire 1,40mm=15AWG OD-59 / 30mm	1,250	0,340	1,40	15	25	59	30	0,407
000-0802	Air Core Coil	1,260mH +/-3% 4,90Ω wire 0,30mm=29AWG OD-20 / 15mm	1,260	4,900	0,30	29	15	20	15	0,013
000-1799	Air Core Coil	1,260mH +/-3% 1,00Ω wire 0,70mm=21AWG OD-36 / 15mm	1,260	1,010	0,70	21	15	36	15	0,079
000-1108	Air Core Coil	1,280mH +/-3% 2,670Ω wire 0,40mm=26AWG OD-23 / 15mm	1,280	2,670	0,40	26	15	23	15	0,023



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno diametro esterno		Altezza [mm]	Peso [kg]
						ø [mm]	ø [mm]		
000-1376	Air Core Coil 1,280mH +/-3% 0,470Ω wire 1,20mm=17AWG OD-50 / 30mm	1,280	0,470	1,20	17	25	50	30	0,300
000-0021	Air Core Coil 1,300mH +/-3% 0,283Ω wire 1,60mm=14AWG OD-63 / 30mm	1,300	0,283	1,60	14	25	63	30	0,575
000-0121	Air Core Coil 1,300mH +/-3% 0,230Ω wire 1,80mm=13AWG OD-71 / 30mm	1,300	0,230	1,80	13	25	71	30	0,766
000-0886	Air Core Coil 1,300mH +/-3% 0,340Ω wire 1,40mm=15AWG OD-65 / 20mm	1,300	0,340	1,40	15	25	65	20	0,405
000-1048	Air Core Coil 1,300mH +/-3% 0,610Ω wire 1,00mm=18AWG OD-44 / 30mm	1,300	0,610	1,00	18	25	44	30	0,197
000-1058	Air Core Coil 1,300mH +/-3% 1,780Ω wire 0,50mm=24AWG OD-34 / 8mm	1,300	1,780	0,50	24	15	34	8	0,037
000-1083	Air Core Coil 1,300mH +/-3% 0,458Ω wire 1,20mm=17AWG OD-56 / 20mm	1,300	0,458	1,20	17	25	56	20	0,282
000-1138	Air Core Coil 1,300mH +/-3% 0,820Ω wire 0,80mm=20AWG OD-42 / 15mm	1,300	0,820	0,80	20	15	42	15	0,111
000-1293	Air Core Coil 1,300mH +/-3% 1,010Ω wire 0,70mm=21AWG OD-36 / 15mm	1,300	1,010	0,70	21	15	36	15	0,081
000-1371	Air Core Coil 1,300mH +/-3% 1,170Ω wire 0,70mm=21AWG OD-36 / 30mm	1,300	1,170	0,70	21	25	36	30	0,091
000-1434	Air Core Coil 1,300mH +/-3% 0,43Ω wire 1,20mm=17AWG OD-57 / 20mm	1,300	0,430	1,20	17	20	57	20	0,290
000-1540	Air Core Coil 1,300mH +/-3% 0,356Ω wire 1,40mm=15AWG OD-59 / 30mm	1,300	0,356	1,40	15	25	59	30	0,417
000-1710	Air Core Coil 1,300mH +/-3% 4,92Ω wire 0,30mm=29AWG OD-20 / 15mm	1,300	4,920	0,30	29	15	20	15	0,013
000-1945	Air Core Coil 1,300mH +/-3% 0,470Ω wire 1,20mm=17AWG OD-50 / 30mm	1,300	0,470	1,20	17	25	50	30	0,300
000-1658	Air Core Coil 1,330mH +/-3% 0,358Ω wire 1,40mm=15AWG OD-59 / 30mm	1,330	0,358	1,40	15	25	59	30	0,425
000-1660	Air Core Coil 1,330mH +/-3% 0,335Ω wire 1,40mm=15AWG OD-67 / 20mm	1,330	0,335	1,40	15	25	67	20	0,405
000-1029	Air Core Coil 1,340mH +/-3% 5,100Ω wire 0,30mm=29AWG OD-20 / 15mm	1,340	5,100	0,30	29	15	20	15	0,013
000-1455	Air Core Coil 1,340mH +/-3% 1,900Ω wire 0,50mm=24AWG OD-27 / 15mm	1,340	1,900	0,50	24	15	27	15	0,039
000-0838	Air Core Coil 1,350mH +/-3% 1,92Ω wire 0,50mm=24AWG OD-34 / 15mm	1,350	1,920	0,50	24	25	34	15	0,040
000-1142	Air Core Coil 1,350mH +/-3% 0,350Ω wire 1,40mm=15AWG OD-75 / 21mm	1,350	0,350	1,40	15	42	75	21	0,405
000-1150	Air Core Coil 1,350mH +/-3% 0,850Ω wire 0,80mm=20AWG OD-42 / 15mm	1,350	0,850	0,80	20	15	42	15	0,111
000-1375	Air Core Coil 1,350mH +/-3% 0,630Ω wire 1,00mm=18AWG OD-44 / 30mm	1,350	0,630	1,00	18	25	44	30	0,202
000-1457	Air Core Coil 1,350mH +/-3% 0,490Ω wire 1,20mm=17AWG OD-50 / 30mm	1,350	0,490	1,20	17	25	50	30	0,307
000-0022	Air Core Coil 1,400mH +/-3% 0,294Ω wire 1,60mm=14AWG OD-66 / 30mm	1,400	0,294	1,60	14	25	66	30	0,608
000-0122	Air Core Coil 1,400mH +/-3% 0,238Ω wire 1,80mm=13AWG OD-75 / 30mm	1,400	0,238	1,80	13	25	75	30	0,793
000-0743	Air Core Coil 1,400mH +/-3% 0,59Ω wire 1,00mm=18AWG OD-49 / 20mm	1,400	0,590	1,00	18	20	49	20	0,199
000-1006	Air Core Coil 1,400mH +/-3% 0,500Ω wire 1,20mm=17AWG OD-50 / 30mm	1,400	0,500	1,20	17	25	50	30	0,309
000-1183	Air Core Coil 1,400mH +/-3% 0,44Ω wire 1,20mm=17AWG OD-59 / 20mm	1,400	0,440	1,20	17	20	59	20	0,305
000-1330	Air Core Coil 1,400mH +/-3% 1,100Ω wire 0,70mm=21AWG OD-37 / 15mm	1,400	1,100	0,70	21	15	37	15	0,084
000-1461	Air Core Coil 1,400mH +/-3% 1,310Ω wire 0,63mm=22AWG OD-33 / 15mm	1,400	1,310	0,63	22	15	33	15	0,065
000-1470	Air Core Coil 1,400mH +/-3% 0,370Ω wire 1,40mm=15AWG OD-59 / 30mm	1,400	0,370	1,40	15	25	59	30	0,437
000-1524	Air Core Coil 1,400mH +/-3% 0,860Ω wire 0,80mm=20AWG OD-42 / 15mm	1,400	0,860	0,80	20	15	42	15	0,112
000-1702	Air Core Coil 1,400mH +/-3% 5,200Ω wire 0,30mm=29AWG OD-20 / 15mm	1,400	5,200	0,30	29	15	20	15	0,013
000-1775	Air Core Coil 1,400mH +/-3% 1,920Ω wire 0,50mm=24AWG OD-27 / 15mm	1,400	1,920	0,50	24	15	27	15	0,040
000-1955	Air Core Coil 1,400mH +/-3% 0,650Ω wire 1,00mm=18AWG OD-44 / 30mm	1,400	0,650	1,00	18	25	44	30	0,207
000-0169	Air Core Coil 1,420mH +/-3% 0,30Ω wire 1,60mm=14AWG OD-67 / 30mm	1,420	0,300	1,60	14	25	67	30	0,610
000-1441	Air Core Coil 1,430mH +/-3% 1,080Ω wire 0,70mm=21AWG OD-38 / 15mm	1,430	1,080	0,70	21	15	38	15	0,086
000-1140	Air Core Coil 1,450mH +/-3% 0,470Ω wire 1,20mm=17AWG OD-66 / 21mm	1,450	0,470	1,20	17	42	66	21	0,300
000-1151	Air Core Coil 1,450mH +/-3% 0,870Ω wire 0,80mm=20AWG OD-42 / 15mm	1,450	0,870	0,80	20	15	42	15	0,116
000-1249	Air Core Coil 1,450mH +/-3% 0,510Ω wire 1,20mm=17AWG OD-51 / 30mm	1,450	0,510	1,20	17	25	51	30	0,313
000-1341	Air Core Coil 1,450mH +/-3% 0,370Ω wire 1,40mm=15AWG OD-75 / 21mm	1,450	0,370	1,40	15	42	75	21	0,416
000-1649	Air Core Coil 1,450mH +/-3% 0,670Ω wire 1,00mm=18AWG OD-44 / 30mm	1,450	0,650	1,00	18	25	44	30	0,210
000-0023	Air Core Coil 1,500mH +/-3% 0,305Ω wire 1,60mm=14AWG OD-66 / 30mm	1,500	0,305	1,60	14	25	66	30	0,628
000-0123	Air Core Coil 1,500mH +/-3% 0,245Ω wire 1,80mm=13AWG OD-75 / 30mm	1,500	0,245	1,80	13	25	75	30	0,810
000-0794	Air Core Coil 1,500mH +/-3% 0,34Ω wire 1,40mm=15AWG OD-54 / 33mm	1,500	0,340	1,40	15	17	54	33	0,480
000-1060	Air Core Coil 1,500mH +/-3% 1,000Ω wire 0,80mm=20AWG OD-39 / 30mm	1,500	1,000	0,80	20	25	39	30	0,130
000-1087	Air Core Coil 1,500mH +/-3% 0,670Ω wire 1,00mm=18AWG OD-45 / 30mm	1,500	0,670	1,00	18	25	45	30	0,212
000-1095	Air Core Coil 1,500mH +/-3% 0,370Ω wire 1,40mm=15AWG OD-75 / 21mm	1,500	0,370	1,40	15	42	75	21	0,438
000-1103	Air Core Coil 1,500mH +/-3% 0,900Ω wire 0,80mm=20AWG OD-43 / 15mm	1,500	0,900	0,80	20	15	43	15	0,119
000-1182	Air Core Coil 1,500mH +/-3% 0,47Ω wire 1,20mm=17AWG OD-59 / 20mm	1,500	0,470	1,20	17	20	59	20	0,318
000-1212	Air Core Coil 1,500mH +/-3% 5,280Ω wire 0,30mm=29AWG OD-21 / 15mm	1,500	5,280	0,30	29	15	21	15	0,014
000-1283	Air Core Coil 1,500mH +/-3% 0,640Ω wire 1,00mm=18AWG OD-57 / 15mm	1,500	0,640	1,00	18	25	57	15	0,199



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

		diametro interno diametro esterno									
codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	ø [mm]	ø [mm]	Altezza [mm]	Peso [kg]		
000-1300	Air Core Coil 1,500mH +/-3% 0,520Ω wire 1,20mm=17AWG OD-52 / 30mm	1,500	0,520	1,20	17	25	52	30	0,320		
000-1469	Air Core Coil 1,500mH +/-3% 0,380Ω wire 1,40mm=15AWG OD-59 / 30mm	1,500	0,380	1,40	15	25	59	30	0,451		
000-1865	Air Core Coil 1,500mH +/-3% 1,100Ω wire 0,70mm=21AWG OD-38 / 15mm	1,500	1,100	0,70	21	15	38	15	0,088		
000-1866	Air Core Coil 1,500mH +/-3% 1,980Ω wire 0,50mm=24AWG OD-28 / 15mm	1,500	1,980	0,50	24	15	28	15	0,041		
000-1867	Air Core Coil 1,500mH +/-3% 2,830Ω wire 0,40mm=26AWG OD-28 / 8mm	1,500	2,830	0,40	26	15	28	8	0,023		
000-1888	Air Core Coil 1,500mH +/-3% 1,350Ω wire 0,63mm=22AWG OD-33 / 15mm	1,500	1,350	0,63	22	15	33	15	0,069		
000-1999	Air Core Coil 1,500mH +/-3% 0,650Ω wire 1,00mm=18AWG OD-40 / 25mm	1,500	0,650	1,00	18	8	40	25	0,216		
000-0942	Air Core Coil 1,520mH +/-3% 0,390Ω wire 1,40mm=15AWG OD-59 / 30mm	1,520	0,390	1,40	15	25	59	30	0,458		
000-1670	Air Core Coil 1,520mH +/-3% 1,100Ω wire 0,70mm=21AWG OD-38 / 15mm	1,520	1,100	0,70	21	15	38	15	0,089		
000-1739	Air Core Coil 1,540mH +/-3% 2,850Ω wire 0,40mm=26AWG OD-29 / 8mm	1,540	2,850	0,40	26	15	29	8	0,024		
000-0976	Air Core Coil 1,570mH +/-3% 0,70Ω wire 1,00mm=18AWG OD-40 / 32mm	1,570	0,700	1,00	18	17	40	33	0,228		
000-0024	Air Core Coil 1,600mH +/-3% 0,320Ω wire 1,60mm=14AWG OD-66 / 30mm	1,600	0,320	1,60	14	25	66	30	0,650		
000-0124	Air Core Coil 1,600mH +/-3% 0,255Ω wire 1,80mm=13AWG OD-75 / 30mm	1,600	0,255	1,80	13	25	75	30	0,840		
000-0146	Air Core Coil 1,600mH +/-3% 1,39Ω wire 0,63mm=22AWG OD-34 / 15mm	1,600	1,390	0,63	22	15	34	15	0,070		
000-1156	Air Core Coil 1,600mH +/-3% 0,400Ω wire 1,40mm=15AWG OD-59 / 30mm	1,600	0,400	1,40	15	25	59	30	0,468		
000-1180	Air Core Coil 1,600mH +/-3% 0,49Ω wire 1,20mm=17AWG OD-59 / 20mm	1,600	0,490	1,20	17	20	59	20	0,330		
000-1253	Air Core Coil 1,600mH +/-3% 0,950Ω wire 0,80mm=20AWG OD-43 / 15mm	1,600	0,950	0,80	20	15	43	15	0,122		
000-1306	Air Core Coil 1,600mH +/-3% 1,150Ω wire 0,70mm=21AWG OD-38 / 15mm	1,600	1,150	0,70	21	15	38	15	0,091		
000-1425	Air Core Coil 1,600mH +/-3% 0,530Ω wire 1,20mm=17AWG OD-54 / 30mm	1,600	0,530	1,20	17	25	54	30	0,328		
000-1703	Air Core Coil 1,600mH +/-3% 5,290Ω wire 0,30mm=29AWG OD-21 / 15mm	1,600	5,290	0,30	29	15	21	15	0,014		
000-1943	Air Core Coil 1,600mH +/-3% 0,650Ω wire 1,00mm=18AWG OD-52 / 20mm	1,600	0,650	1,00	18	25	52	20	0,211		
000-0842	Air Core Coil 1,620mH +/-3% 2,05Ω wire 0,50mm=24AWG OD-29 / 15mm	1,620	2,050	0,50	24	15	29	15	0,043		
000-0957	Air Core Coil 1,640mH +/-3% 0,530Ω wire 1,20mm=17AWG OD-53 / 30mm	1,640	0,530	1,20	17	25	53	30	0,335		
000-1005	Air Core Coil 1,640mH +/-3% 3,000Ω wire 0,40mm=26AWG OD-29 / 8mm	1,640	3,000	0,40	26	15	29	8	0,025		
000-1176	Air Core Coil 1,640mH +/-3% 0,49Ω wire 1,20mm=17AWG OD-61 / 20mm	1,640	0,490	1,20	17	20	61	20	0,337		
000-1788	Air Core Coil 1,650mH +/-3% 0,410Ω wire 1,40mm=15AWG OD-61 / 30mm	1,650	0,410	1,40	15	25	61	30	0,476		
000-0025	Air Core Coil 1,700mH +/-3% 0,332Ω wire 1,60mm=14AWG OD-69 / 30mm	1,700	0,332	1,60	14	25	69	30	0,670		
000-0125	Air Core Coil 1,700mH +/-3% 0,265Ω wire 1,80mm=13AWG OD-79 / 30mm	1,700	0,265	1,80	13	25	79	30	0,875		
000-0223	Air Core Coil 1,700mH +/-3% 1,45Ω wire 0,63mm=22AWG OD-35 / 15mm	1,700	1,450	0,63	22	15	35	15	0,074		
000-1175	Air Core Coil 1,700mH +/-3% 0,50Ω wire 1,20mm=17AWG OD-61 / 20mm	1,700	0,500	1,20	17	20	61	20	0,342		
000-1252	Air Core Coil 1,700mH +/-3% 0,990Ω wire 0,80mm=20AWG OD-44 / 15mm	1,700	0,990	0,80	20	15	44	15	0,125		
000-1309	Air Core Coil 1,700mH +/-3% 1,200Ω wire 0,70mm=21AWG OD-38 / 15mm	1,700	1,200	0,70	21	15	38	15	0,094		
000-1339	Air Core Coil 1,700mH +/-3% 0,400Ω wire 1,40mm=15AWG OD-76 / 21mm	1,700	0,400	1,40	15	42	76	21	0,490		
000-1465	Air Core Coil 1,700mH +/-3% 2,180Ω wire 0,50mm=24AWG OD-29 / 15mm	1,700	2,180	0,50	24	15	29	15	0,045		
000-1487	Air Core Coil 1,700mH +/-3% 0,42Ω wire 1,40mm=15AWG OD-61 / 30mm	1,700	0,420	1,40	15	25	61	30	0,485		
000-1516	Air Core Coil 1,700mH +/-3% 0,720Ω wire 1,00mm=18AWG OD-46 / 30mm	1,700	0,720	1,00	18	25	46	30	0,225		
000-1789	Air Core Coil 1,700mH +/-3% 0,544Ω wire 1,20mm=17AWG OD-54 / 30mm	1,700	0,544	1,20	17	25	54	30	0,343		
000-1521	Air Core Coil 1,720mH +/-3% 0,660Ω wire 1,00mm=18AWG OD-59 / 15mm	1,720	0,660	1,00	18	25	59	15	0,215		
000-0157	Air Core Coil 1,750mH +/-3% 0,690Ω wire 1,00mm=18AWG OD-59 / 15mm	1,750	0,690	1,00	18	25	59	15	0,215		
000-0235	Air Core Coil 1,750mH +/-3% 0,70Ω wire 1,00mm=18AWG OD-52 / 20mm	1,750	0,700	1,00	18	25	52	20	0,225		
000-0819	Air Core Coil 1,750mH +/-3% 0,970Ω wire 0,80mm=20AWG OD-49 / 15mm	1,750	0,970	0,80	20	25	49	15	0,129		
000-1424	Air Core Coil 1,750mH +/-3% 0,550Ω wire 1,20mm=17AWG OD-55 / 30mm	1,750	0,550	1,20	17	25	55	30	0,348		
000-0026	Air Core Coil 1,800mH +/-3% 0,345Ω wire 1,60mm=14AWG OD-69 / 30mm	1,800	0,345	1,60	14	25	69	30	0,695		
000-0126	Air Core Coil 1,800mH +/-3% 0,275Ω wire 1,80mm=13AWG OD-79 / 30mm	1,800	0,275	1,80	13	25	79	30	0,900		
000-0218	Air Core Coil 1,800mH +/-3% 1,03Ω wire 0,80mm=20AWG OD-45 / 15mm	1,800	1,030	0,80	20	15	45	15	0,134		
000-0713	Air Core Coil 1,800mH +/-3% 0,318Ω wire 1,80mm=13AWG OD-66 / 60mm	1,800	0,318	1,80	13	35	66	60	1,039		
000-0732	Air Core Coil 1,800mH +/-3% 1,48Ω wire 0,63mm=22AWG OD-35 / 15mm	1,800	1,610	0,63	22	15	35	15	0,077		
000-0891	Air Core Coil 1,800mH +/-3% 0,460Ω wire 1,40mm=15AWG OD-49 / 50mm	1,800	0,460	1,40	15	13	49	50	0,554		
000-0935	Air Core Coil 1,800mH +/-3% 0,444Ω wire 1,40mm=15AWG OD-56 / 42mm	1,800	0,444	1,40	15	24	56	42	0,550		
000-1111	Air Core Coil 1,800mH +/-3% 0,51Ω wire 1,20mm=17AWG OD-61 / 20mm	1,800	0,510	1,20	17	20	61	20	0,353		
000-1131	Air Core Coil 1,800mH +/-3% 0,740Ω wire 1,00mm=18AWG OD-46 / 30mm	1,800	0,740	1,00	18	25	46	30	0,235		
000-1132	Air Core Coil 1,800mH +/-3% 0,570Ω wire 1,20mm=17AWG OD-55 / 30mm	1,800	0,570	1,20	17	25	55	30	0,353		



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1250	Air Core Coil	1,800mH +/-3% 3,130Q wire 0,40mm=26AWG OD-30 / 8mm	1,800	3,130	0,40	26	15	30	8	0,026
000-1290	Air Core Coil	1,800mH +/-3% 0,700Q wire 1,00mm=18AWG OD-60 / 15mm	1,800	0,700	1,00	18	25	60	15	0,218
000-1411	Air Core Coil	1,800mH +/-3% 1,380Q wire 0,70mm=21AWG OD-38 / 30mm	1,800	1,380	0,70	21	25	38	30	0,110
000-1466	Air Core Coil	1,800mH +/-3% 1,250Q wire 0,70mm=21AWG OD-40 / 15mm	1,800	1,250	0,70	21	15	40	15	0,097
000-1480	Air Core Coil	1,800mH +/-3% 1,100Q wire 0,80mm=20AWG OD-40 / 30mm	1,800	1,100	0,80	20	25	40	30	0,145
000-1484	Air Core Coil	1,800mH +/-3% 0,420Q wire 1,40mm=15AWG OD-61 / 30mm	1,800	0,420	1,40	15	25	61	30	0,499
000-1868	Air Core Coil	1,800mH +/-3% 2,200Q wire 0,50mm=24AWG OD-29 / 15mm	1,800	2,200	0,50	24	15	29	15	0,046
000-1893	Air Core Coil	1,800mH +/-3% 0,970Q wire 0,80mm=20AWG OD-49 / 15mm	1,800	0,970	0,80	20	25	49	15	0,130
000-1942	Air Core Coil	1,800mH +/-3% 0,700Q wire 1,00mm=18AWG OD-52 / 20mm	1,800	0,700	1,00	18	25	52	20	0,226
000-0159	Air Core Coil	1,820mH +/-3% 3,087Q wire 0,40mm=26AWG OD-31 / 8mm	1,820	3,087	0,40	26	15	31	8	0,026
000-0250	Air Core Coil	1,825mH +/-3% 0,51Q wire 1,20mm=17AWG OD-61 / 20mm	1,825	0,510	1,20	17	20	61	20	0,353
000-0141	Air Core Coil	1,850mH +/-3% 0,280Q wire 1,80mm=13AWG OD-79 / 30mm	1,850	0,280	1,80	13	25	79	30	0,915
000-0160	Air Core Coil	1,850mH +/-3% 0,45Q wire 1,40mm=15AWG OD-57 / 42mm	1,850	0,450	1,40	15	24	57	42	0,543
000-1774	Air Core Coil	1,860mH +/-3% 2,200Q wire 0,50mm=24AWG OD-29 / 15mm	1,860	2,200	0,50	24	15	29	15	0,048
000-1377	Air Core Coil	1,870mH +/-3% 0,760Q wire 1,00mm=18AWG OD-47 / 30mm	1,870	0,760	1,00	18	25	47	30	0,243
000-0127	Air Core Coil	1,900mH +/-3% 0,318Q wire 1,80mm=13AWG OD-66 / 60mm	1,900	0,318	1,80	13	35	66	60	1,039
000-0725	Air Core Coil	1,900mH +/-3% 0,72Q wire 1,00mm=18AWG OD-58 / 15mm	1,900	0,720	1,00	18	15	58	15	0,238
000-0864	Air Core Coil	1,900mH +/-3% 1,11Q wire 0,80mm=20AWG OD-40 / 30mm	1,900	1,110	0,80	20	25	40	30	0,146
000-1159	Air Core Coil	1,900mH +/-3% 1,040Q wire 0,80mm=20AWG OD-49 / 15mm	1,900	1,040	0,80	20	25	49	15	0,134
000-1215	Air Core Coil	1,900mH +/-3% 0,54Q wire 1,20mm=17AWG OD-63 / 20mm	1,900	0,540	1,20	17	20	63	20	0,366
000-1311	Air Core Coil	1,900mH +/-3% 1,260Q wire 0,70mm=21AWG OD-40 / 15mm	1,900	1,260	0,70	21	15	40	15	0,100
000-1733	Air Core Coil	1,900mH +/-3% 3,21Q wire 0,40mm=26AWG OD-30 / 8mm	1,900	3,210	0,40	26	15	30	8	0,026
000-0719	Air Core Coil	1,930mH +/-3% 0,800Q wire 1,00mm=18AWG OD-48 / 30mm	1,930	0,800	1,00	18	25	48	30	0,252
000-0162	Air Core Coil	1,940mH +/-3% 1,30Q wire 0,70mm=21AWG OD-40 / 15mm	1,940	1,300	0,70	21	15	40	15	0,101
000-0027	Air Core Coil	2,000mH +/-3% 0,363Q wire 1,60mm=14AWG OD-72 / 30mm	2,000	0,363	1,60	14	25	72	30	0,743
000-0128	Air Core Coil	2,000mH +/-3% 0,328Q wire 1,80mm=13AWG OD-66 / 60mm	2,000	0,328	1,80	13	35	66	60	1,055
000-0744	Air Core Coil	2,000mH +/-3% 0,74Q wire 1,00mm=18AWG OD-55 / 20mm	2,000	0,740	1,00	18	25	55	20	0,249
000-0745	Air Core Coil	2,000mH +/-3% 0,74Q wire 1,00mm=18AWG OD-61 / 15mm	2,000	0,740	1,00	18	25	61	15	0,244
000-0750	Air Core Coil	2,000mH +/-3% 0,74Q wire 1,00mm=18AWG OD-52 / 20mm	2,000	0,740	1,00	18	20	52	20	0,243
000-0852	Air Core Coil	2,000mH +/-3% 1,61Q wire 0,63mm=22AWG OD-36 / 15mm	2,000	1,610	0,63	22	15	36	15	0,080
000-1062	Air Core Coil	2,000mH +/-3% 1,180Q wire 0,80mm=20AWG OD-40 / 30mm	2,000	1,180	0,80	20	25	40	30	0,154
000-1063	Air Core Coil	2,000mH +/-3% 0,800Q wire 1,00mm=18AWG OD-48 / 30mm	2,000	0,800	1,00	18	25	48	30	0,252
000-1097	Air Core Coil	2,000mH +/-3% 0,460Q wire 1,40mm=15AWG OD-78 / 31mm	2,000	0,460	1,40	15	54	78	31	0,543
000-1166	Air Core Coil	2,000mH +/-3% 0,500Q wire 1,40mm=15AWG OD-56 / 60mm	2,000	0,500	1,40	15	35	56	60	0,613
000-1216	Air Core Coil	2,000mH +/-3% 0,55Q wire 1,20mm=17AWG OD-63 / 20mm	2,000	0,550	1,20	17	20	63	20	0,378
000-1245	Air Core Coil	2,000mH +/-3% 0,444Q wire 1,40mm=15AWG OD-64 / 30mm	2,000	0,444	1,40	15	25	64	30	0,534
000-1254	Air Core Coil	2,000mH +/-3% 0,440Q wire 1,40mm=15AWG OD-79 / 21mm	2,000	0,440	1,40	15	42	79	21	0,505
000-1260	Air Core Coil	2,000mH +/-3% 5,99Q wire 0,30mm=29AWG OD-21 / 15mm	2,000	5,990	0,30	29	15	21	15	0,015
000-1482	Air Core Coil	2,000mH +/-3% 1,330Q wire 0,70mm=21AWG OD-41 / 15mm	2,000	1,330	0,70	21	15	41	15	0,104
000-1711	Air Core Coil	2,000mH +/-3% 3,21Q wire 0,40mm=26AWG OD-31 / 8mm	2,000	3,210	0,40	26	15	31	8	0,027
000-1778	Air Core Coil	2,000mH +/-3% 2,410Q wire 0,50mm=24AWG OD-30 / 15mm	2,000	2,410	0,50	24	15	30	15	0,049
000-1946	Air Core Coil	2,000mH +/-3% 0,590Q wire 1,20mm=17AWG OD-55 / 30mm	2,000	0,590	1,20	17	25	55	30	0,377
000-0129	Air Core Coil	2,100mH +/-3% 0,335Q wire 1,80mm=13AWG OD-66 / 60mm	2,100	0,335	1,80	13	35	66	60	1,100
000-0875	Air Core Coil	2,100mH +/-3% 2,510Q wire 0,50mm=24AWG OD-31 / 15mm	2,100	2,510	0,50	24	15	31	15	0,051
000-1217	Air Core Coil	2,100mH +/-3% 0,56Q wire 1,20mm=17AWG OD-63 / 20mm	2,100	0,560	1,20	17	20	63	20	0,388
000-1255	Air Core Coil	2,100mH +/-3% 1,200Q wire 0,80mm=20AWG OD-41 / 30mm	2,100	1,200	0,80	20	25	41	30	0,154
000-1338	Air Core Coil	2,100mH +/-3% 0,460Q wire 1,40mm=15AWG OD-80 / 21mm	2,100	0,460	1,40	15	42	80	21	0,519
000-1697	Air Core Coil	2,100mH +/-3% 1,360Q wire 0,70mm=21AWG OD-37 / 30mm	2,100	1,360	0,70	21	25	37	30	0,116
000-1844	Air Core Coil	2,100mH +/-3% 0,600Q wire 1,20mm=17AWG OD-55 / 30mm	2,100	0,600	1,20	17	25	55	30	0,390
000-1459	Air Core Coil	2,170mH +/-3% 3,500Q wire 0,40mm=26AWG OD-31 / 8mm	2,170	3,500	0,40	26	15	31	8	0,029
000-0028	Air Core Coil	2,200mH +/-3% 0,385Q wire 1,60mm=14AWG OD-72 / 30mm	2,200	0,385	1,60	14	25	72	30	0,791
000-0130	Air Core Coil	2,200mH +/-3% 0,345Q wire 1,80mm=13AWG OD-66 / 60mm	2,200	0,345	1,80	13	35	66	60	1,146



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno		diametro esterno		Altezza [mm]	Peso [kg]
						ø [mm]	ø [mm]	ø [mm]	ø [mm]		
000-0202	Air Core Coil 2,200mH +/-3% 1,20Q wire 0,80mm=20AWG OD-46 / 15mm	2,200	1,200	0,80	20	15		46		15	0,142
000-0985	Air Core Coil 2,200mH +/-3% 0,39Q wire 1,60mm=14AWG OD-78 / 25mm	2,200	0,390	1,60	14	8		78		25	0,810
000-1033	Air Core Coil 2,200mH +/-3% 2,510Q wire 0,50mm=24AWG OD-31 / 15mm	2,200	2,510	0,50	24	15		31		15	0,052
000-1065	Air Core Coil 2,200mH +/-3% 0,840Q wire 1,00mm=18AWG OD-49 / 30mm	2,200	0,840	1,00	18	25		49		30	0,263
000-1218	Air Core Coil 2,200mH +/-3% 0,59Q wire 1,20mm=17AWG OD-65 / 20mm	2,200	0,590	1,20	17	20		65		20	0,401
000-1246	Air Core Coil 2,200mH +/-3% 0,473Q wire 1,40mm=15AWG OD-64 / 30mm	2,200	0,473	1,40	15	25		64		30	0,568
000-1299	Air Core Coil 2,200mH +/-3% 0,630Q wire 1,20mm=17AWG OD-56 / 30mm	2,200	0,630	1,20	17	25		56		30	0,404
000-1314	Air Core Coil 2,200mH +/-3% 0,490Q wire 1,40mm=15AWG OD-80 / 31mm	2,200	0,490	1,40	15	54		80		31	0,566
000-1316	Air Core Coil 2,200mH +/-3% 1,550Q wire 0,70mm=21AWG OD-39 / 30mm	2,200	1,550	0,70	21	25		39		30	0,121
000-1355	Air Core Coil 2,200mH +/-3% 1,380Q wire 0,70mm=21AWG OD-41 / 15mm	2,200	1,380	0,70	21	15		41		15	0,111
000-1495	Air Core Coil 2,200mH +/-3% 0,520Q wire 1,40mm=15AWG OD-59 / 60mm	2,200	0,520	1,40	15	35		59		60	0,651
000-1564	Air Core Coil 2,200mH +/-3% 1,230Q wire 0,80mm=20AWG OD-41 / 30mm	2,200	1,230	0,80	20	25		41		30	0,163
000-1582	Air Core Coil 2,200mH +/-3% 6,00Q wire 0,30mm=29AWG OD-21 / 15mm	2,200	6,000	0,30	29	15		21		15	0,016
000-1637	Air Core Coil 2,200mH +/-3% 0,700Q wire 1,20mm=17AWG OD-45 / 62mm	2,200	0,700	1,20	17	24		45		62	0,477
000-1638	Air Core Coil 2,200mH +/-3% 0,485Q wire 1,40mm=15AWG OD-65 / 33mm	2,200	0,485	1,40	15	32		65		33	0,569
000-1869	Air Core Coil 2,200mH +/-3% 3,500Q wire 0,40mm=26AWG OD-31 / 8mm	2,200	3,500	0,40	26	15		31		8	0,029
000-1941	Air Core Coil 2,200mH +/-3% 0,800Q wire 1,00mm=18AWG OD-57 / 20mm	2,200	0,800	1,00	18	25		57		20	0,255
000-1730	Air Core Coil 2,250mH +/-3% 0,635Q wire 1,20mm=17AWG OD-56 / 30mm	2,250	0,635	1,20	17	25		56		30	0,402
000-1471	Air Core Coil 2,280mH +/-3% 2,650Q wire 0,50mm=24AWG OD-31 / 15mm	2,280	2,650	0,50	24	15		31		15	0,053
000-0131	Air Core Coil 2,300mH +/-3% 0,355Q wire 1,80mm=13AWG OD-70 / 60mm	2,300	0,355	1,80	13	35		70		60	1,160
000-0705	Air Core Coil 2,300mH +/-3% 1,70Q wire 0,63mm=22AWG OD-37 / 15mm	2,300	1,700	0,63	22	15		37		15	0,089
000-0936	Air Core Coil 2,300mH +/-3% 0,845Q wire 1,00mm=18AWG OD-49 / 30mm	2,300	0,845	1,00	18	25		49		30	0,269
000-1220	Air Core Coil 2,300mH +/-3% 0,60Q wire 1,20mm=17AWG OD-65 / 20mm	2,300	0,600	1,20	17	20		65		20	0,411
000-1821	Air Core Coil 2,300mH +/-3% 0,48Q wire 1,40mm=15AWG OD-65 / 30mm	2,300	0,480	1,40	15	25		65		30	0,587
000-0931	Air Core Coil 2,330mH +/-3% 2,650Q wire 0,50mm=24AWG OD-37 / 15mm	2,330	2,650	0,50	24	25		37		15	0,054
000-1623	Air Core Coil 2,370mH +/-3% 0,850Q wire 1,00mm=18AWG OD-49 / 30mm	2,370	0,850	1,00	18	25		49		30	0,275
000-0029	Air Core Coil 2,400mH +/-3% 0,405Q wire 1,60mm=14AWG OD-75 / 30mm	2,400	0,405	1,60	14	25		75		30	0,830
000-0132	Air Core Coil 2,400mH +/-3% 0,360Q wire 1,80mm=13AWG OD-70 / 60mm	2,400	0,360	1,80	13	35		70		60	1,195
000-0226	Air Core Coil 2,400mH +/-3% 2,65Q wire 0,50mm=24AWG OD-37 / 15mm	2,400	2,650	0,50	24	25		37		15	0,054
000-0799	Air Core Coil 2,400mH +/-3% 6,43Q wire 0,30mm=29AWG OD-22 / 15mm	2,400	6,430	0,30	29	15		22		15	0,018
000-0906	Air Core Coil 2,400mH +/-3% 1,300Q wire 0,80mm=20AWG OD-43 / 30mm	2,400	1,300	0,80	20	25		43		30	0,167
000-1219	Air Core Coil 2,400mH +/-3% 0,61Q wire 1,20mm=17AWG OD-65 / 20mm	2,400	0,610	1,20	17	20		65		20	0,421
000-1473	Air Core Coil 2,400mH +/-3% 0,660Q wire 1,20mm=17AWG OD-56 / 30mm	2,400	0,660	1,20	17	25		56		30	0,415
000-1783	Air Core Coil 2,400mH +/-3% 0,512Q wire 1,40mm=15AWG OD-80 / 31mm	2,400	0,512	1,40	15	54		80		31	0,578
000-0030	Air Core Coil 2,500mH +/-3% 0,410Q wire 1,60mm=14AWG OD-75 / 30mm	2,500	0,410	1,60	14	25		75		30	0,856
000-0133	Air Core Coil 2,500mH +/-3% 0,368Q wire 1,80mm=13AWG OD-70 / 60mm	2,500	0,368	1,80	13	35		70		60	1,200
000-0183	Air Core Coil 2,500mH +/-3% 6,44Q wire 0,30mm=29AWG OD-22 / 15mm	2,500	6,440	0,30	29	15		22		15	0,018
000-0201	Air Core Coil 2,500mH +/-3% 1,28Q wire 0,80mm=20AWG OD-48 / 15mm	2,500	1,280	0,80	20	15		48		15	0,156
000-0717	Air Core Coil 2,500mH +/-3% 0,57Q wire 1,40mm=15AWG OD-60 / 60mm	2,500	0,570	1,40	15	35		60		60	0,707
000-1088	Air Core Coil 2,500mH +/-3% 0,880Q wire 1,00mm=18AWG OD-49 / 30mm	2,500	0,880	1,00	18	25		49		30	0,284
000-1098	Air Core Coil 2,500mH +/-3% 0,520Q wire 1,40mm=15AWG OD-81 / 31mm	2,500	0,520	1,40	15	54		81		31	0,614
000-1118	Air Core Coil 2,500mH +/-3% 2,710Q wire 0,50mm=24AWG OD-37 / 15mm	2,500	2,710	0,50	24	25		37		15	0,056
000-1119	Air Core Coil 2,500mH +/-3% 1,840Q wire 0,63mm=22AWG OD-38 / 15mm	2,500	1,840	0,63	22	15		38		15	0,090
000-1618	Air Core Coil 2,500mH +/-3% 3,91Q wire 0,40mm=26AWG OD-27 / 15mm	2,500	3,910	0,40	26	15		27		15	0,033
000-1673	Air Core Coil 2,500mH +/-3% 0,670Q wire 1,20mm=17AWG OD-56 / 30mm	2,500	0,670	1,20	17	25		56		30	0,432
000-1695	Air Core Coil 2,500mH +/-3% 1,300Q wire 0,80mm=20AWG OD-42 / 30mm	2,500	1,300	0,80	20	25		42		30	0,170
000-1940	Air Core Coil 2,500mH +/-3% 0,850Q wire 1,00mm=18AWG OD-58 / 20mm	2,500	0,850	1,00	18	25		58		20	0,266
000-0946	Air Core Coil 2,530mH +/-3% 0,490Q wire 1,40mm=15AWG OD-77 / 20mm	2,530	0,490	1,40	15	20		77		20	0,599
000-1126	Air Core Coil 2,550mH +/-3% 1,840Q wire 0,63mm=22AWG OD-38 / 15mm	2,550	1,840	0,63	22	15		38		15	0,091
000-1298	Air Core Coil 2,550mH +/-3% 0,680Q wire 1,20mm=17AWG OD-58 / 30mm	2,550	0,680	1,20	17	25		58		30	0,436
000-1503	Air Core Coil 2,550mH +/-3% 0,890Q wire 1,00mm=18AWG OD-50 / 30mm	2,550	0,890	1,00	18	25		50		30	0,285
000-0031	Air Core Coil 2,600mH +/-3% 0,422Q wire 1,60mm=14AWG OD-75 / 30mm	2,600	0,422	1,60	14	25		75		30	0,870

COSTRUIRE

AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-0134	Air Core Coil	2,600mH +/-3% 0,374Ω wire 1,80mm=13AWG OD-70 / 60mm	2,600	0,374	1,80	13	35	70	60	1,230
000-1491	Air Core Coil	2,600mH +/-3% 0,900Ω wire 1,00mm=18AWG OD-50 / 30mm	2,600	0,900	1,00	18	25	50	30	0,286
000-1889	Air Core Coil	2,600mH +/-3% 0,690Ω wire 1,20mm=17AWG OD-58 / 30mm	2,600	0,690	1,20	17	25	58	30	0,440
000-0032	Air Core Coil	2,700mH +/-3% 0,437Ω wire 1,60mm=14AWG OD-75 / 30mm	2,700	0,437	1,60	14	25	75	30	0,890
000-0135	Air Core Coil	2,700mH +/-3% 0,380Ω wire 1,80mm=13AWG OD-70 / 60mm	2,700	0,380	1,80	13	35	70	60	1,257
000-0186	Air Core Coil	2,700mH +/-3% 1,31Ω wire 0,80mm=20AWG OD-52 / 15mm	2,700	1,310	0,80	20	25	52	15	0,161
000-0715	Air Core Coil	2,700mH +/-3% 6,50Ω wire 0,30mm=29AWG OD-25 / 12mm	2,700	5,600	0,30	29	17	25	12	0,016
000-0823	Air Core Coil	2,700mH +/-3% 2,90Ω wire 0,50mm=24AWG OD-28 / 17mm	2,700	2,900	0,50	24	10	28	17	0,059
000-1041	Air Core Coil	2,700mH +/-3% 0,700Ω wire 1,20mm=17AWG OD-58 / 30mm	2,700	0,700	1,20	17	25	58	30	0,443
000-1247	Air Core Coil	2,700mH +/-3% 0,525Ω wire 1,40mm=15AWG OD-69 / 30mm	2,700	0,525	1,40	15	25	69	30	0,631
000-1307	Air Core Coil	2,700mH +/-3% 0,920Ω wire 1,00mm=18AWG OD-51 / 30mm	2,700	0,920	1,00	18	25	51	30	0,295
000-1342	Air Core Coil	2,700mH +/-3% 1,750Ω wire 0,70mm=21AWG OD-39 / 30mm	2,700	1,750	0,70	21	25	39	30	0,134
000-1378	Air Core Coil	2,700mH +/-3% 1,560Ω wire 0,70mm=21AWG OD-42 / 15mm	2,700	1,560	0,70	21	15	42	15	0,124
000-1732	Air Core Coil	2,700mH +/-3% 4,09Ω wire 0,40mm=26AWG OD-26 / 15mm	2,700	4,090	0,40	26	15	26	15	0,034
000-1802	Air Core Coil	2,700mH +/-3% 0,590Ω wire 1,40mm=15AWG OD-61 / 60mm	2,700	0,590	1,40	15	35	61	60	0,711
000-1870	Air Core Coil	2,700mH +/-3% 2,800Ω wire 0,50mm=24AWG OD-32 / 15mm	2,700	2,800	0,50	24	15	32	15	0,056
000-1939	Air Core Coil	2,700mH +/-3% 0,900Ω wire 1,00mm=18AWG OD-58 / 20mm	2,700	0,900	1,00	18	25	58	20	0,285
000-0063	Air Core Coil	2,750mH +/-3% 0,91Ω wire 1,00mm=18AWG OD-51 / 30mm	2,750	0,910	1,00	18	25	51	30	0,309
000-0217	Air Core Coil	2,750mH +/-3% 0,39Ω wire 1,80mm=13AWG OD-72 / 60mm	2,750	0,390	1,80	13	35	72	60	1,278
000-0796	Air Core Coil	2,750mH +/-3% 0,43Ω wire 1,60mm=14AWG OD-79 / 30mm	2,750	0,430	1,60	14	25	79	30	0,912
000-0049	Air Core Coil	2,800mH +/-3% 0,443Ω wire 1,60mm=14AWG OD-78 / 30mm	2,800	0,443	1,60	14	25	78	30	0,920
000-0200	Air Core Coil	2,800mH +/-3% 1,36Ω wire 0,80mm=20AWG OD-48 / 15mm	2,800	1,360	0,80	20	15	48	15	0,166
000-0938	Air Core Coil	2,800mH +/-3% 0,720Ω wire 1,20mm=17AWG OD-60 / 30mm	2,800	0,720	1,20	17	25	60	30	0,455
000-0971	Air Core Coil	2,800mH +/-3% 0,95Ω wire 1,00mm=18AWG OD-50 / 30mm	2,800	0,950	1,00	18	25	50	30	0,310
000-1595	Air Core Coil	2,800mH +/-3% 0,600Ω wire 1,40mm=15AWG OD-61 / 60mm	2,800	0,600	1,40	15	35	61	60	0,726
000-1978	Air Core Coil	2,800mH +/-3% 3,500Ω wire 0,50mm=24AWG OD-22 / 35mm	2,800	3,500	0,50	24	7	22	35	0,075
000-0062	Air Core Coil	2,900mH +/-3% 0,450Ω wire 1,60mm=14AWG OD-78 / 30mm	2,900	0,450	1,60	14	25	78	30	0,930
000-0224	Air Core Coil	2,900mH +/-3% 2,90Ω wire 0,50mm=24AWG OD-32 / 15mm	2,900	2,900	0,50	24	15	32	15	0,061
000-0726	Air Core Coil	2,900mH +/-3% 0,93Ω wire 1,00mm=18AWG OD-65 / 15mm	2,900	0,930	1,00	18	15	65	15	0,307
000-0865	Air Core Coil	2,900mH +/-3% 0,680Ω wire 1,20mm=17AWG OD-59 / 30mm	2,900	0,680	1,20	17	25	59	30	0,467
000-0900	Air Core Coil	2,900mH +/-3% 0,630Ω wire 1,40mm=15AWG OD-61 / 60mm	2,900	0,630	1,40	15	35	61	60	0,740
000-0990	Air Core Coil	2,900mH +/-3% 0,95Ω wire 1,00mm=18AWG OD-52 / 30mm	2,900	0,950	1,00	18	25	52	30	0,316
000-0996	Air Core Coil	2,900mH +/-3% 2,100Ω wire 0,63mm=22AWG OD-53 / 21mm	2,900	2,100	0,63	22	42	53	21	0,106
000-1221	Air Core Coil	2,900mH +/-3% 1,43Ω wire 0,80mm=20AWG OD-43 / 30mm	2,900	1,430	0,80	20	25	43	30	0,188
000-0033	Air Core Coil	3,000mH +/-3% 0,46Ω wire 1,60mm=14AWG OD-78 / 30mm	3,000	0,460	1,60	14	25	78	30	0,943
000-0136	Air Core Coil	3,000mH +/-3% 0,400Ω wire 1,80mm=13AWG OD-74 / 60mm	3,000	0,400	1,80	13	35	74	60	1,331
000-0947	Air Core Coil	3,000mH +/-3% 0,540Ω wire 1,40mm=15AWG OD-77 / 20mm	3,000	0,540	1,40	15	10	77	20	0,709
000-1068	Air Core Coil	3,000mH +/-3% 0,990Ω wire 1,00mm=18AWG OD-51 / 30mm	3,000	0,990	1,00	18	25	51	30	0,312
000-1107	Air Core Coil	3,000mH +/-3% 4,350Ω wire 0,40mm=26AWG OD-27 / 15mm	3,000	4,350	0,40	26	15	27	15	0,036
000-1259	Air Core Coil	3,000mH +/-3% 7,600Ω wire 0,30mm=29AWG OD-22 / 15mm	3,000	7,600	0,30	29	15	22	15	0,019
000-1392	Air Core Coil	3,000mH +/-3% 1,680Ω wire 0,70mm=21AWG OD-43 / 15mm	3,000	1,680	0,70	21	15	43	15	0,131
000-1560	Air Core Coil	3,000mH +/-3% 0,750Ω wire 1,20mm=17AWG OD-60 / 30mm	3,000	0,750	1,20	17	25	60	30	0,470
000-1779	Air Core Coil	3,000mH +/-3% 3,040Ω wire 0,50mm=24AWG OD-32 / 15mm	3,000	3,040	0,50	24	15	32	15	0,062
000-1891	Air Core Coil	3,000mH +/-3% 2,220Ω wire 0,63mm=22AWG OD-38 / 30mm	3,000	2,220	0,63	22	25	38	30	0,113
000-1894	Air Core Coil	3,000mH +/-3% 0,640Ω wire 1,40mm=15AWG OD-61 / 60mm	3,000	0,640	1,40	15	35	61	60	0,758
000-1913	Air Core Coil	3,000mH +/-3% 1,380Ω wire 0,80mm=20AWG OD-44 / 30mm	3,000	1,380	0,80	20	25	44	30	0,196
000-0833	Air Core Coil	3,100mH +/-3% 0,46Ω wire 1,60mm=14AWG OD-82 / 30mm	3,100	0,460	1,60	14	25	82	30	0,958
000-0735	Air Core Coil	3,150mH +/-3% 0,56Ω wire 1,40mm=15AWG OD-84 / 20mm	3,150	0,560	1,40	15	25	84	20	0,707
000-1592	Air Core Coil	3,160mH +/-3% 1,46Ω wire 0,80mm=20AWG OD-45 / 21mm	3,160	1,460	0,80	20	15	45	21	0,192
000-0189	Air Core Coil	3,200mH +/-3% 1,04Ω wire 1,00mm=18AWG OD-52 / 30mm	3,200	1,040	1,00	18	25	52	30	0,325
000-0884	Air Core Coil	3,200mH +/-3% 3,100Ω wire 0,50mm=24AWG OD-33 / 15mm	3,200	3,100	0,50	24	15	33	15	0,061
000-1422	Air Core Coil	3,200mH +/-3% 0,780Ω wire 1,20mm=17AWG OD-60 / 30mm	3,200	0,780	1,20	17	25	60	30	0,488



JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno		diametro esterno		Altezza [mm]	Peso [kg]
						ø [mm]	ø [mm]	ø [mm]	ø [mm]		
000-1583	Air Core Coil 3,200mH +/-3% 7,70Ω wire 0,30mm=29AWG OD-22 / 15mm	3,200	7,700	0,30	29	15	22	15	0,020		
000-1672	Air Core Coil 3,200mH +/-3% 0,650Ω wire 1,40mm=15AWG OD-61 / 60mm	3,200	0,650	1,40	15	35	61	60	0,796		
000-1705	Air Core Coil 3,200mH +/-3% 1,46Ω wire 0,80mm=20AWG OD-45 / 21mm	3,200	1,460	0,80	20	15	45	21	0,193		
000-0034	Air Core Coil 3,300mH +/-3% 0,482Ω wire 1,60mm=14AWG OD-81 / 30mm	3,300	0,482	1,60	14	25	81	30	1,000		
000-0137	Air Core Coil 3,300mH +/-3% 0,420Ω wire 1,80mm=13AWG OD-75 / 60mm	3,300	0,420	1,80	13	35	75	60	1,385		
000-0238	Air Core Coil 3,300mH +/-3% 4,40Ω wire 0,40mm=26AWG OD-34,5 / 8mm	3,300	4,400	0,40	26	15	34,5	8	0,038		
000-1025	Air Core Coil 3,300mH +/-3% 0,800Ω wire 1,20mm=17AWG OD-63 / 30mm	3,300	0,800	1,20	17	25	63	30	0,496		
000-1070	Air Core Coil 3,300mH +/-3% 1,040Ω wire 1,00mm=18AWG OD-54 / 30mm	3,300	1,040	1,00	18	25	54	30	0,326		
000-1199	Air Core Coil 3,300mH +/-3% 0,615Ω wire 1,40mm=15AWG OD-72 / 30mm	3,300	0,615	1,40	15	25	72	30	0,648		
000-1200	Air Core Coil 3,300mH +/-3% 1,760Ω wire 0,70mm=21AWG OD-45 / 15mm	3,300	1,760	0,70	21	15	45	15	0,138		
000-1423	Air Core Coil 3,300mH +/-3% 1,480Ω wire 0,80mm=20AWG OD-46 / 21mm	3,300	1,480	0,80	20	15	46	21	0,197		
000-1494	Air Core Coil 3,300mH +/-3% 0,660Ω wire 1,40mm=15AWG OD-61 / 60mm	3,300	0,660	1,40	15	35	61	60	0,817		
000-1871	Air Core Coil 3,300mH +/-3% 3,090Ω wire 0,50mm=24AWG OD-33 / 15mm	3,300	3,090	0,50	24	15	33	15	0,063		
000-1872	Air Core Coil 3,300mH +/-3% 4,600Ω wire 0,40mm=26AWG OD-28 / 15mm	3,300	4,600	0,40	26	15	28	15	0,037		
000-1050	Air Core Coil 3,350mH +/-3% 1,950Ω wire 0,70mm=21AWG OD-40 / 30mm	3,350	1,950	0,70	21	25	40	30	0,153		
000-0035	Air Core Coil 3,400mH +/-3% 0,488Ω wire 1,60mm=14AWG OD-81 / 30mm	3,400	0,488	1,60	14	25	81	30	1,033		
000-0154	Air Core Coil 3,450mH +/-3% 0,49Ω wire 1,60mm=14AWG OD-82 / 30mm	3,450	0,490	1,60	14	25	82	30	1,037		
000-0960	Air Core Coil 3,450mH +/-3% 3,170Ω wire 0,50mm=24AWG OD-33 / 15mm	3,450	3,170	0,50	24	15	33	15	0,066		
000-0998	Air Core Coil 3,450mH +/-3% 4,750Ω wire 0,40mm=26AWG OD-28 / 15mm	3,450	4,750	0,40	26	15	28	15	0,038		
000-0070	Air Core Coil 3,500mH +/-3% 0,45Ω wire 1,80mm=13AWG OD-77 / 60mm	3,500	0,450	1,80	13	35	77	60	1,458		
000-0088	Air Core Coil 3,500mH +/-3% 0,78Ω wire 1,20mm=17AWG OD-64 / 30mm	3,500	0,780	1,20	17	25	64	30	0,533		
000-0091	Air Core Coil 3,500mH +/-3% 0,60Ω wire 1,40mm=15AWG OD-75 / 30mm	3,500	0,600	1,40	15	25	75	30	0,756		
000-0153	Air Core Coil 3,500mH +/-3% 0,55Ω wire 1,60mm=14AWG OD-82 / 30mm	3,500	0,552	1,60	14	25	82	30	1,038		
000-0711	Air Core Coil 3,500mH +/-3% 7,86Ω wire 0,30mm=29AWG OD-23 / 15mm	3,500	7,860	0,30	29	15	23	15	0,022		
000-1312	Air Core Coil 3,500mH +/-3% 1,760Ω wire 0,70mm=21AWG OD-46 / 15mm	3,500	1,760	0,70	21	15	46	15	0,141		
000-1493	Air Core Coil 3,500mH +/-3% 0,690Ω wire 1,40mm=15AWG OD-64 / 60mm	3,500	0,690	1,40	15	35	64	60	0,818		
000-1709	Air Core Coil 3,500mH +/-3% 1,57Ω wire 0,80mm=20AWG OD-45 / 30mm	3,500	1,570	0,80	20	25	45	30	0,206		
000-1975	Air Core Coil 3,500mH +/-3% 1,100Ω wire 1,00mm=18AWG OD-54 / 30mm	3,500	1,100	1,00	18	25	54	30	0,339		
000-1996	Air Core Coil 3,580mH +/-3% 0,820Ω wire 1,20mm=17AWG OD-63 / 30mm	3,580	0,820	1,20	17	25	63	30	0,533		
000-0046	Air Core Coil 3,600mH +/-3% 0,583Ω wire 1,60mm=14AWG OD-70 / 60mm	3,600	0,583	1,60	14	35	70	60	1,157		
000-0167	Air Core Coil 3,600mH +/-3% 1,08Ω wire 1,00mm=18AWG OD-54 / 30mm	3,600	1,080	1,00	18	25	54	30	0,351		
000-0700	Air Core Coil 3,600mH +/-3% 2,20Ω wire 0,63mm=22AWG OD-42 / 15mm	3,600	2,320	0,63	22	15	42	15	0,117		
000-1584	Air Core Coil 3,600mH +/-3% 7,87Ω wire 0,30mm=29AWG OD-23 / 15mm	3,600	7,870	0,30	29	15	23	15	0,021		
000-0185	Air Core Coil 3,700mH +/-3% 5,05Ω wire 0,40mm=26AWG OD-28 / 15mm	3,700	5,050	0,40	26	15	28	15	0,041		
000-1704	Air Core Coil 3,700mH +/-3% 3,250Ω wire 0,50mm=24AWG OD-33 / 15mm	3,700	3,250	0,50	24	15	33	15	0,069		
000-0094	Air Core Coil 3,800mH +/-3% 0,47Ω wire 1,80mm=13AWG OD-77 / 60mm	3,800	0,470	1,80	13	35	77	60	1,549		
000-1222	Air Core Coil 3,800mH +/-3% 1,200Ω wire 1,00mm=18AWG OD-54 / 30mm	3,800	1,200	1,00	18	25	54	30	0,370		
000-1800	Air Core Coil 3,800mH +/-3% 0,63Ω wire 1,40mm=15AWG OD-74 / 30mm	3,800	0,630	1,40	15	25	74	30	0,783		
000-0036	Air Core Coil 3,900mH +/-3% 0,593Ω wire 1,60mm=14AWG OD-70 / 60mm	3,900	0,593	1,60	14	35	70	60	1,164		
000-1127	Air Core Coil 3,900mH +/-3% 2,320Ω wire 0,63mm=22AWG OD-43 / 15mm	3,900	2,320	0,63	22	15	43	15	0,120		
000-1139	Air Core Coil 3,900mH +/-3% 3,450Ω wire 0,50mm=24AWG OD-35 / 15mm	3,900	3,450	0,50	24	15	35	15	0,069		
000-1241	Air Core Coil 3,900mH +/-3% 0,660Ω wire 1,40mm=15AWG OD-74 / 30mm	3,900	0,660	1,40	15	25	74	30	0,790		
000-1326	Air Core Coil 3,900mH +/-3% 2,100Ω wire 0,70mm=21AWG OD-41 / 30mm	3,900	2,100	0,70	21	25	41	30	0,165		
000-1713	Air Core Coil 3,900mH +/-3% 0,825Ω wire 1,20mm=17AWG OD-64 / 30mm	3,900	0,825	1,20	17	25	64	30	0,556		
000-1873	Air Core Coil 3,900mH +/-3% 5,070Ω wire 0,40mm=26AWG OD-29 / 15mm	3,900	5,070	0,40	26	15	29	15	0,041		
000-1930	Air Core Coil 3,900mH +/-3% 1,200Ω wire 1,00mm=18AWG OD-54 / 30mm	3,900	1,200	1,00	18	25	54	30	0,370		
000-1944	Air Core Coil 3,900mH +/-3% 0,700Ω wire 1,40mm=15AWG OD-64 / 60mm	3,900	0,700	1,40	15	35	64	60	0,871		
000-1458	Air Core Coil 3,940mH +/-3% 5,070Ω wire 0,40mm=26AWG OD-29 / 15mm	3,940	5,070	0,40	26	15	29	15	0,042		
000-0047	Air Core Coil 4,000mH +/-3% 0,60Ω wire 1,60mm=14AWG OD-70 / 60mm	4,000	0,603	1,60	14	35	70	60	1,230		
000-0172	Air Core Coil 4,000mH +/-3% 0,48Ω wire 1,80mm=13AWG OD-78 / 60mm	4,000	0,480	1,80	13	35	78	60	1,583		
000-0181	Air Core Coil 4,000mH +/-3% 0,83Ω wire 1,20mm=17AWG OD-65 / 30mm	4,000	0,830	1,20	17	25	65	30	0,572		
000-0885	Air Core Coil 4,000mH +/-3% 3,610Ω wire 0,50mm=24AWG OD-35 / 15mm	4,000	3,610	0,50	24	15	35	15	0,072		



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1099	Air Core Coil	4,000mH +/-3% 0,720Q wire 1,40mm=15AWG OD-66 / 60mm	4,000	0,720	1,40	15	35	66	60	0,891
000-1185	Air Core Coil	4,000mH +/-3% 2,030Q wire 0,70mm=21AWG OD-47 / 15mm	4,000	2,030	0,70	21	15	47	15	0,152
000-1605	Air Core Coil	4,000mH +/-3% 3,950Q wire 0,50mm=24AWG OD-29 / 27mm	4,000	3,950	0,50	24	15	29	27	0,081
000-1793	Air Core Coil	4,000mH +/-3% 2,190Q wire 0,80mm=20AWG OD-35 / 50mm	4,000	1,980	0,80	20	13	35	50	0,271
000-1920	Air Core Coil	4,000mH +/-3% 2,200Q wire 0,70mm=21AWG OD-43 / 30mm	4,000	2,200	0,70	21	25	43	30	0,163
000-1956	Air Core Coil	4,000mH +/-3% 1,21Q wire 1,00mm=18AWG OD-55 / 30mm	4,000	1,210	1,00	18	25	55	30	0,375
000-1981	Air Core Coil	4,000mH +/-3% 1,700Q wire 0,80mm=20AWG OD-45 / 30mm	4,000	1,700	0,80	20	25	45	30	0,220
000-0707	Air Core Coil	4,100mH +/-3% 3,610Q wire 0,50mm=24AWG OD-35 / 15mm	4,100	3,610	0,50	24	15	35	15	0,072
000-1639	Air Core Coil	4,100mH +/-3% 0,660Q wire 1,40mm=15AWG OD-73 / 33mm	4,100	0,660	1,40	15	32	73	33	0,800
000-1798	Air Core Coil	4,100mH +/-3% 8,60Q wire 0,30mm=29AWG OD-24 / 15mm	4,100	8,600	0,30	29	15	24	15	0,023
000-0090	Air Core Coil	4,200mH +/-3% 0,50Q wire 1,80mm=13AWG OD-79 / 60mm	4,200	0,500	1,80	13	35	79	60	1,600
000-1393	Air Core Coil	4,200mH +/-3% 2,190Q wire 0,70mm=21AWG OD-41 / 30mm	4,200	2,190	0,70	21	25	41	30	0,172
000-0724	Air Core Coil	4,300mH +/-3% 0,51Q wire 1,80mm=13AWG OD-82 / 60mm	4,300	0,510	1,80	13	35	82	60	1,650
000-1664	Air Core Coil	4,300mH +/-3% 1,800Q wire 0,80mm=20AWG OD-47 / 30mm	4,300	1,800	0,80	20	25	47	30	0,231
000-0059	Air Core Coil	4,400mH +/-3% 0,52Q wire 1,80mm=13AWG OD-82 / 60mm	4,400	0,520	1,80	13	35	82	60	1,650
000-1671	Air Core Coil	4,400mH +/-3% 2,230Q wire 0,70mm=21AWG OD-43 / 30mm	4,400	2,230	0,70	21	25	43	30	0,176
000-1043	Air Core Coil	4,430mH +/-3% 1,240Q wire 1,00mm=18AWG OD-55 / 30mm	4,430	1,240	1,00	18	25	55	30	0,382
000-0143	Air Core Coil	4,400mH +/-3% 0,780Q wire 1,40mm=15AWG OD-59 / 62mm	4,500	0,780	1,40	15	24	59	62	0,970
000-0857	Air Core Coil	4,500mH +/-3% 1,85Q wire 0,80mm=20AWG OD-46 / 30mm	4,500	1,850	0,80	20	25	46	30	0,246
000-0923	Air Core Coil	4,500mH +/-3% 0,930Q wire 1,20mm=17AWG OD-68 / 30mm	4,500	0,930	1,20	17	25	68	30	0,604
000-0932	Air Core Coil	4,500mH +/-3% 3,850Q wire 0,50mm=24AWG OD-35 / 15mm	4,500	3,850	0,50	24	15	35	15	0,076
000-1468	Air Core Coil	4,500mH +/-3% 0,800Q wire 1,40mm=15AWG OD-58 / 62mm	4,500	0,800	1,40	15	24	58	62	0,980
000-1585	Air Core Coil	4,500mH +/-3% 8,84Q wire 0,30mm=29AWG OD-24 / 15mm	4,500	8,840	0,30	29	15	24	15	0,024
000-1957	Air Core Coil	4,500mH +/-3% 1,250Q wire 1,00mm=18AWG OD-57 / 30mm	4,500	1,250	1,00	18	25	57	30	0,396
000-0037	Air Core Coil	4,700mH +/-3% 0,650Q wire 1,60mm=14AWG OD-73 / 60mm	4,700	0,650	1,60	14	35	73	60	1,334
000-0880	Air Core Coil	4,700mH +/-3% 1,900Q wire 0,80mm=20AWG OD-46 / 30mm	4,700	1,900	0,80	20	25	46	30	0,250
000-1187	Air Core Coil	4,700mH +/-3% 0,760Q wire 1,40mm=15AWG OD-76 / 30mm	4,700	0,760	1,40	15	25	76	30	0,870
000-1240	Air Core Coil	4,700mH +/-3% 1,300Q wire 1,00mm=18AWG OD-57 / 30mm	4,700	1,300	1,00	18	25	57	30	0,402
000-1519	Air Core Coil	4,700mH +/-3% 0,820Q wire 1,40mm=15AWG OD-60 / 62mm	4,700	0,820	1,40	15	24	60	62	1,000
000-1520	Air Core Coil	4,700mH +/-3% 2,330Q wire 0,70mm=21AWG OD-43 / 30mm	4,700	2,330	0,70	21	25	43	30	0,182
000-1587	Air Core Coil	4,700mH +/-3% 0,800Q wire 1,40mm=15AWG OD-66 / 60mm	4,700	0,800	1,40	15	35	66	60	0,976
000-1607	Air Core Coil	4,700mH +/-3% 4,300Q wire 0,50mm=24AWG OD-30 / 27mm	4,700	4,300	0,50	24	15	30	27	0,088
000-1714	Air Core Coil	4,700mH +/-3% 0,970Q wire 1,20mm=17AWG OD-68 / 30mm	4,700	0,970	1,20	17	25	68	30	0,622
000-1780	Air Core Coil	4,700mH +/-3% 3,910Q wire 0,50mm=24AWG OD-36 / 15mm	4,700	3,910	0,50	24	15	36	15	0,080
000-1935	Air Core Coil	4,700mH +/-3% 2,190Q wire 0,80mm=20AWG OD-36 / 50mm	4,700	2,190	0,80	20	13	36	50	0,282
000-0800	Air Core Coil	4,770mH +/-3% 10,100Q wire 0,30mm=29AWG OD-25 / 15mm	4,770	10,100	0,30	29	15	25	15	0,026
000-0234	Air Core Coil	4,800mH +/-3% 0,53Q wire 1,80mm=13AWG OD-82 / 60mm	4,800	0,530	1,80	13	35	82	60	1,722
000-0720	Air Core Coil	4,800mH +/-3% 0,95Q wire 1,20mm=17AWG OD-68 / 30mm	4,800	0,950	1,20	17	25	69	30	0,630
000-1486	Air Core Coil	4,800mH +/-3% 0,830Q wire 1,40mm=15AWG OD-60 / 62mm	4,800	0,830	1,40	15	24	60	62	1,026
000-0138	Air Core Coil	5,000mH +/-3% 0,54Q wire 1,80mm=13AWG OD-82 / 60mm	5,000	0,540	1,80	13	35	82	60	1,775
000-0147	Air Core Coil	5,000mH +/-3% 3,06Q wire 0,63mm=22AWG OD-40 / 30mm	5,000	3,060	0,63	22	25	40	30	0,148
000-1258	Air Core Coil	5,000mH +/-3% 10,100Q wire 0,30mm=29AWG OD-25 / 15mm	5,000	10,100	0,30	29	15	25	15	0,026
000-1501	Air Core Coil	5,000mH +/-3% 0,990Q wire 1,20mm=17AWG OD-69 / 30mm	5,000	0,990	1,20	17	25	69	30	0,640
000-1604	Air Core Coil	5,000mH +/-3% 4,450Q wire 0,50mm=24AWG OD-30 / 27mm	5,000	4,450	0,50	24	15	30	27	0,102
000-1614	Air Core Coil	5,000mH +/-3% 0,830Q wire 1,40mm=15AWG OD-66 / 60mm	5,000	0,830	1,40	15	35	66	60	1,009
000-1874	Air Core Coil	5,000mH +/-3% 9,00Q wire 0,30mm=29AWG OD-27 / 12mm	5,000	9,000	0,30	29	17	27	12	0,026
000-1892	Air Core Coil	5,000mH +/-3% 1,300Q wire 1,00mm=18AWG OD-60 / 30mm	5,000	1,300	1,00	18	25	60	30	0,419
000-1938	Air Core Coil	5,000mH +/-3% 2,450Q wire 0,70mm=21AWG OD-43 / 30mm	5,000	2,450	0,70	21	25	43	30	0,190
000-1982	Air Core Coil	5,000mH +/-3% 1,950Q wire 0,80mm=20AWG OD-48 / 30mm	5,000	1,950	0,80	20	25	48	30	0,259
000-0937	Air Core Coil	5,100mH +/-3% 1,010Q wire 1,20mm=17AWG OD-70 / 30mm	5,100	1,010	1,20	17	25	70	30	0,655
000-1346	Air Core Coil	5,100mH +/-3% 8,800Q wire 0,30mm=29AWG OD-30 / 8mm	5,100	8,800	0,30	29	15	30	8	0,025
000-1351	Air Core Coil	5,100mH +/-3% 10,200Q wire 0,30mm=29AWG OD-25 / 15mm	5,100	10,200	0,30	29	15	25	15	0,026



induttanze in aria

in ordine di valore (mH)

		diametro interno diametro esterno									
codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	ø [mm]	ø [mm]	Altezza [mm]	Peso [kg]	
000-0095	Air Core Coil	5,150mH +/-3% 0,65Ω wire 1,60mm=14AWG OD-74 / 60mm	5,150	0,650	1,60	14	35	74	60	1,410	
000-0093	Air Core Coil	5,300mH +/-3% 0,66Ω wire 1,60mm=14AWG OD-74 / 60mm	5,300	0,660	1,60	14	35	74	60	1,481	
000-0089	Air Core Coil	5,400mH +/-3% 0,57Ω wire 1,80mm=13AWG OD-85 / 60mm	5,400	0,573	1,80	13	35	85	60	1,840	
000-0701	Air Core Coil	5,400mH +/-3% 0,870Ω wire 1,40mm=15AWG OD-69 / 60mm	5,400	0,870	1,40	15	35	69	60	1,075	
000-0710	Air Core Coil	5,400mH +/-3% 0,69Ω wire 1,60mm=14AWG OD-74 / 60mm	5,400	0,690	1,60	14	35	74	60	1,444	
000-0805	Air Core Coil	5,400mH +/-3% 1,33Ω wire 1,00mm=18AWG OD-78 / 15mm	5,400	1,330	1,00	18	25	78	15	0,438	
000-0184	Air Core Coil	5,500mH +/-3% 1,37Ω wire 1,00mm=18AWG OD-78 / 15mm	5,500	1,370	1,00	18	25	78	15	0,437	
000-0718	Air Core Coil	5,500mH +/-3% 0,58Ω wire 1,80mm=13AWG OD-82 / 60mm	5,500	0,580	1,80	13	35	82	60	1,900	
000-0861	Air Core Coil	5,500mH +/-3% 0,69Ω wire 1,60mm=14AWG OD-76 / 60mm	5,500	0,690	1,60	14	35	76	60	1,462	
000-1980	Air Core Coil	5,500mH +/-3% 3,29Ω wire 0,63mm=22AWG OD-41 / 30mm	5,500	3,290	0,63	22	25	41	30	0,165	
000-0038	Air Core Coil	5,600mH +/-3% 0,700Ω wire 1,60mm=14AWG OD-76 / 60mm	5,600	0,700	1,60	14	35	76	60	1,466	
000-1500	Air Core Coil	5,600mH +/-3% 1,170Ω wire 1,20mm=17AWG OD-60 / 60mm	5,600	1,170	1,20	17	35	60	60	0,777	
000-1538	Air Core Coil	5,600mH +/-3% 1,400Ω wire 1,00mm=18AWG OD-60 / 30mm	5,600	1,400	1,00	18	25	60	30	0,456	
000-1546	Air Core Coil	5,600mH +/-3% 0,870Ω wire 1,40mm=15AWG OD-69 / 60mm	5,600	0,870	1,40	15	35	69	60	1,075	
000-1611	Air Core Coil	5,600mH +/-3% 4,740Ω wire 0,50mm=24AWG OD-31 / 27mm	5,600	4,740	0,50	24	15	31	27	0,100	
000-1652	Air Core Coil	5,600mH +/-3% 2,100Ω wire 0,80mm=20AWG OD-48 / 30mm	5,600	2,100	0,80	20	25	48	30	0,277	
000-1653	Air Core Coil	5,600mH +/-3% 2,650Ω wire 0,70mm=21AWG OD-44 / 30mm	5,600	2,650	0,70	21	25	44	30	0,205	
000-1349	Air Core Coil	5,700mH +/-3% 10,80Ω wire 0,30mm=29AWG OD-25 / 15mm	5,700	10,800	0,30	29	15	25	15	0,028	
000-0161	Air Core Coil	5,780mH +/-3% 0,90Ω wire 1,40mm=15AWG OD-69 / 60mm	5,780	0,900	1,40	15	35	69	60	1,091	
000-0804	Air Core Coil	5,800mH +/-3% 3,29Ω wire 0,63mm=22AWG OD-41 / 30mm	5,800	3,290	0,63	22	25	41	30	0,165	
000-0970	Air Core Coil	5,800mH +/-3% 1,68Ω wire 1,00mm=18AWG OD-54 / 60mm	5,800	1,680	1,00	18	35	54	60	0,529	
000-0148	Air Core Coil	6,000mH +/-3% 3,29Ω wire 0,63mm=22AWG OD-41 / 30mm	6,000	3,290	0,63	22	25	41	30	0,165	
000-0182	Air Core Coil	6,000mH +/-3% 4,85Ω wire 0,50mm=24AWG OD-32 / 27mm	6,000	4,850	0,50	24	15	32	27	0,101	
000-0811	Air Core Coil	6,000mH +/-3% 0,68Ω wire 1,60mm=14AWG OD-95 / 30mm	6,000	0,680	1,60	14	25	95	30	1,419	
000-0945	Air Core Coil	6,000mH +/-3% 2,720Ω wire 0,70mm=21AWG OD-45 / 30mm	6,000	2,720	0,70	21	25	45	30	0,218	
000-0992	Air Core Coil	6,000mH +/-3% 0,730Ω wire 1,60mm=14AWG OD-76 / 60mm	6,000	0,730	1,60	14	35	76	60	1,550	
000-1167	Air Core Coil	6,000mH +/-3% 0,910Ω wire 1,40mm=15AWG OD-71 / 60mm	6,000	0,910	1,40	15	35	71	60	1,202	
000-1225	Air Core Coil	6,000mH +/-3% 1,220Ω wire 1,20mm=17AWG OD-61 / 60mm	6,000	1,220	1,20	17	35	61	60	0,812	
000-1348	Air Core Coil	6,000mH +/-3% 11,100Ω wire 0,30mm=29AWG OD-26 / 15mm	6,000	11,100	0,30	29	15	26	15	0,029	
000-1508	Air Core Coil	6,000mH +/-3% 1,660Ω wire 1,00mm=18AWG OD-54 / 60mm	6,000	1,660	1,00	18	35	54	60	0,533	
000-1934	Air Core Coil	6,000mH +/-3% 7,64Ω wire 0,80mm=26AWG OD-33 / 30mm	6,000	7,640	0,40	26	25	30	30	0,064	
000-1958	Air Core Coil	6,000mH +/-3% 1,450Ω wire 1,00mm=18AWG OD-61 / 30mm	6,000	1,450	1,00	18	25	61	30	0,462	
000-0983	Air Core Coil	6,150mH +/-3% 0,75Ω wire 1,60mm=14AWG OD-78 / 60mm	6,150	0,750	1,60	14	35	78	60	1,560	
000-0039	Air Core Coil	6,200mH +/-3% 0,750Ω wire 1,60mm=14AWG OD-78 / 60mm	6,200	0,750	1,60	14	35	78	60	1,566	
000-0893	Air Core Coil	6,200mH +/-3% 0,930Ω wire 1,40mm=15AWG OD-71 / 60mm	6,200	0,930	1,40	15	35	71	60	1,205	
000-1329	Air Core Coil	6,200mH +/-3% 2,740Ω wire 0,70mm=21AWG OD-45 / 30mm	6,200	2,740	0,70	21	25	45	30	0,213	
000-1499	Air Core Coil	6,200mH +/-3% 1,250Ω wire 1,20mm=17AWG OD-62 / 60mm	6,200	1,250	1,20	17	35	62	60	0,820	
000-1610	Air Core Coil	6,200mH +/-3% 5,050Ω wire 0,50mm=24AWG OD-32 / 27mm	6,200	5,050	0,50	24	15	32	27	0,102	
000-0933	Air Core Coil	6,400mH +/-3% 5,120Ω wire 0,50mm=24AWG OD-32 / 27mm	6,400	5,120	0,50	24	15	32	27	0,105	
000-1347	Air Core Coil	6,400mH +/-3% 11,600Ω wire 0,30mm=29AWG OD-26 / 15mm	6,400	11,600	0,30	29	15	26	15	0,030	
000-1630	Air Core Coil	6,400mH +/-3% 0,950Ω wire 1,40mm=15AWG OD-71 / 60mm	6,400	0,950	1,40	15	35	71	60	1,215	
000-1768	Air Core Coil	6,400mH +/-3% 1,540Ω wire 1,00mm=18AWG OD-61 / 30mm	6,400	1,540	1,00	18	25	61	30	0,480	
000-0086	Air Core Coil	6,500mH +/-3% 0,95Ω wire 1,40mm=15AWG OD-71 / 60mm	6,500	0,950	1,40	15	35	71	60	1,215	
000-0740	Air Core Coil	6,600mH +/-3% 1,280Ω wire 1,20mm=17AWG OD-63 / 60mm	6,600	1,280	1,20	17	35	63	60	0,861	
000-0993	Air Core Coil	6,600mH +/-3% 0,780Ω wire 1,60mm=14AWG OD-79 / 60mm	6,600	0,780	1,60	14	35	79	60	1,640	
000-1586	Air Core Coil	6,600mH +/-3% 10,97Ω wire 0,30mm=29AWG OD-26 / 15mm	6,600	10,970	0,30	29	15	26	15	0,030	
000-1666	Air Core Coil	6,600mH +/-3% 1,580Ω wire 1,00mm=18AWG OD-62 / 30mm	6,600	1,580	1,00	18	25	62	30	0,488	
000-0040	Air Core Coil	6,800mH +/-3% 0,790Ω wire 1,60mm=14AWG OD-79 / 60mm	6,800	0,790	1,60	14	35	79	60	1,650	
000-0087	Air Core Coil	6,800mH +/-3% 0,66Ω wire 1,80mm=13AWG OD-89 / 60mm	6,800	0,660	1,80	13	35	89	60	2,121	
000-1333	Air Core Coil	6,800mH +/-3% 2,850Ω wire 0,70mm=21AWG OD-45 / 30mm	6,800	2,850	0,70	21	25	45	30	0,224	
000-1498	Air Core Coil	6,800mH +/-3% 1,300Ω wire 1,20mm=17AWG OD-62 / 60mm	6,800	1,300	1,20	17	35	62	60	0,870	
000-1547	Air Core Coil	6,800mH +/-3% 0,960Ω wire 1,40mm=15AWG OD-71 / 60mm	6,800	0,960	1,40	15	35	71	60	1,218	

COSTRUIRE

AUDIO

JANTZEN AUDIO

induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1609	Air Core Coil	6,800mH +/-3% 5,280Ω wire 0,50mm=24AWG OD-33 / 27mm	6,800	5,280	0,50	24	15	33	27	0,105
000-1706	Air Core Coil	6,800mH +/-3% 2,300Ω wire 0,80mm=20AWG OD-52 / 30mm	6,800	2,300	0,80	20	25	52	30	0,312
000-1707	Air Core Coil	6,800mH +/-3% 1,590Ω wire 1,00mm=18AWG OD-63 / 30mm	6,800	1,590	1,00	18	25	63	30	0,496
000-0240	Air Core Coil	7,000mH +/-3% 2,30Ω wire 0,80mm=20AWG OD-55 / 21mm	7,000	2,300	0,80	20	15	55	21	0,303
000-0934	Air Core Coil	7,000mH +/-3% 3,080Ω wire 0,70mm=21AWG OD-46 / 30mm	7,000	3,080	0,70	21	25	46	30	0,226
000-1257	Air Core Coil	7,000mH +/-3% 11,99Ω wire 0,30mm=29AWG OD-26 / 15mm	7,000	11,990	0,30	29	15	26	15	0,031
000-1497	Air Core Coil	7,000mH +/-3% 1,330Ω wire 1,20mm=17AWG OD-64 / 60mm	7,000	1,330	1,20	17	35	64	60	0,885
000-1506	Air Core Coil	7,000mH +/-3% 0,980Ω wire 1,40mm=15AWG OD-74 / 60mm	7,000	0,980	1,40	15	35	74	60	1,238
000-1598	Air Core Coil	7,000mH +/-3% 5,28Ω wire 0,50mm=24AWG OD-33 / 27mm	7,000	5,280	0,50	24	15	33	27	0,107
000-1959	Air Core Coil	7,000mH +/-3% 1,600Ω wire 1,00mm=18AWG OD-63 / 30mm	7,000	1,600	1,00	18	25	63	30	0,504
000-0069	Air Core Coil	7,200mH +/-3% 0,83Ω wire 1,60mm=14AWG OD-79 / 60mm	7,200	0,830	1,60	14	35	79	60	1,720
000-0708	Air Core Coil	7,200mH +/-3% 5,810Ω wire 0,50mm=24AWG OD-33 / 27mm	7,200	5,810	0,50	24	15	33	27	0,116
000-0733	Air Core Coil	7,200mH +/-3% 1,34Ω wire 1,20mm=17AWG OD-65 / 60mm	7,200	1,340	1,20	17	35	65	60	0,906
000-1588	Air Core Coil	7,200mH +/-3% 11,44Ω wire 0,30mm=29AWG OD-25 / 15mm	7,200	11,440	0,30	29	15	25	15	0,031
000-0041	Air Core Coil	7,500mH +/-3% 0,830Ω wire 1,60mm=14AWG OD-79 / 60mm	7,500	0,830	1,60	14	35	79	60	1,749
000-0709	Air Core Coil	7,500mH +/-3% 10,60Ω wire 0,40mm=26AWG OD-31 / 62mm	7,500	10,600	0,40	26	24	31	62	0,093
000-1541	Air Core Coil	7,500mH +/-3% 12,500Ω wire 0,30mm=29AWG OD-26 / 15mm	7,500	12,500	0,30	29	15	26	15	0,032
000-0704	Air Core Coil	7,800mH +/-3% 1,07Ω wire 1,40mm=15AWG OD-72 / 60mm	7,800	1,070	1,40	15	35	72	60	1,312
000-0851	Air Core Coil	7,800mH +/-3% 3,81Ω wire 0,63mm=22AWG OD-43 / 30mm	7,800	3,810	0,63	22	25	43	30	0,190
000-0048	Air Core Coil	8,000mH +/-3% 0,870Ω wire 1,60mm=14AWG OD-82 / 60mm	8,000	0,870	1,60	14	35	82	60	1,826
000-0212	Air Core Coil	8,000mH +/-3% 0,70Ω wire 1,80mm=13AWG OD-92 / 60mm	8,000	0,700	1,80	13	35	92	60	2,323
000-1271	Air Core Coil	8,000mH +/-3% 2,540Ω wire 0,80mm=20AWG OD-54 / 30mm	8,000	2,540	0,80	20	25	54	30	0,324
000-1427	Air Core Coil	8,000mH +/-3% 1,240Ω wire 1,40mm=15AWG OD-61 / 75mm	8,000	1,240	1,40	15	20	61	75	1,456
000-1502	Air Core Coil	8,000mH +/-3% 1,420Ω wire 1,20mm=17AWG OD-64 / 60mm	8,000	1,420	1,20	17	35	64	60	0,942
000-1613	Air Core Coil	8,000mH +/-3% 1,080Ω wire 1,40mm=15AWG OD-74 / 60mm	8,000	1,080	1,40	15	35	74	60	1,300
000-1785	Air Core Coil	8,000mH +/-3% 5,810Ω wire 0,50mm=24AWG OD-33 / 27mm	8,000	5,810	0,50	24	15	33	27	0,116
000-1960	Air Core Coil	8,000mH +/-3% 1,750Ω wire 1,00mm=18AWG OD-66 / 30mm	8,000	1,750	1,00	18	25	66	30	0,549
000-0042	Air Core Coil	8,200mH +/-3% 0,870Ω wire 1,60mm=14AWG OD-82 / 60mm	8,200	0,870	1,60	14	35	82	60	1,852
000-0230	Air Core Coil	8,200mH +/-3% 1,43Ω wire 1,20mm=17AWG OD-66 / 60mm	8,200	1,430	1,20	17	35	66	60	0,965
000-1023	Air Core Coil	8,200mH +/-3% 3,350Ω wire 0,70mm=21AWG OD-48 / 30mm	8,200	3,350	0,70	21	25	48	30	0,248
000-1238	Air Core Coil	8,200mH +/-3% 1,780Ω wire 1,00mm=18AWG OD-66 / 30mm	8,200	1,780	1,00	18	25	66	30	0,568
000-1602	Air Core Coil	8,200mH +/-3% 1,100Ω wire 1,40mm=15AWG OD-74 / 60mm	8,200	1,100	1,40	15	35	74	60	1,328
000-1608	Air Core Coil	8,200mH +/-3% 5,830Ω wire 0,50mm=24AWG OD-33 / 27mm	8,200	5,830	0,50	24	15	33	27	0,119
000-1933	Air Core Coil	8,400mH +/-3% 9,15Ω wire 0,40mm=26AWG OD-34 / 30mm	8,400	9,150	0,40	26	25	34	30	0,076
000-0233	Air Core Coil	9,000mH +/-3% 3,33Ω wire 0,70mm=21AWG OD-48 / 30mm	9,000	3,330	0,70	21	25	48	30	0,264
000-0836	Air Core Coil	9,000mH +/-3% 5,11Ω wire 0,63mm=22AWG OD-44 / 60mm	9,000	5,110	0,63	22	35	44	60	0,240
000-0909	Air Core Coil	9,000mH +/-3% 1,180Ω wire 1,40mm=15AWG OD-74 / 60mm	9,000	1,180	1,40	15	35	74	60	1,435
000-1442	Air Core Coil	9,000mH +/-3% 1,530Ω wire 1,20mm=17AWG OD-66 / 60mm	9,000	1,530	1,20	17	35	66	60	0,995
000-1932	Air Core Coil	9,000mH +/-3% 9,33Ω wire 0,40mm=26AWG OD-35 / 30mm	9,000	9,330	0,40	26	25	35	30	0,078
000-1961	Air Core Coil	9,000mH +/-3% 1,850Ω wire 1,00mm=18AWG OD-69 / 30mm	9,000	1,850	1,00	18	25	69	30	0,599
000-0043	Air Core Coil	9,100mH +/-3% 0,920Ω wire 1,60mm=14AWG OD-82 / 60mm	9,100	0,920	1,60	14	35	82	60	1,951
000-0144	Air Core Coil	10,000mH +/-3% 0,76Ω wire 1,80mm=13AWG OD-95 / 60mm	10,000	0,760	1,80	13	35	95	60	2,500
000-0222	Air Core Coil	10,000mH +/-3% 1,00Ω wire 1,60mm=14AWG OD-83 / 62mm	10,000	1,000	1,60	14	24	83	62	2,096
000-0728	Air Core Coil	10,000mH +/-3% 10,12Ω wire 0,40mm=26AWG OD-35 / 30mm	10,000	10,120	0,40	26	25	34	30	0,085
000-1248	Air Core Coil	10,000mH +/-3% 3,700Ω wire 0,70mm=21AWG OD-49 / 30mm	10,000	3,700	0,70	21	25	49	30	0,280
000-1504	Air Core Coil	10,000mH +/-3% 13,000Ω wire 0,30mm=29AWG OD-28 / 15mm	10,000	13,000	0,30	29	15	28	15	0,038
000-1549	Air Core Coil	10,000mH +/-3% 2,880Ω wire 0,80mm=20AWG OD-55 / 30mm	10,000	2,880	0,80	20	25	55	30	0,363
000-1601	Air Core Coil	10,000mH +/-3% 1,200Ω wire 1,40mm=15AWG OD-76 / 60mm	10,000	1,200	1,40	15	35	76	60	1,489
000-1681	Air Core Coil	10,000mH +/-3% 1,660Ω wire 1,20mm=17AWG OD-67 / 60mm	10,000	1,660	1,20	17	35	67	60	1,095
000-1781	Air Core Coil	10,000mH +/-3% 4,230Ω wire 0,70mm=21AWG OD-48 / 60mm	10,000	4,230	0,70	21	35	48	60	0,331
000-1962	Air Core Coil	10,000mH +/-3% 1,950Ω wire 1,00mm=18AWG OD-70 / 30mm	10,000	1,950	1,00	18	25	70	30	0,624
000-0220	Air Core Coil	11,000mH +/-3% 0,90Ω wire 1,80mm=13AWG OD-91 / 66mm	11,000	0,900	1,80	13	25	91	66	2,884



induttanze in aria

in ordine di valore (mH)

codice		Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno ø [mm]	diametro esterno ø [mm]	Altezza [mm]	Peso [kg]
000-1418	Air Core Coil	11,000mH +/-3% 1,720Q wire 1,20mm=17AWG OD-68 / 60mm	11,000	1,720	1,20	17	35	68	60	1,098
000-1698	Air Core Coil	11,000mH +/-3% 4,450Q wire 0,70mm=21AWG OD-48 / 60mm	11,000	4,450	0,70	21	35	48	60	0,345
000-1749	Air Core Coil	11,000mH +/-3% 5,550Q wire 0,63mm=22AWG OD-46 / 60mm	11,000	5,550	0,63	22	35	46	60	0,275
000-0158	Air Core Coil	11,200mH +/-3% 2,198Q wire 1,00mm=18AWG OD-68 / 30mm	11,200	2,198	1,00	18	25	68	30	0,660
000-0897	Air Core Coil	11,600mH +/-3% 2,860Q wire 1,00mm=18AWG OD-53 / 100mm	11,600	2,860	1,00	18	33	53	100	0,882
000-0211	Air Core Coil	12,000mH +/-3% 1,32Q wire 1,40mm=15AWG OD-79 / 60mm	12,000	1,320	1,40	15	35	79	60	1,648
000-0856	Air Core Coil	12,000mH +/-3% 3,29Q wire 0,80mm=20AWG OD-57 / 30mm	12,000	3,290	0,80	20	25	57	30	0,422
000-0926	Air Core Coil	12,000mH +/-3% 5,800Q wire 0,63mm=22AWG OD-46 / 60mm	12,000	5,800	0,63	22	35	46	60	0,285
000-0964	Air Core Coil	12,000mH +/-3% 4,71Q wire 0,70mm=21AWG OD-49 / 60mm	12,000	4,710	0,70	21	35	49	60	0,360
000-1715	Air Core Coil	12,000mH +/-3% 1,910Q wire 1,20mm=17AWG OD-69 / 60mm	12,000	1,910	1,20	17	35	69	60	1,100
000-1971	Air Core Coil	12,000mH +/-3% 2,230Q wire 1,00mm=18AWG OD-72 / 30mm	12,000	2,230	1,00	18	25	72	30	0,700
000-0731	Air Core Coil	12,700mH +/-3% 2,080Q wire 1,20mm=17AWG OD-70 / 60mm	12,700	2,080	1,20	17	35	70	60	1,176
000-1037	Air Core Coil	13,000mH +/-3% 9,260Q wire 0,50mm=24AWG OD-42 / 60mm	13,000	9,260	0,50	24	35	42	60	0,183
000-1687	Air Core Coil	13,000mH +/-3% 4,970Q wire 0,70mm=21AWG OD-50 / 60mm	13,000	4,970	0,70	21	35	50	60	0,374
000-0956	Air Core Coil	13,280mH +/-3% 3,170Q wire 1,00mm=18AWG OD-55 / 100mm	13,280	3,170	1,00	18	33	55	100	0,992
000-1594	Air Core Coil	13,500mH +/-3% 7,80Q wire 0,50mm=24AWG OD-41 / 30mm	13,500	7,800	0,50	24	25	41	30	0,159
000-0872	Air Core Coil	14,000mH +/-3% 2,450Q wire 1,00mm=18AWG OD-73 / 30mm	14,000	2,450	1,00	18	25	73	30	0,747
000-1719	Air Core Coil	14,000mH +/-3% 2,080Q wire 1,20mm=17AWG OD-70 / 60mm	14,000	2,080	1,20	17	35	70	60	1,176
000-1770	Air Core Coil	14,400mH +/-3% 7,840Q wire 0,50mm=24AWG OD-40 / 30mm	14,400	7,840	0,50	24	25	40	30	0,164
000-1720	Air Core Coil	14,500mH +/-3% 2,150Q wire 1,20mm=17AWG OD-71 / 60mm	14,500	2,150	1,20	17	35	71	60	1,204
000-0196	Air Core Coil	14,800mH +/-3% 1,250Q wire 1,60mm=14AWG OD-90 / 62mm	14,800	1,250	1,60	14	24	90	62	2,550
000-0892	Air Core Coil	15,000mH +/-3% 13,300Q wire 0,40mm=26AWG OD-36 / 30mm	15,000	13,300	0,40	26	25	36	30	0,099
000-0963	Air Core Coil	15,000mH +/-3% 1,250Q wire 1,60mm=14AWG OD-91 / 62mm	15,000	1,250	1,60	14	24	91	62	2,560
000-1476	Air Core Coil	15,000mH +/-3% 15,720Q wire 0,40mm=26AWG OD-40 / 60mm	15,000	15,720	0,40	26	35	40	60	0,130
000-1561	Air Core Coil	15,000mH +/-3% 5,270Q wire 0,70mm=21AWG OD-51 / 60mm	15,000	5,270	0,70	21	35	51	60	0,412
000-1591	Air Core Coil	15,000mH +/-3% 2,44Q wire 1,00mm=18AWG OD-73 / 30mm	15,000	2,440	1,00	18	25	73	30	0,814
000-1716	Air Core Coil	15,000mH +/-3% 2,180Q wire 1,20mm=17AWG OD-72 / 60mm	15,000	2,180	1,20	17	35	72	60	1,224
000-0841	Air Core Coil	16,000mH +/-3% 5,52Q wire 0,70mm=21AWG OD-51 / 60mm	16,000	5,520	0,70	21	35	51	60	0,433
000-0873	Air Core Coil	16,000mH +/-3% 2,660Q wire 1,00mm=18AWG OD-75 / 30mm	16,000	2,660	1,00	18	25	75	30	0,837
000-1721	Air Core Coil	16,000mH +/-3% 2,220Q wire 1,20mm=17AWG OD-73 / 60mm	16,000	2,220	1,20	17	35	73	60	1,259
000-0197	Air Core Coil	16,800mH +/-3% 2,660Q wire 1,00mm=18AWG OD-75 / 30mm	16,800	2,660	1,00	18	25	75	30	0,867
000-0943	Air Core Coil	17,000mH +/-3% 5,780Q wire 0,70mm=21AWG OD-52 / 60mm	17,000	5,780	0,70	21	35	52	60	0,443
000-1722	Air Core Coil	17,000mH +/-3% 2,310Q wire 1,20mm=17AWG OD-75 / 60mm	17,000	2,310	1,20	17	35	75	60	1,301
000-0840	Air Core Coil	18,000mH +/-3% 2,81Q wire 1,00mm=18AWG OD-77 / 30mm	18,000	2,810	1,00	18	25	77	30	0,898
000-1699	Air Core Coil	18,000mH +/-3% 5,780Q wire 0,70mm=21AWG OD-52 / 60mm	18,000	5,780	0,70	21	35	52	60	0,455
000-1717	Air Core Coil	18,000mH +/-3% 2,400Q wire 1,20mm=17AWG OD-75 / 60mm	18,000	2,400	1,20	17	35	75	60	1,341
000-0253	Air Core Coil	18,500mH +/-3% 2,80Q wire 1,00mm=18AWG OD-80 / 30mm	18,500	2,800	1,00	18	25	80	30	0,931
000-1723	Air Core Coil	19,000mH +/-3% 2,470Q wire 1,20mm=17AWG OD-77 / 60mm	19,000	2,470	1,20	17	35	77	60	1,385
000-0809	Air Core Coil	20,000mH +/-3% 3,04Q wire 1,00mm=18AWG OD-80 / 30mm	20,000	3,040	1,00	18	25	80	30	0,969
000-1718	Air Core Coil	20,000mH +/-3% 2,550Q wire 1,20mm=17AWG OD-77 / 60mm	20,000	2,550	1,20	17	35	77	60	1,426
000-1748	Air Core Coil	20,000mH +/-3% 5,100Q wire 0,80mm=20AWG OD-57 / 60mm	20,000	5,100	0,80	20	35	57	60	0,632
000-1765	Air Core Coil	20,000mH +/-3% 6,380Q wire 0,70mm=21AWG OD-52 / 60mm	20,000	6,380	0,70	21	35	52	60	0,480
000-1792	Air Core Coil	20,000mH +/-3% 1,85Q wire 1,40mm=15AWG OD-89 / 60mm	20,000	1,850	1,40	15	35	89	60	2,240
000-0815	Air Core Coil	21,000mH +/-3% 8,06Q wire 0,63mm=22AWG OD-51 / 60mm	21,000	8,060	0,63	22	35	51	60	0,388
000-1724	Air Core Coil	21,000mH +/-3% 2,620Q wire 1,20mm=17AWG OD-79 / 60mm	21,000	2,620	1,20	17	35	79	60	1,475
000-0097	Air Core Coil	21,500mH +/-3% 4,96Q wire 0,80mm=20AWG OD-59 / 60mm	21,500	4,960	0,80	20	35	59	60	0,692
000-0810	Air Core Coil	22,000mH +/-3% 3,17Q wire 1,00mm=18AWG OD-83 / 30mm	22,000	3,170	1,00	18	25	83	30	1,024
000-0871	Air Core Coil	22,000mH +/-3% 6,650Q wire 0,70mm=21AWG OD-53 / 60mm	22,000	6,650	0,70	21	35	53	60	0,505
000-0915	Air Core Coil	22,000mH +/-3% 8,100Q wire 0,63mm=22AWG OD-51 / 60mm	22,000	8,100	0,63	22	35	51	60	0,401
000-0975	Air Core Coil	22,000mH +/-3% 10,60Q wire 0,50mm=24AWG OD-40 / 32mm	22,000	10,600	0,50	24	17	40	33	0,210
000-1725	Air Core Coil	22,000mH +/-3% 2,680Q wire 1,20mm=17AWG OD-79 / 60mm	22,000	2,628	1,20	17	35	79	60	1,512
000-1726	Air Core Coil	23,000mH +/-3% 2,730Q wire 1,20mm=17AWG OD-79 / 60mm	23,000	2,730	1,20	17	35	79	60	1,547



induttanze in aria

in ordine di valore (mH)

codice	Descrizione	induttanza [mH]	DCR [Ω]	diametro filo [mm]	AWG	diametro interno diametro esterno		Altezza [mm]	Peso [kg]
						ø [mm]	ø [mm]		
000-1727	Air Core Coil 24,000mH +/-3% 2,790Ω wire 1,20mm=17AWG OD-79 / 60mm	24,000	2,790	1,20	17	35	79	60	1,589
000-0830	Air Core Coil 25,000mH +/-3% 19,71Ω wire 0,40mm=26AWG OD-28 / 47mm	25,000	19,710	0,40	26	10	28	47	0,159
000-1659	Air Core Coil 25,000mH +/-3% 3,700Ω wire 1,00mm=18AWG OD-70 / 60mm	25,000	3,700	1,00	18	35	70	60	1,149
000-1663	Air Core Coil 25,000mH +/-3% 7,000Ω wire 0,70mm=21AWG OD-55 / 60mm	25,000	7,000	0,70	21	35	55	60	0,545
000-0876	Air Core Coil 27,000mH +/-3% 13,830Ω wire 0,50mm=24AWG OD-47 / 30mm	27,000	13,830	0,50	24	25	47	30	0,225
000-1690	Air Core Coil 27,000mH +/-3% 7,300Ω wire 0,70mm=21AWG OD-55 / 60mm	27,000	7,300	0,70	21	35	55	60	0,566
000-0898	Air Core Coil 28,000mH +/-3% 5,970Ω wire 0,80mm=20AWG OD-60 / 60mm	28,000	5,970	0,80	20	35	60	60	0,761
000-0236	Air Core Coil 30,000mH +/-3% 8,72Ω wire 0,70mm=21AWG OD-46 / 75mm	30,000	8,720	0,70	21	20	46	75	0,679
000-0959	Air Core Coil 30,000mH +/-3% 8,000Ω wire 0,70mm=21AWG OD-56 / 60mm	30,000	8,000	0,70	21	35	56	60	0,597
000-0806	Air Core Coil 32,000mH +/-3% 3,90Ω wire 1,00mm=18AWG OD-93 / 30mm	32,000	3,900	1,00	18	25	93	30	1,295
000-0742	Air Core Coil 33,000mH +/-3% 4,20Ω wire 1,00mm=18AWG OD-93 / 30mm	33,000	4,200	1,00	18	25	93	30	1,304
000-0850	Air Core Coil 34,000mH +/-3% 6,82Ω wire 0,80mm=20AWG OD-64 / 60mm	34,000	6,820	0,80	20	35	64	60	0,859
000-0874	Air Core Coil 34,000mH +/-3% 4,180Ω wire 1,00mm=18AWG OD-92 / 30mm	34,000	4,180	1,00	18	25	92	30	1,260
000-1662	Air Core Coil 35,000mH +/-3% 9,960Ω wire 0,70mm=21AWG OD-46 / 75mm	35,000	9,960	0,70	21	20	46	75	0,712
000-0979	Air Core Coil 39,000mH +/-3% 24,76Ω wire 0,40mm=26AWG OD-32 / 47mm	39,000	24,760	0,40	26	10	32	47	0,206
000-0216	Air Core Coil 40,000mH +/-3% 7,50Ω wire 0,80mm=20AWG OD-59 / 66mm	40,000	7,500	0,80	20	25	59	66	0,996
000-0816	Air Core Coil 50,000mH +/-3% 8,72Ω wire 0,80mm=20AWG OD-61 / 66mm	50,000	8,720	0,80	20	25	61	66	1,110
000-0229	Air Core Coil 65,000mH +/-3% 22,220Ω wire 0,50mm=24AWG OD-52 / 60mm	65,000	22,220	0,50	24	35	52	60	0,444
000-0817	Air Core Coil 100,000mH +/-3% 12,61Ω wire 0,80mm=20AWG OD-72 / 66mm	100,000	12,610	0,80	20	25	72	66	1,628